



# Edging and Reinforcing Tape

## 8411

Technical Data

January, 2009

**Product Description** 3M™ Edging and Reinforcing Tape 8411 is a transparent polyester film tape for many permanent edging and reinforcing types of applications.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester	Acrylic	Transparent	72 yds. (66 m)

**Typical Physical Properties** **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	30 oz./in. width (33 N/100 mm)	D-3330
Tensile Strength at Break:	26 lbs./in. width (456 N/100 mm)	D-3759
Elongation at Break:	120%	D-3759
Backing Thickness:	1.0 mil (0.025 mm)	D-3652
Total Tape Thickness:	1.5 mil (0.04 mm)	D-3652
Temperature Use Range:	Dimensionally stable over temperature from -60° to 300°F (-50° to 149°C)	
Water Vapor Transmission Rate:	1.6 gms H <sub>2</sub> O/100 in. <sup>2</sup> /24 hrs. (24.8 g <sup>2</sup> /24 hr.)	D-3833

### Features

- Strong polyester backing for good edge tear resistance.
- Long aging, non-yellowing, pressure sensitive acrylic adhesive.
- Thinness of tape helps keep pages flat.
- High transparency for ease of reading thru tape.

### Application Ideas

- Paper edging.
- Hole reinforcing.
- Many miscellaneous applications where a high degree of clarity and permanence are desired.

# 3M™ Edging and Reinforcing Tape

8411

---

**Storage** Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 50% R.H. in the original carton.

---

**Shelf Life** To obtain best performance, use this product within 18 months from date of manufacture.

---

**Product Use** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

**Warranty, Limited Remedy, and Disclaimer** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

**Limitation of Liability** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**ISO 9001:2000**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



## Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M company.  
Printed in U.S.A.

©3M 2009 70-0703-0623-1 (1/09)