



**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

# 2450 MHz Ceramic Band Pass Filter

**Part Number: AE2450CB1798**



## Electrical Specifications

**Center Frequency(CF):** 2450 MHz  
**1 dB Bandwidth(BW):** 115 MHz Min  
**Passband Frequency (PB):** 2392.5-2507.5 MHz  
**Insertion Loss @ CF :** 3 dB Max  
**VSWR in BW:** 1.7:1 Max.  
**Rejection1:** 55 dB Min.@ DC-2300 MHz  
**Rejection2:** 45 dB Min. @ 2600 MHz  
**Power Handling:** 1 Watt  
**Input / output Impedance:** 50 Ohms

## Mechanical


**Mounting Method:** SMT  
**Dimensions:** 30 x 12 x 5.5 mm

## Environmental

**Operating Temperature:** -35°C to +85°C  
**Storage Temperature:** -50°C to +100 °C  
**Shock:** 10G. 11ms  
**Vibration:** 10G 0.5 to 200 Hz

**This Product is RoHS Compliant.**

## Outline Drawing:



Tolerance: +/-0.01 inches [ +/- 0.3mm]

Angles: +/- 1 Deg.

\*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.

\*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.