0.25 METER LENGTH



Connector A 132182 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-316DB Continuity/Hi-Pot Connector B 172171 N-Type Plug Straight Brass White Bronze + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

[Connector A			Cable			Connector B		
	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132182 SMA R/A PLUG RG316DB 500 SMA Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold None Brass Gold 12.4 GHz SMA Plug Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-316DS RG-316DB - ST 0.102 ST Double Braid 0.102 50 Ohm None Continuity Hi-Pot 0.25 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	172171 N-Type PLUG RG3 N-Type Plug Straight Solder Standard 50 Ohm Cable Brass White Bronze None Brass Gold 11 GHz N-Type Plug Straigh 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CODY			PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUG IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA	DRAWING MAY CONTAIN PATENTED OR RIETARY INFORMATION AND MUST NOT BE USED ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE IT MAY NOT BE REPRODUCED OR TRANSCRIBED NY FORM WITHOUT THE WRITTEN CONSENT OF 'OM CABLE INC. ACCEPTANCE OF THIS DRAWING BLISHES AND AGREEMENT OF THE FOREGOING.		Title: SMA-RA-PL/N-ST-PL G316D 0.25M Part No: Q-3502M000R.25M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-3502M000R.25M

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-PL/N-ST-PL G316D 0.25M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank