

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

- . - .

© COPYRIGHT - TE Connectivity Ltd.

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B1	CUTTING BURR DETAILS ADDED	19NOV2018	RK	PS

1. MATERIAL:
 HOUSING: POLYAMIDE 6 UL94V-2.
 COLOR: NATURAL (OFF WHITE).
 TUBULAR CONTACT: BRASS, TIN PLATED.
 SCREW: M5, STEEL, ZINC PLATED W/ NON-HEXAVALENT CHROMATE (CHROME III).

2. ELECTRICAL:
 CURRENT RATING: 65A, 600V.
 WIRE RANGE: 6-14 AWG.

3. CONTINUOUS WORKING TEMP.: 100°C MAX.

4. CUTTING PROJECTION CAN BE ON BOTH SIDES DEPENDING ON CUTTING LOCATION.

5. CUTTING BURR MAX. 1mm ALLOWED.

	PHILLIPS HEAD	145.0	170.7	12	TSB200012K/12PM	2-1776892-2
	PHILLIPS HEAD	72.5	98.2	7	TSB20007K/7PM	1-1776892-7
OBSOLETE	PHILLIPS HEAD	43.5	69.2	5	TSB20005K/5PM	1-1776892-5
OBSOLETE	SLOTTED HEAD	145.0	170.7	12	TSB200012K/12	1-1776892-2
	SLOTTED HEAD	72.5	98.2	7	TSB20007K/7	1776892-7
OBSOLETE	SLOTTED HEAD	43.5	69.2	5	TSB20005K/5	1776892-5
	SCREW TYPE	DIM B	DIM A	NO OF POS	T & B PART NUMBER	TE PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN S SCHLEGEL 9/25/06

CHK C RICHARD 9/25/06

APVD C RICHARD 9/25/06

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

TE Connectivity Ltd.

NAME
14.5MM PITCH, 65A HIGH VOLTAGE VERSION

-

-

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C=1776892 -

SCALE NTS SHEET 1 OF 1 REV B1

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± 0.3
2 PLC	± 0.25
3 PLC	± -
4 PLC	± -
ANGLES	± 2'

MATERIAL

SEE NOTES

FINISH

SEE NOTES

1470-19 (1/15)