# CQ4300LF-B-R

Datasheet revision 1.3 www.chipquik.com

# Liquid Flux Alcohol-Based No-Clean Water-Washable in 6ml (0.2oz) Refillable Pen with Tip + Brush

### **Product Highlights**

No-Clean and Water-Washable
Low solids
Alcohol-Based
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with isopropyl alcohol (IPA) or hot water (60°C+)
Can be used with Leaded and Lead-Free applications



#### **Specifications**

Flux Type: No-Clean Water-Washable Liquid (for Leaded and Lead-Free applications)

Flux Classification: ORL0 Specific Gravity: 0.8

**RoHS 3 and REACH compliant** 

Packaging: Refillable Pen 6ml (0.2oz) - Two Ends: Tip and Brush Shelf Life: Refrigerated >24 months, Unrefrigerated >24 months

#### **Dispensing**

Gently press tip into work piece (depress tip) to dispense.

#### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

#### **Transportation**

This product requires ground shipping. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground will not impact this product's stated shelf life.

## Cleaning

This is a no-clean and water-washable liquid flux, post-use cleaning is not required. However, if post-use cleaning is desired, the non-corrosive non-conductive residue can be cleaned off using hot water (60°C+) or isopropyl alcohol (IPA).

#### **Conforms to the following Industry Standards:**

J-STD-004B, Amendment 1 (Solder Fluxes): RoHS 3 Directive 2015/863/EU:

Yes Yes

1