

# IRF7424GPbF

HEXFET® Power MOSFET


- Ultra Low On-Resistance
- P-Channel MOSFET
- Surface Mount
- Available in Tape & Reel
- Lead-Free
- Halogen-Free

<b>V<sub>DSS</sub></b>	<b>R<sub>DS(on)</sub> max (mΩ)</b>	<b>I<sub>D</sub></b>
<b>-30V</b>	13.5@V <sub>GS</sub> = -10V	-11A
	22@V <sub>GS</sub> = -4.5V	-8.8A

## Description

These P-Channel MOSFETs from International Rectifier utilize advanced processing techniques to achieve the extremely low on-resistance per silicon area. This benefit provides the designer with an extremely efficient device for use in battery and load management applications..

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infrared, or wave soldering techniques.



## Absolute Maximum Ratings

	Parameter	Max.	Units
V <sub>DS</sub>	Drain- Source Voltage	-30	V
I <sub>D</sub> @ T <sub>A</sub> = 25°C	Continuous Drain Current, V <sub>GS</sub> @ -10V	-11	
I <sub>D</sub> @ T <sub>A</sub> = 70°C	Continuous Drain Current, V <sub>GS</sub> @ -10V	-9.3	A
I <sub>DM</sub>	Pulsed Drain Current ①	-47	
P <sub>D</sub> @ T <sub>A</sub> = 25°C	Power Dissipation ③	2.5	W
P <sub>D</sub> @ T <sub>A</sub> = 70°C	Power Dissipation ③	1.6	
	Linear Derating Factor	20	mW/°C
V <sub>GS</sub>	Gate-to-Source Voltage	± 20	V
T <sub>J</sub> , T <sub>STG</sub>	Junction and Storage Temperature Range	-55 to + 150	°C

## Thermal Resistance

	Parameter	Max.	Units
R <sub>0JA</sub>	Maximum Junction-to-Ambient ②	50	°C/W


# IRF7424GPbF

International  
Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	-30	—	—	V	$V_{\text{GS}} = 0\text{V}$ , $I_D = -250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$	Breakdown Voltage Temp. Coefficient	—	0.019	—	$\text{V}/^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $I_D = -1\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	—	13.5	$\text{m}\Omega$	$V_{\text{GS}} = -10\text{V}$ , $I_D = -11\text{A}$ ②
		—	—	22		$V_{\text{GS}} = -4.5\text{V}$ , $I_D = -8.8\text{A}$ ②
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	-1.0	—	-2.5	V	$V_{\text{DS}} = V_{\text{GS}}$ , $I_D = -250\mu\text{A}$
$g_{\text{fs}}$	Forward Transconductance	17	—	—	S	$V_{\text{DS}} = -10\text{V}$ , $I_D = -11\text{A}$
$I_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	-15	$\mu\text{A}$	$V_{\text{DS}} = -24\text{V}$ , $V_{\text{GS}} = 0\text{V}$
		—	—	-25		$V_{\text{DS}} = -24\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 70^\circ\text{C}$
$I_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	-100	nA	$V_{\text{GS}} = -20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	100		$V_{\text{GS}} = 20\text{V}$
$Q_g$	Total Gate Charge	—	75	110	nC	$I_D = -11\text{A}$
$Q_{\text{gs}}$	Gate-to-Source Charge	—	14	21		$V_{\text{DS}} = -15\text{V}$
$Q_{\text{gd}}$	Gate-to-Drain ("Miller") Charge	—	12	18		$V_{\text{GS}} = -10\text{V}$
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	15	—	ns	$V_{\text{DD}} = -15\text{V}$ ②
$t_r$	Rise Time	—	23	—		$I_D = -1.0\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	150	—		$R_G = 6.0\Omega$
$t_f$	Fall Time	—	76	—		$V_{\text{GS}} = -10\text{V}$
$C_{\text{iss}}$	Input Capacitance	—	4030	—	pF	$V_{\text{GS}} = 0\text{V}$
$C_{\text{oss}}$	Output Capacitance	—	580	—		$V_{\text{DS}} = -25\text{V}$
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	410	—		$f = 1.0\text{kHz}$


## Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	-2.5	A	MOSFET symbol showing the integral reverse p-n junction diode.
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ①	—	—	-47		
$V_{\text{SD}}$	Diode Forward Voltage	—	—	-1.2		$T_J = 25^\circ\text{C}$ , $I_S = -2.5\text{A}$ , $V_{\text{GS}} = 0\text{V}$ ②
$t_{\text{rr}}$	Reverse Recovery Time	—	40	60	ns	$T_J = 25^\circ\text{C}$ , $I_F = -2.5\text{A}$
$Q_{\text{rr}}$	Reverse Recovery Charge	—	47	71	nC	$dI/dt = -100\text{A}/\mu\text{s}$ ②


### Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ③ Surface mounted on 1 in square Cu board
- ② Pulse width  $\leq 400\mu\text{s}$ ; duty cycle  $\leq 2\%$ .


## IRF7424GPbF




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance  
Vs. Temperature

# IRF7424GPbF


International  
**IR** Rectifier




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage



**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode  
Forward Voltage




**Fig 8.** Maximum Safe Operating Area


## IRF7424GPbF




**Fig 9.** Maximum Drain Current Vs.  
Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

# IRF7424GPbF


International  
Rectifier




**Fig 12.** Typical On-Resistance Vs.  
Gate Voltage




**Fig 13.** Typical On-Resistance Vs.  
Drain Current




**Fig 14a.** Basic Gate Charge Waveform



**Fig 14b.** Gate Charge Test Circuit



**Fig 15.** Typical  $V_{GS(th)}$  Vs.  
Junction Temperature




**Fig 16.** Typical Power Vs. Time

# IRF7424GPbF


International  
**IR** Rectifier

## SO-8 Package Outline(Mosfet & Fetky)


Dimensions are shown in milimeters (inches)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.0532	.0688	1.35	1.75
A1	.0040	.0098	0.10	0.25
b	.013	.020	0.33	0.51
c	.0075	.0098	0.19	0.25
D	.189	.1968	4.80	5.00
E	.1497	.1574	3.80	4.00
e	.050	BASIC	1.27	BASIC
e1	.025	BASIC	0.635	BASIC
H	.2284	.2440	5.80	6.20
K	.0099	.0196	0.25	0.50
L	.016	.050	0.40	1.27
y	0°	8°	0°	8°




FOOTPRINT



## SO-8 Part Marking Information

EXAMPLE: THIS IS AN IRF8707GPBF




Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

International  
**IR** Rectifier

**IRF7424GPbF**


## SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package>

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.07/2009