



Leiterquerschnitt	Abisolierlänge	
0,75 - 1,00 mm ²	AWG 18	8 mm
1,50 mm ²	AWG 16	8 mm
2,50 mm ²	AWG 14	8 mm
4,00 mm ²	AWG 12	8 mm

General ordering data

Order No.	1682320000
Part designation	HDC-C-M5-SM0.5AG
Version	HDC contact, CM 5, Pin, 0.00 - 0.50 mm ² , turned, silver
EAN	4008190474058
Qty.	100 pc(s).

General data

Text	Crimping cont. / pin, for module CM-5
Contact diameter	2.5 mm
Production methods	turned
Stripping length	7.5 mm
Type	Pin
Type of connection	Crimping
Connection cross-section, min.	0 mm ²
Connection cross-section, max.	0.5 mm ²
Base material	Copper alloy

General data

Surface finish	silver
Volume resistance	$\leq 4\text{m}\Omega$

Approvals

Approvals institutes	n.a.
----------------------	-------------

Classifications

ETIM 2.0	EC000796
ETIM 3.0	EC000796
eClass 4.1	27-14-08-05
eClass 5.0	27-14-34-19
eClass 5.1	27-14-34-19

Similar products

Order No.	Part designation	Version
1682330000	HDC-C-M5-BM0.5AG	HDC contact, CM 5, Socket, 0.50 - 0.50 mm ² , turned, silver
1682350000	HDC-C-M5-BM0.75-1.0AG	HDC contact, CM 5, Socket, 0.75 - 1.00 mm ² , turned, silver
1682370000	HDC-C-M5-BM1.5AG	HDC contact, CM 5, Socket, 1.50 - 1.50 mm ² , turned, silver
1682390000	HDC-C-M5-BM2.5AG	HDC contact, CM 5, Socket, 2.50 - 2.50 mm ² , turned, silver
1682410000	HDC-C-M5-BM4.0AG	HDC contact, CM 5, Socket, 4.00 - 4.00 mm ² , turned, silver
1682340000	HDC-C-M5-SM0.75-1.0AG	HDC contact, CM 5, Pin, 0.75 - 1.00 mm ² , turned, silver
1682360000	HDC-C-M5-SM1.5AG	HDC contact, CM 5, Pin, 1.50 - 1.50 mm ² , turned, silver
1682380000	HDC-C-M5-SM2.5AG	HDC contact, CM 5, Pin, 2.50 - 2.50 mm ² , turned, silver
1682400000	HDC-C-M5-SM4.0AG	HDC contact, CM 5, Pin, 4.00 - 4.00 mm ² , turned, silver