


Steward



CORE DIMENSIONS		28T0100-200			
UNCOATED CORE					
		MM	INCHES	MM	INCHES
OD	2.54	(.100)	±	.13	(.005)
ID	1.27	(.050)	±	.13	(.005)
TH	0.76	(.030)	±	.13	(.005)
SINGLE PARYLENE COATING		28T0100-20P			
OD	2.57	(.101)	±	.13	(.005)
ID	1.24	(.049)	±	.13	(.005)
TH	0.79	(.031)	±	.13	(.005)

WEIGHT / K 0.03 LBS
 INITIAL PERMEABILITY 850

ELECTRICAL SPECIFICATION								
	MIN		NOM	MAX	MAX	FREQ.	VOLT.	
	(μH)	MIN TOL.	(μH)	(μH)	TOL.	(kHz)	(V)	TURNS
L	.072	(-20%)	.090	.108	(+20%)	100	≤ .00021	1
Q	REF		-	-		100	≤ .00021	1
Net Impedance	MIN		NOM			FREQ.		
	(Ω)	TOL	(Ω)			(MHz)		TURNS
Z1 (Ref.)	2.84	(-25%)	3.78	-	-	25	-	1
Z2	5.36	(-25%)	7.15	-	-	150	-	1

COATING SPECIFICATIONS			
	TYPE	Max. Coating (mils.)	Min. DLB VAC TEST FORCE (LB)
	PARYLENE	0.5	1000 0.06

NOTES:



Rev	Description	Date	INT
A	Original Draft	7/6/1995	JBE
B	Updated to new format	7/6/1995	JBE
C	Updated elect. & Z specs	5/6/1996	BAC
D	Transfer to lotus notes	11/12/1997	IS
E	Revised Gauss level to 10	12/17/2003	TPM
F	REMOVE DOUBLE PARYLENE COATING CHG P/N	9/27/2005	JRK
G	Revised Template	6/1/2006	WMM

Date: 6/1/2006	DWG # 28T0100-20P-G	Rev:
Drawn By: WMM	Title # 28T0100-20P	G

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT