



Affordable Precision GNSS Antennas

What is your application? We can help!

Precision OEM and Housed: Single, Dual, Triple and Full-Band antennas with optional L-Band support

Accutenna®, **Helical**, **VeroStar™**, and **VeraPhase®** Technologies



Accutenna® Technology

Provides low axial ratio and high multipath signal rejection. Suitable for the most demanding applications

Features

- Lightweight Single, Dual, Triple, and L-Band Corrections
- · Very low-current options
- Patented Accutenna® Technology
- Pre-filtering options available
- Antenna customization (tuning, cables, connectors, radomes)
- Short lead times

Learn More: accutenna.tallysman.com


(ww) > (ww) > 3 (ww)

Tight Phase Centre

Great X-Pol Rejection

X (mm)

-3





TW1700 Series
Embedded Single Band
Antennas



TW1800 Series
Embedded Dual Band
Antennas



TW2000 Series
Single Band
Antennas



TW3000 SeriesSingle, Dual, and Triple
Band Antennas



TW3000 SeriesEmbedded Single, Dual, and Triple Band Antennas



TW4000 Series
Single Band
Antennas



TW7000 Series

Dual and Triple Band

Antennas



TW8000 Series

Dual Band
Antennas

Helical Technology

Unprecedented performance in a lightweight, military grade IP69K compliant form factor

Features

- Provides Single, Dual, Triple, and L-Band coverage
- Extremely lightweight (5g (OEM) 37g)
- Novel Helical element
- Excellent axial ratio
- · Low noise amplifier and pre-filter
- Embedded models coming soon



Learn More: helical.tallysman.com

| Model | Frequencies | Mounting |
|-------|--|------------------------------|
| HC600 | Iridium | Surface Mount / Direct Screw |
| HC771 | L1, G1, E1, B1 | Surface Mount / Direct Screw |
| HC871 | L1/L2, G1/G2, E1, B1 | Surface Mount / Direct Screw |
| HC872 | L1/L2, G1/G2, E1, B1, L-Band Corrections | Surface Mount / Direct Screw |
| HC882 | L1/L2, G1/G2/G3, E1/E5b, B1/B2, L-Band Corrections | Surface Mount / Direct Screw |
| HC975 | L1/L2/L5, G1/G3, E1/E5a/E5b, B1/B2/B2a, L-Band Corrections | Surface Mount / Direct Screw |

VeroStar[™] Technology

Precise, accurate, robust, lightweight survey grade antenna

Features

- Patent pending innovative Full Band Antenna element
- · Models provide full GNSS Band and L-Band support
- Excellent radiating pattern with low roll-off for excellent low elevation tracking
- Tight Phase Centre (±2 mm)
- Excellent axial ratio for improved multipath rejection
- Innovative low-noise amplifier with superior out of band filtering
- Waterproof with IP69K compliance
- Embedded models coming soon



VeroStar™ Full Band and L-Band Antenna

Learn More: verostar.tallysman.com

| Model | Frequencies | Mounting |
|---------|--|-------------|
| VSP600L | All Bands, L-Band Corrections | Pole / Pipe |
| VSP610 | L1, G1, E1, B1 | Pole / Pipe |
| VSP620 | L1/L2, G1/G2, E1, B1 | Pole / Pipe |
| VSP630 | L1/L2/L5, G1/G3, E1/E5a/E5b, B1/B2/B2a | Pole / Pipe |
| VSP650L | L1/L5, G1, E1/E5a, B1/B2a, L-Band Corrections | Pole / Pipe |



VeraPhase® Technology

Features

- Patented Full GNSS Bandwidth Antenna
- ± 35-50dB gain models available
- Extremely tight phase centre variation (±1 mm) and excellent PCV repeatability
- TNC or N connector
- Exceptionally low axial ratio from Zenith to Horizon (< 2dB) resulting in excellent multipath rejection
- Innovative low noise amplifier and filter to mitigate Ligado and LTE



VP6000 SeriesVeraPhase® Antennas

| Model | Frequencies | Mounting |
|--------|--|-----------------------|
| VP6000 | L1/L2/L5, G1/G2/G3, E1/E5a/E5b/E6, B1/B2/B2a/B3, L6, L5, | Standard Survey Mount |
| | L-Band Corrections | |
| VP6100 | L1/L2/L5, G1/G2/G3, E1/E5a/E5b/E6, B1/B2/B2a/B3, L6, L5 | Standard Survey Mount |
| VP6200 | L1/L2, G1/G2/G3, E1/E5b, B1/B2, L-Band Corrections | Standard Survey Mount |
| VP6300 | L1/L2/L5, G1/G2/G3, E1/E5a/E5b, B1/B2 | Standard Survey Mount |

VeraChoke® Technology

Features

- Efficient VeraPhase Antenna element
- 50dB LNA gain
- Three dimensional choke ring to mitigate multipath
- N-Type connector
- · Available with or without SCIGN radome
- Extremely tight phase centre variation (±0.5 mm) and excellent PCV repeatability



VC6050 VeraChoke® Antenna

| Model | Frequencies | Mounting |
|--------|---|-----------------------|
| VC6050 | 1/L2/L5, G1/G2/G3, E1/E5a/E5b/E6, B1/B2/B2a/B3, L6, L5, L-Band Corrections | Standard Survey Mount |

Learn More: vera.tallysman.com

About Tallysman: With global headquarters and manufacturing in Ottawa, Canada, Tallysman is a leading manufacturer of high-precision antennas and components for Global Navigation Satellite System (GNSS) applications. Tallysman's mission is to support the needs of a new generation of positioning systems by delivering unprecedented antenna precision at competitive prices. Learn more at **www.tallysman.com**

Contact us: info@tallysman.com T: +1 613 591-3131

© 2019 Tallysman Inc. All rights reserved. Tallysman, the "When Precision Matters" tag line and the Tallysman logo are trademarks or registered trademarks of Tallysman Inc. and/or its affiliates in Canada and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. The information presented is subject to change without notice. Tallysman assumes no responsibility or any errors or ormissions in this document. Tallysman Wireless Inc. hereby disclaims any or all warranties and liabilities of any kind.