



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 6720°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3228-21B	x = .315 y = .295	1190	475	5 ± 1	28,000 ± 10%	40,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

				<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
		THIRD ANGLE PROJECTION				TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>					
<b>C</b> CHANGE LEAD LENGTH TO 15±2 1/28/20			DRAWN BY L. WENGSTROM	APPV'D BY S.N.	DATE 1/28/20	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF3228-21B</b>			
<b>B</b> ELECTRICAL RATING CHANGES 8/5/04			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 12/95	REVISION DATE 1/28/20	REV. NO. <b>C</b>	SHEET 1 OF 1	
<b>A</b> BRIGHTNESS RATING CHANGES 8/20/97 RELEASED 12/95	DESCRIPTION/ECO NUMBER		APPV'D DATE								