5177983-5 ACTIVE

Free Height

TE Internal #: 5177983-5

PCB Mount Receptacle, Vertical, Board-to-Board, 120 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free

Height

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Receptacle Connector: Free Height, PCB Mount for Parallel Stacking











PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Vertical
Connector System: Board-to-Board

Number of Positions: 120

Centerline (Pitch): .8 mm [.031 in]

All Receptacle Connector: Free Height, PCB Mount for Parallel Stacking (27)

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	120
Board-to-Board Configuration	Parallel

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	500 VAC
Insulation Resistance	2 ΜΩ



Operating Voltage	100 VAC
Body Features	
Primary Product Color	Natural
Contact Features	
PCB Contact Termination Area Plating Material Thickness	2 μm[78.74 μin]
Contact Layout	Inline
Mating Tab Width	.4 mm[.016 in]
Mating Tab Thickness	.2 mm[.008 in]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.2 μm[8 μin]
Contact Type	Socket
Contact Current Rating (Max)	.5 A
Termination Features	
Rectangular Termination Post & Tail Thickness	0 1000:1
Rectangular remination rost & ran mickiess	.2 mm[.008 in]
Rectangular Termination Post & Tail Width	.2 mm[.008 in] .3 mm[.012 in]
Rectangular Termination Post & Tail Width	.3 mm[.012 in]
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board	.3 mm[.012 in]
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment	.3 mm[.012 in] Surface Mount
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length	.3 mm[.012 in] Surface Mount .5 mm[.02 in]
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type PCB Mount Retention	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization Without
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type PCB Mount Retention PCB Mount Alignment	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization Without With
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type PCB Mount Retention PCB Mount Alignment Connector Mounting Type	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization Without With
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type PCB Mount Retention PCB Mount Alignment Connector Mounting Type Housing Features	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization Without With Board Mount
Rectangular Termination Post & Tail Width Termination Method to Printed Circuit Board Mechanical Attachment Mounting Alignment Feature Length PCB Mount Alignment Type Mating Alignment Mating Alignment Type PCB Mount Retention PCB Mount Alignment Connector Mounting Type Housing Features Mating Entry Location	.3 mm[.012 in] Surface Mount .5 mm[.02 in] Positioning Bosses With Polarization Without With Board Mount Top



Dimensions

Connector Height	5 mm[.197 in]
Stack Height	5 mm, 6 mm, 7 mm, 8 mm[.197 in][.236 in][. 276 in][.315 in]
Usago Conditions	

Usage Conditions

Housing Temperature Rating	High
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]

Operation/Application

Assembly Process Feature	None
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

	.5 in
Packaging Quantity	9
Packaging Type	Box, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Free Height




Customers Also Bought



















Documents

Product Drawings

0.8FH,R05H.5,120,08/Sn,TU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5177983-5_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5177983-5_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5177983-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Fine Pitch Stacking Connectors - 0.8mm Free Height (FH) Connectors

English

Product Specifications

Product Specification

English

Product Specification

English