

- 1. ENTIRE SWITCH BRACKET IS STAINLESS STEEL. ROLLER IS DELRIN.
- SWITCH IS COMPLETELY WATERPROOF.
   WIRE CONECTIONS MUST BE SEALED TO MAINTAIN THE WATERPROOFNESS OF THE SWITCH.
- 4. MINIMUM POSITION FOR UNLIMITED ACTUATOR ENDURANCE.

- 5. SWITCH ACTION: SPDT
- 6. ELECTRICAL RATING (28VDC/120VAC): 5 AMP RESISITIVE, 3 AMP INDUCTIVE.
- 7. PROPER APPLICATION OF THIS PRODUCT IS THE RESPONSIBILITY OF THE USER.

-	- De la composition della comp				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:	DRAWN	APPROVALS GHS	7/26/21	CF		CONTROL PRODUCTS,	INC.	
REV	DESCRIPTION	DATE	BY	APP	.X ±.1 .XX ±.03 .XXX ±.015 ANG ± :	- CHECKEI	matter and a state of the state	7/27/21	TITLE	E	LIMIT SWITCH, SPDT		
REVISIONS							DIGI-KEY			INSTALLATION DRAWING			
THE INFORMATION FURNISHED HEREIN IS THE PROPERTY OF CONTROL PRODUCTS, INC. AND SHALL NOT BE USED, DISCLOSED TO OTHERS, OR COPIED WITHOUT THE										SCALE	DRAWING NO. E1134-507	SHEET 1 OF 1	
EXPRESS WRITTEN CONSENT OF CONTROL PRODUCTS, INC.						DO NOT SCALE DRAWING			A	HONE	E1134-307	1 0	