



SIGN	DATE	DESCRIPTION	APPROVER
△	2010.01.30	The material is changed from Brass to Copper	Jacke
△	2010.01.30	The Part No is changed	Jacke
△	07/31/12	Added TUV standard	Chen Bo
△	07/31/12	The Dimension is added	Chen Bo
△	07/31/12	The IEC spec is removed	Chen Bo
△	07/31/12	Soldering temperature changed from 250°C±10°C/5Sec to 260°C± 5°C/5Sec	Chen Bo

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

- Material:
- Item ② Terminal(housing): Thermoplastic (UL94V-0)
  - △ Item ③ Male contact pin: Copper Tin plated
- |                              |                                     |      |
|------------------------------|-------------------------------------|------|
| △ 5 Electrical               | cULus                               | TUV  |
| ● Voltage rating:            | 300V                                | 800V |
| ● Current rating:            | 20A <sup>1)</sup> 32A <sup>2)</sup> | 32A  |
| ● Withstanding Voltage:      | 1.6KV                               | 6KV  |
| ● Operating temperature:     | -40°C to +115°C                     |      |
| △ 6 ● Soldering temperature: | 260°C± 5°C/5 Sec                    |      |
| △ 3 ● Safety Approval:       |                                     |      |
| ● Critical dimension:        | ▽                                   |      |

△ 2 VC xx 02 x 1 xxxx G

Solid Block  
02 2 POLES  
03 3 POLES  
... ..  
16 16 POLES

0 2 3 4 5 6 8  
Black (RAL9005)  
Red (RAL3001/D)  
Orange(RAL2011/P)  
Yellow(RAL1018/A)  
Green(RAL6018/T)  
Blue (RAL5015/A)  
Grey(RAL7035/D)

G RoHS compliant (lead<4%)  
In copper Alloy  
000 0 Standard @ Logo  
000 A Standard ANY Logo  
Any special item by customer request, please contact sales department.

DIM		TOL		
		2P-6P	7P-12P	13P-16P
Dim L	(N+2)×7.62	±0.15	±0.20	±0.30
Dim A	N×7.62	±0.15	±0.20	±0.30
Dim B	(N-1)×7.62	±0.15	±0.20	±0.30
Dim C	(N+1)×7.62	±0.15	±0.20	±0.30

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		VC 7.62 SERIES (Feed-through header with slip-on connection)					
PART NO.		VCxx02x1xxxxG			DWG NO.		8VC0005
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Chen Bo 07/31/12	Chen Bo 07/31/12			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
					UNIT: mm		
					SCALE: NONE		
				SHEET: 01/01	REV.: D		