2 METERS LENGTH



Connector A 132117 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122192-15 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
Part #:	132117		Part #:	RG-174	Part #:	122192-15		
Descripti	on: SMA JK RG174	SMA JK RG174 RG316 LMR100 500		RG-174 - PE 0.1	Description:	TNC BHD JK RG174 RG188 RG316 IP67 500		
Туре:	SMA	SMA		PE	Туре:	TNC		
Gender:	Jack		Shielding:	Braid	Gender:	Jack		
Body Typ	be: Straight		Diameter:	0.1	Body Type:	Straight		
Contact	Type: Solder	Solder Standard 50 Ohm		50 Ohm	Contact Type:	Contact Type: Crimp Polarity: Standard Impedance: 50 Ohm		
Polarity:	Standard			None	Polarity:			
Impedan	ce: 50 Ohm			Continuity Hi-Pot	Impedance:			
Mounting	Cable	Cable		2 Meters	Mounting:	Bulkhead - Rear Mount		
Body Ma	terial: Brass	Brass			Body Material:	Brass		
Body Fin					Body Finish:	Nickel IP67 Phosphor Bronze		
IP Rating	: None				IP Rating:			
Contact	Material: Beryllium Coppe	r			Contact Material:			
Contact F	, , , , , , , , , , , , , , , , , , , ,				Contact Finish:	Gold 11 GHz TNC Jack Straight BHD 0°		
Max. Free	12.4 GHz				Max. Freq.:			
Booting:	•				Booting:			
					Clocking:			
		THIS DRAWING MAY CONTAIN		Title:			UNLESS SPECIFIED TOLERANCE:	
Amphenol USTOM CABLE		TAL TO CUSTOM CABLE ICED OR TRANSCRIBED		ST-JK G174 2M	К G174 2М			
CONTROLLED DOCUMENT DO NOT CODY		CUSTOM CABLE INC. ACCEPTA	ANCE OF THIS DRAW	ING Part No:			ASSEMBLY: CENTER LABEL IF LENGTH	
CONTROLLED DOCUMENT - DO NOT COPY		ESTABLISHES AND AGREEMENT OF THE FOREGOING.		NG. Q-2V04E0003002M	Q-2V04E0003002M		IS LESS THAN 12 INCHES	