## 6 INCHES LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 122148 TNC Plug Right Angle Brass Nickel + Heatshrink

Connector B

## **Assembly & Label Notes**

Connector A

Assembly label to be placed  $\sim$  2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



| Commodel A        |                                   |              | 545.0             |                   | 4                                  |  |
|-------------------|-----------------------------------|--------------|-------------------|-------------------|------------------------------------|--|
| Part #:           | 132245                            | Part #:      | RG-316            | Part #:           | 122148                             |  |
| Description:      | SMA R/A BHD JK RG174 RG316 LMR100 | Description: | RG-316 - ST 0.102 | Description:      | TNC R/A PLUG RG174 RG188 RG316 500 |  |
| Description.      | 500                               | Dielectric:  | ST                | Type:             | TNC                                |  |
| Type:             | SMA                               | Shielding:   | Braid             | Gender:           | Plug                               |  |
| Gender:           | Jack                              | Diameter:    | 0.102             | Body Type:        | Right Angle                        |  |
| Body Type:        | Right Angle                       | Impedance:   | 50 Ohm            | Contact Type:     | Solder                             |  |
| Contact Type:     | Solder                            | Sheathing:   | None              | Polarity:         | Standard                           |  |
| Polarity:         | Standard                          | Testing:     | Continuity Hi-Pot | Impedance:        | 50 Ohm                             |  |
| Impedance:        | 50 Ohm                            | Length:      | 6 Inches          | Mounting:         | Cable                              |  |
| Mounting:         | Bulkhead - Rear Mount             | "            |                   | Body Material:    | Brass                              |  |
| Body Material:    | Brass                             |              |                   | Body Finish:      | Nickel                             |  |
| Body Finish:      | Gold                              |              |                   | IP Rating:        | None                               |  |
| IP Rating:        | None                              |              |                   | Contact Material: | Brass                              |  |
| Contact Material: | Beryllium Copper                  |              |                   | Contact Finish:   | Gold                               |  |
| Contact Finish:   | Gold                              |              |                   | Max. Freg.:       | 11 GHz                             |  |
| Max. Freq.:       | 12.4 GHz                          |              |                   | Booting:          | TNC Plug Right Angle               |  |
| Booting:          | SMA Jack Right Angle              |              |                   | Clocking:         | 0°                                 |  |
|                   |                                   | 1            |                   |                   |                                    |  |

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/TNC-RA-PL G316 6I

Part No

Q-2P04T0005006I

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

**Date:** 10/2/2023

Part Number: Q-2P04T00050061

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-JK/TNC-RA-PL G316 6I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

