

Han 16B-HTE-R-NPTF 3/4 Zoll

		Part number	09 30 516 0440
		Specification	Han 16B-HTE-R-NPTF 3/4 Zoll
Identification			
Category	Hoods/Housi	ings	
Series of hoods/housings	Han [®] B		
Type of hood/housing	Hood		
Туре	High constru	ction	
Version			
Size	16 B		
Version	Top entry		
Cable entry	1x NPTF 3/4	n	
Locking type	Single locking	g lever	
Field of application	Standard hoo	ods/housings for industria	al connectors
Technical characteristics			

Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66 IP67

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant

Page 1 / 2 | Creation date 2023-06-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	222 g
Country of origin	China
eCl@ss	27440202 Shell for industrial connectors