

Protect It! 8-Outlet Surge Protector, 10 ft. Cord, 3240 Joules, Modem/Coax/Ethernet Protection, RJ45

MODEL NUMBER: TLP810NET



Highlights

- 8 outlets / 10 ft. cord
- 3240 joule rating
- Coaxial surge protection (digital broadband quality accommodates 2.2 GHz bandwidth)
- Ethernet surge protection
- 2-line modem/fax surge protection

Package Includes

- TLP810NET
- 6 ft. telephone cord
- 6 ft. network cable
- 6 ft. coax cable
- Instruction manual with warranty information

Description

Tripp Lite's TLP810NET surge suppressor has 8 outlets, a 10-foot (3.1-meter) cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 3240 joules to handle the strongest surges. Built-in RJ11, RJ45, and Type F coax jacks prevent surges from damaging your modem/fax/100Bt/cable/satellite equipment. Coaxial jacks provide digital broadband quality and can handle 2.2 GHz bandwidth. \$250,000 Ultimate Lifetime Insurance (U.S., Canada and Puerto Rico only)

Features

- 8 outlets with integrated child safety covers; black housing
- 10 ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment on 2 lines simultaneously; 6 ft. telephone cord included
- Built-in RJ45 jacks prevent surges from damaging your 100Bt equipment; 6 ft. network cable included
- Built-in gold, Type F coax jacks prevent surges from damaging your cable/satellite equipment; digital broadband quality accommodates 2.2 GHz bandwidth; 6 ft. coax cable included
- Surge suppression rating: 3240 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$250,000 Ultimate Lifetime Insurance (U.S., Canada and Puerto Rico only)
- Diagnostic LEDs indicate protection present & ground present
- Audible alarm notifies user when the unit is damaged and needs to be replaced
- Keyhole supports for wall mounting
- Lighted power switch
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications



| OVERVIEW | |
|----------------------------------------------|-------------------------------------------------------------------------------------------|
| UPC Code | 037332095329 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Plug Features | Right Angle (36D) |
| Input Cord Gauge Type | 14 gauge; SJT |
| Input Cord Gauge (AWG) | 14 |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 216000 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Details | SJT |
| Input Cord Length (ft.) | 10 |
| Right-Angle Plug | Yes |
| Input Cord Length (m) | 3.05 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (8) 5-15R |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (6) Yes |
| Outlet Orientation | Single row of 5, plus a second row of 3 for transformer accommodation |
| Right-Angle Outlets | No |
| Outlet Safety Covers Detail | Includes built-in sliding outlet safety covers |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Switches | Combination AC circuit breaker and 2-position red illuminated on/off power switch |
| Audible Alarm | Audible alarm sounds to indicate damage to suppression components |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 3240 |



| | |
|---------------------------------------------------|-----------------------------------------------------------------------------------------|
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating | 330/400/400 |
| EMI / RFI Filtering | Up to 40 dB |
| Automatic Shut-Off | Yes |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection Details | 2 line |
| Cable (Coax) Protection | Yes |
| Cable (Coax) Protection Details | 1 line (2.2 GHz Bandwidth) |
| Network (Ethernet) Protection | Yes |
| Telephone/DSL Protection | Yes |
| PHYSICAL | |
| Material of Construction | Plastic |
| Power Cord Color | Gray |
| Housing Color | Gray |
| Mounting Holes or Slots | Yes |
| Slot or Hole Mount Measurement (Center to Center) | Distance between horizontal tabs = 75 mm; Distance between vertical tabs = 41.6 mm |
| Outlets Measurement (Center to Center) | Distance between standard outlets = 28.5mm; Distance between transformer outlets = 57mm |
| Receptacle Color | Gray |
| Shipping Dimensions (hwd / in.) | 11.41 x 8.66 x 2.04 |
| Shipping Dimensions (hwd / cm) | 28.98 x 22.00 x 5.18 |
| Shipping Weight (lbs.) | 3.00 |
| Shipping Weight (kg) | 1.36 |
| Unit Dimensions (hwd / in.) | 4.86 x 9.55 x 1.51 |
| Unit Dimensions (hwd / cm) | 12.34 x 24.26 x 3.84 |
| Unit Weight (lbs.) | 2.02 |
| Unit Weight (kg) | 0.92 |
| Input Cord Color | White |
| COMMUNICATIONS | |
| Network Compatibility | 100 Mbps (Fast Ethernet) |
| FEATURES & SPECIFICATIONS | |
| Antimicrobial | No |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Rotatable Outlets | No |
| STANDARDS & COMPLIANCE | |
| Industry Canada (Communications) | Industry Canada |
| Product Certifications | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed |
| Product Compliance | FCC Part 68; RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 Ultimate Lifetime Insurance |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>