0.75 METER LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot

132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

Connector B

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



Part #:	132245	Part #:	RG-174	Part #:	132245
Description:	SMA R/A BHD JK RG174 RG316 LMR100 50O	Description: Dielectric:	RG-174 - PE 0.1 PE	Description:	SMA R/A BHD JK RG174 RG316 LMR100 500
Type:	SMA	Shielding:	Braid	Type:	SMA
Gender:	Jack	Diameter:	0.1	Gender:	Jack
Body Type:	Right Angle	Impedance:	50 Ohm	Body Type:	Right Angle
Contact Type:	Solder	Sheathing:	None	Contact Type:	Solder
Polarity:	Standard	Testing:	Continuity Hi-Pot	Polarity:	Standard
Impedance:	50 Ohm	Length:	0.75 Meter	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount			Mounting:	Bulkhead - Rear Mount
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Gold
IP Rating:	None			IP Rating:	None
Contact Material:	Beryllium Copper			Contact Material:	Beryllium Copper
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	12.4 GHz			Max. Freq.:	12.4 GHz
Booting:	SMA Jack Right Angle			Booting:	SMA Jack Right Angle
				Clocking:	0°

Cable



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/SMA-RA-JK G174 0.75M

Part No:

Q-2P02P0003.75M

UNLESS SPECIFIED TOLERANCE:

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH

IS LESS THAN 12 INCHES