2-487406-4 <

TE Internal #: 2-487406-4 FFC Contacts, .1 in [2.54 mm] Centerline, FFC, Socket, Tin, Reel, Insulation Displacement (IDC), 2 A, -85 – 221 °F [-65 – 105 °C] View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FFC Contacts >

2.54mm FFC Connectors Socket Contacts



Centerline (Pitch): 2.54 mm [.1 in]

Compatible With Wire & Cable Type: FFC

Contact Type: Socket

Contact Mating Area Plating Material: Tin

Packaging Method: Reel

#### All 2.54mm FFC Connectors Socket Contacts (35)

## Features

### Product Type Features

Connector & Contact Terminates To	Wire & Cable			
Configuration Features				
Compatible With Wire & Cable Type	FFC			
Contact Features				
PCB Contact Termination Area Plating Material	Gold Flash			
Contact Base Material	Phosphor Bronze			
Contact Type	Socket			
Contact Mating Area Plating Material	Tin			
Contact Current Rating (Max)	2 A			
Termination Features				
Termination Method to Wire & Cable	Insulation Displacement (IDC)			
Housing Features				

**C** For support call+1 800 522 6752

### 2-487406-4

FFC Contacts, .1 in [2.54 mm] Centerline, FFC, Socket, Tin, Reel, Insulation Displacement (IDC), 2 A, -85 – 221 °F [-65 – 105 °C]



Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Accepts Conductor Width	1.27 mm[.05 in]
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Method	Reel
<b>Product Compliance</b> For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 202

#### (233)

Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

#### Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**

#### 2-487406-4

FFC Contacts, .1 in [2.54 mm] Centerline, FFC, Socket, Tin, Reel, Insulation Displacement (IDC), 2 A, -85 – 221 °F [-65 – 105 °C]





# Customers Also Bought



2.54mm FFC Connectors Receptacle Housing	FFC,RCPT CONTACT,STD PRESSURE	MOD2 STIFT M A-PIN	TAB0.5X0.4,NANO MS, NANOMULTISPRING SNFL	
TE Part #4-539498-0 CAM CYLINDER COMPLETE				
Documents				
Product Drawings FFC,RCPT CONTACT,STD F	PRESSURE			
English				

CAD Files

Customer View Model

ENG\_CVM\_CVM\_2-487406-4\_AV.2d\_dxf.zip

English

3D PDF

#### 2-487406-4

FFC Contacts, .1 in [2.54 mm] Centerline, FFC, Socket, Tin, Reel, Insulation Displacement (IDC), 2 A, -85 – 221 °F [-65 – 105 °C]



3D

Customer View Model ENG\_CVM\_CVM\_2-487406-4\_AV.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-487406-4\_AV.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Product Environmental Compliance MD\_2-487406-4\_10222018040\_dmtec

English

MD\_2-487406-4\_10222018040\_dmtec

English

Instruction Sheets

Instruction Sheet (U.S.)

English

**Extraction Tools** 

English