



For more Information
please call

1-800-Belden1

General Description:

Connecting Tool

Usage (Overall)

Suitable Applications: To terminate cables, pigtails or cross-connect wires on any 110 product.

Related Parts: 110 Connector, Tool Pouch, Pigtails, Cross-Connect Wire.

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (mm)	Width (mm)	Length (mm)
38.100	25.400	158.750

Materials

Materials:

Description	Material
Handle	Plastic
Blade	Metal

Color

Color: Black

Weight

Weight: 0.113 kg

Packaging

Packaging: Individual packaged in carton.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

Suitability

Suitability - Indoor: Yes - Indoor

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: Visit our web site at <http://www.belden.com>

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100749	1 EA	0.364 LB			110 TOOL ASSEMBLY

Revision Number: 1 Revision Date: 08-03-2010

© 2018 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.