




UE Series

SDXC Memory Card, Consumer Plus MLC Model

■ **Product Outline**

UE series are SDXC memory cards adopting built-in consumer type MLC NAND flash memory. They support U3 speed grade of UHS-I, and suitable for 4K video recording. They are formatted complying with SDXC card specification.

■ **Product Specification** (specifications and appearances are subject to be changed without notice.)

		64GB	128GB	256GB
Appearance				
Part Number		RP-SDUE64DA1	RP-SDUE12DA1	RP-SDUE25*** (Custom Part Number Only)
Capacity	Available user data area capacity *1)	63,216,156,672 byte	128,278,200,320 byte	256,421,658,624 byte
Compliant Specification	SD Physical Specification	Ver. 4.20		
	SD speed class	CLASS 10		
	UHS speed grade	U3		
	Speed mode	Default Speed Mode, High Speed Mode, SDR12/SDR25/SDR50/DDR50/SDR104		
Backside mark	Control Code	---		
Read/Write Performance (up to)	Read	95MB/s (SDR104 mode)	95MB/s (SDR104 mode)	95MB/s (SDR104 mode)
	Write	90MB/s (SDR104 mode)	90MB/s (SDR104 mode)	90MB/s (SDR104 mode)
Absolute Maximum Ratings	Supply Voltage	Min : -0.3 V ; Max : +4.6 V		
	Input Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Current	Min : -24 mA ; Max : +24 mA		
Environmental Specification	Operating Temperature	-25 degree C to +85 degree C		
	Storage Temperature	-40 degree C to +85 degree C		
	Humidity	5 % RH to 95 % RH		
	Vibration	15 Gp-p		
	Shock	1,000 G		
	Mating Cycles	10,000 cycles		

*1) Free user area capacity after formatted.

Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.

Products comply with EU RoHS directives.

■ Marking Specification



“D000” Control Code (Defined as product parts combination)
“UJYM00000000” Serial Number
Y Last digit of Manufacture year
M Manufacture month (January->A, February->B,)
“MADE IN TAIWAN” Country of origin
“RS00000”, “000000000”, “00000000000000” Internal control code

■ System Reliability

- a. Error detect and corrective function
- b. Static wear leveling
- c. Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.