

# A-CRF-RFRM Series

Wireless antenna cables with RP-SMA (male) to RP-SMA (female) connectors



## Features and Benefits

- Compact, lightweight design
- 1.5 m, 3 m, 5 m options available
- Straight mount or magnetic base mount

## Introduction

The A-CRF-RFRM Series is a set of cable accessories with RP-SMA (male) to RP-SMA (female) connectors and magnetic base mount options for placement on metal surfaces.

## Specifications

### Antenna Characteristics

Impedance	50±3 ohms
Connector	SMA Jack (Female) / SMA Plug (Male)
V.S.W.R.	≤ 2.0 @ 100 MHz to 3 GHz ≤ 2.5 @ 4000 MHz to 5 GHz

### Physical Characteristics

Cable	A-CRF-RFRM-R4-150: RG-174 A-CRF-RFRM-C2-300: CFD-200 A-CRF-RFRM-C2-500: CFD-200
Cable Length	A-CRF-RFRM-R4-150: 1.5 m A-CRF-RFRM-C2-300: 3 m A-CRF-RFRM-C2-500: 5 m
Weight	A-CRF-RFRM-R4-150: 118 g (0.26 lb) A-CRF-RFRM-C2-300: 135 g (0.30 lb) A-CRF-RFRM-C2-500: 155 g (0.34 lb)
Dimensions	A-CRF-RFRM-R4-150: Height: 40.5 mm (including base)
Radome Color	Black
Radome Material	Plastic
Installation	A-CRF-RFRM-R4-150: Magnetic mount A-CRF-RFRM-C2-500: N/A A-CRF-RFRM-C2-300: N/A

## Environmental Limits

Operating Temperature -40 to 85°C (-40 to 185°F)

Storage Temperature -40 to 85°C (-40 to 185°F)

## Warranty

Warranty Period 1 year

Details See [www.moxa.com/warranty](http://www.moxa.com/warranty)


## Package Contents

Device 1 x A-CRF-RFRM Series wireless antenna cable

## Dimensions


### A-CRF-RFRM-R14-150

Unit: mm




### A-CRF-RFRM-C2-300

Unit: mm



### A-CRF-RFRM-C2-500

Unit: mm



## Ordering Information

Model Name	Cable Type	Connector Type	Cable Length
A-CRF-RFRM-R4-150	RG-174	RP-SMA (male) to RP-SMA (female)	1.5 m
A-CRF-RFRM-C2-300	CFD-200	RP-SMA (male) to RP-SMA (female)	3 m
A-CRF-RFRM-C2-500	CFD-200	RP-SMA (male) to RP-SMA (female)	5 m

© Moxa Inc. All rights reserved. Updated Nov 11, 2022.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.