

Identification	Part number	Drawing	Dimensions in mm
<p>HARTING PushPull Signal</p> <p>Insert for panel feed-through HIFF, 10-poles incl. male insert</p> <p>Order D-Sub crimp male contacts separately</p> <p>D-Sub crimp contacts for device side</p> <p>male, turned AWG 24-20; 0.25-0.52 mm²</p> <p>male, turned AWG 22-18; 0.33-0.82 mm²</p> <p>male, stamped AWG 24-20; 0.25-0.56 mm²</p>	<p>09 45 545 9010</p>		
<p>HARTING PushPull</p> <p>suitable housing, bulkhead mounting, plastic</p> <p>EasyInstall</p>	<p>09 45 545 0032</p>		
<p>Compact</p>	<p>09 45 545 0028</p>		
<p>HARTING PushPull Signal solder jack angled</p> <p>suitable housings, bulkhead mounting</p> <p>with fixing clip</p> <p>without fixing clip</p>	<p>09 45 545 9011</p> <p>09 45 545 0029</p> <p>09 45 545 0033</p>		
<p>HARTING PushPull Signal solder jack straight</p> <p>suitable housing, bulkhead mounting</p>	<p>09 45 545 9012</p> <p>09 45 545 0027</p>		

1) To be used with crimp tool 09 99 000 0501. Suitable locator: 09 99 000 0531
 2) To be used with crimp tool 09 99 000 0175.