

# IRFB3004PbF IRFS3004PbF IRFSL3004PbF


HEXFET® Power MOSFET

## Applications


- High Efficiency Synchronous Rectification in SMPS
- Uninterruptible Power Supply
- High Speed Power Switching
- Hard Switched and High Frequency Circuits

## Benefits

- Improved Gate, Avalanche and Dynamic dV/dt Ruggedness
- Fully Characterized Capacitance and Avalanche SOA
- Enhanced body diode dV/dt and dl/dt Capability
- Lead-Free



|  |                    |
|--|--------------------|
| <b>V<sub>DSS</sub></b>                 | <b>40V</b>         |
| <b>R<sub>DS(on)</sub></b>              | <b>typ. 1.4mΩ</b>  |
|  | <b>max. 1.75mΩ</b> |
| <b>I<sub>D</sub> (Silicon Limited)</b> | <b>340A①</b>       |
| <b>I<sub>D</sub> (Package Limited)</b> | <b>195A</b>        |



| G    | D     | S      |
|------|-------|--------|
| Gate | Drain | Source |

## Absolute Maximum Ratings

| Symbol                                  | Parameter   | Max.              | Units |
|---|---|-------------------|-------|
| I <sub>D</sub> @ T <sub>C</sub> = 25°C  | Continuous Drain Current, V <sub>GS</sub> @ 10V (Silicon Limited)   | 340①              | A     |
| I <sub>D</sub> @ T <sub>C</sub> = 100°C | Continuous Drain Current, V <sub>GS</sub> @ 10V (Silicon Limited)   | 240①              |       |
| I <sub>D</sub> @ T <sub>C</sub> = 25°C  | Continuous Drain Current, V <sub>GS</sub> @ 10V (Wire Bond Limited) | 195               |       |
| I <sub>DM</sub>                         | Pulsed Drain Current ②  | 1310              |       |
| P <sub>D</sub> @ T <sub>C</sub> = 25°C  | Maximum Power Dissipation   | 380               | W     |
|   | Linear Derating Factor  | 2.5               | W/°C  |
| V <sub>GS</sub>                         | Gate-to-Source Voltage  | ± 20              | V     |
| dv/dt                                   | Peak Diode Recovery ④   | 4.4               | V/ns  |
| T <sub>J</sub>                          | Operating Junction and  | -55 to + 175      | °C    |
| T <sub>STG</sub>                        | Storage Temperature Range   |                   |       |
|   | Soldering Temperature, for 10 seconds (1.6mm from case)             | 300               |       |
|   | Mounting torque, 6-32 or M3 screw                                   | 10lbf·in (1.1N·m) |       |

## Avalanche Characteristics

|                                     |                                 |                           |    |
|-------------------------------------|---------------------------------|---------------------------|----|
| E <sub>AS</sub> (Thermally limited) | Single Pulse Avalanche Energy ③ | 300                       | mJ |
| I <sub>AR</sub>                     | Avalanche Current ②             | See Fig. 14, 15, 22a, 22b | A  |
| E <sub>AR</sub>                     | Repetitive Avalanche Energy ②   |                           | mJ |

## Thermal Resistance

| Symbol           | Parameter  | Typ. | Max. | Units |
|------------------|--|------|------|-------|
| R <sub>θJC</sub> | Junction-to-Case ⑨⑩                                    | —    | 0.40 | °C/W  |
| R <sub>θCS</sub> | Case-to-Sink, Flat Greased Surface, TO-220             | 0.50 | —    |       |
| R <sub>θJA</sub> | Junction-to-Ambient, TO-220                            | —    | 62   |       |
| R <sub>θJA</sub> | Junction-to-Ambient (PCB Mount) , D <sup>2</sup> Pak ⑧ | —    | 40   |       |

**Static @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

| Symbol  | Parameter                            | Min. | Typ.  | Max. | Units               | Conditions   |
|---|--------------------------------------|------|-------|------|---------------------|--|
| $V_{(\text{BR})\text{DSS}}$                   | Drain-to-Source Breakdown Voltage    | 40   | —     | —    | V                   | $V_{GS} = 0V, I_D = 250\mu\text{A}$                  |
| $\Delta V_{(\text{BR})\text{DSS}}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.037 | —    | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}, I_D = 5\text{mA}$ ②  |
| $R_{DS(\text{on})}$                           | Static Drain-to-Source On-Resistance | —    | 1.4   | 1.75 | $\text{m}\Omega$    | $V_{GS} = 10V, I_D = 195\text{A}$ ⑤                  |
| $V_{GS(\text{th})}$                           | Gate Threshold Voltage               | 2.0  | —     | 4.0  | V                   | $V_{DS} = V_{GS}, I_D = 250\mu\text{A}$              |
| $I_{DSS}$                                     | Drain-to-Source Leakage Current      | —    | —     | 20   | $\mu\text{A}$       | $V_{DS} = 40V, V_{GS} = 0V$                          |
|   |                                      | —    | —     | 250  | —                   | $V_{DS} = 40V, V_{GS} = 0V, T_J = 125^\circ\text{C}$ |
| $I_{GSS}$                                     | Gate-to-Source Forward Leakage       | —    | —     | 100  | nA                  | $V_{GS} = 20V$                                       |
|   | Gate-to-Source Reverse Leakage       | —    | —     | -100 | —                   | $V_{GS} = -20V$                                      |
| $R_G$   | Internal Gate Resistance             | —    | 2.2   | —    | $\Omega$            |  |

**Dynamic @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

| Symbol                      | Parameter                                       | Min. | Typ. | Max. | Units | Conditions  |
|-----------------------------|---|------|------|------|-------|---|
| $g_{fs}$                    | Forward Transconductance                        | 1170 | —    | —    | S     | $V_{DS} = 10V, I_D = 195\text{A}$                         |
| $Q_g$                       | Total Gate Charge                               | —    | 160  | 240  | nC    | $I_D = 187\text{A}$                                       |
| $Q_{gs}$                    | Gate-to-Source Charge                           | —    | 40   | —    | —     | $V_{DS} = 20V$  |
| $Q_{gd}$                    | Gate-to-Drain ("Miller") Charge                 | —    | 68   | —    | —     | $V_{GS} = 10V$ ⑤  |
| $Q_{\text{sync}}$           | Total Gate Charge Sync. ( $Q_g - Q_{gd}$ )      | —    | 92   | —    | —     | $I_D = 187\text{A}, V_{DS} = 0V, V_{GS} = 10V$            |
| $t_{d(on)}$                 | Turn-On Delay Time                              | —    | 23   | —    | ns    | $V_{DD} = 26V$  |
| $t_r$                       | Rise Time                                       | —    | 220  | —    | —     | $I_D = 195\text{A}$                                       |
| $t_{d(off)}$                | Turn-Off Delay Time                             | —    | 90   | —    | —     | $R_G = 2.7\Omega$   |
| $t_f$                       | Fall Time                                       | —    | 130  | —    | —     | $V_{GS} = 10V$ ⑤  |
| $C_{iss}$                   | Input Capacitance                               | —    | 9200 | —    | pF    | $V_{GS} = 0V$   |
| $C_{oss}$                   | Output Capacitance                              | —    | 2020 | —    | —     | $V_{DS} = 25V$  |
| $C_{rss}$                   | Reverse Transfer Capacitance                    | —    | 1340 | —    | —     | $f = 1.0 \text{ MHz, See Fig. 5}$                         |
| $C_{oss \text{ eff. (ER)}}$ | Effective Output Capacitance (Energy Related) ⑦ | —    | 2440 | —    | —     | $V_{GS} = 0V, V_{DS} = 0V \text{ to } 32V$ ⑦, See Fig. 11 |
| $C_{oss \text{ eff. (TR)}}$ | Effective Output Capacitance (Time Related) ⑥   | —    | 2690 | —    | —     | $V_{GS} = 0V, V_{DS} = 0V \text{ to } 32V$ ⑥              |







**Diode Characteristics**

| Symbol    | Parameter                              | Min.   | Typ. | Max. | Units | Conditions  |
|-----------|--|--|------|------|-------|---|
| $I_s$     | Continuous Source Current (Body Diode) | —  | —    | 340① | A     | MOSFET symbol showing the integral reverse p-n junction diode.          |
| $I_{SM}$  | Pulsed Source Current (Body Diode) ②   | —  | —    | 1310 | A     |   |
| $V_{SD}$  | Diode Forward Voltage                  | —  | —    | 1.3  | V     | $T_J = 25^\circ\text{C}, I_s = 195\text{A}, V_{GS} = 0V$ ⑤              |
| $t_{rr}$  | Reverse Recovery Time                  | —  | 27   | —    | ns    | $T_J = 25^\circ\text{C} \quad V_R = 34V,$                               |
|           |  | —  | 31   | —    | —     | $T_J = 125^\circ\text{C} \quad I_F = 195\text{A}$                       |
| $Q_{rr}$  | Reverse Recovery Charge                | —  | 18   | —    | nC    | $T_J = 25^\circ\text{C} \quad \text{di/dt} = 100\text{A}/\mu\text{s}$ ⑤ |
|           |  | —  | 41   | —    | —     | $T_J = 125^\circ\text{C}$   |
| $I_{RRM}$ | Reverse Recovery Current               | —  | 1.2  | —    | A     | $T_J = 25^\circ\text{C}$  |
| $t_{on}$  | Forward Turn-On Time                   | Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD) |      |      |       |   |

**Notes:**


- ① Calculated continuous current based on maximum allowable junction temperature. Bond wire current limit is 195A. Note that current limitations arising from heating of the device leads may occur with some lead mounting arrangements. (Refer to AN-1140)
- ② Repetitive rating; pulse width limited by max. junction temperature.
- ③ Limited by  $T_{J\text{max}}$ , starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.016\text{mH}$   $R_G = 25\Omega$ ,  $I_{AS} = 195\text{A}$ ,  $V_{GS} = 10V$ . Part not recommended for use above this value .

- ④  $I_{SD} \leq 195\text{A}$ ,  $\text{di/dt} \leq 930\text{A}/\mu\text{s}$ ,  $V_{DD} \leq V_{(\text{BR})\text{DSS}}$ ,  $T_J \leq 175^\circ\text{C}$ .
- ⑤ Pulse width  $\leq 400\mu\text{s}$ ; duty cycle  $\leq 2\%$ .
- ⑥  $C_{oss \text{ eff. (TR)}}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .
- ⑦  $C_{oss \text{ eff. (ER)}}$  is a fixed capacitance that gives the same energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .
- ⑧ When mounted on 1" square PCB (FR-4 or G-10 Material). For recommended footprint and soldering techniques refer to application note #AN-994.
- ⑨  $R_\theta$  is measured at  $T_J$  approximately  $90^\circ\text{C}$ .
- ⑩  $R_{\theta\text{JC}}$  value shown is at time zero.




# IRFB/S/SL3004PbF


International  
Rectifier




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current vs. Case Temperature



**Fig 10.** Drain-to-Source Breakdown Voltage



**Fig 11.** Typical  $C_{oss}$  Stored Energy



**Fig 12.** Maximum Avalanche Energy vs. Drain Current




Fig 13. Maximum Effective Transient Thermal Impedance, Junction-to-Case





Fig 14. Typical Avalanche Current vs.Pulsewidth



Notes on Repetitive Avalanche Curves , Figures 14, 15:  
 (For further info, see AN-1005 at [www.irf.com](http://www.irf.com))






1. Avalanche failures assumption:  
 Purely a thermal phenomenon and failure occurs at a temperature far in excess of  $T_{jmax}$ . This is validated for every part type.
  2. Safe operation in Avalanche is allowed as long as  $T_{jmax}$  is not exceeded.
  3. Equation below based on circuit and waveforms shown in Figures 16a, 16b.
  4.  $P_{D(ave)}$  = Average power dissipation per single avalanche pulse.
  5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).
  6.  $I_{av}$  = Allowable avalanche current.
  7.  $\Delta T$  = Allowable rise in junction temperature, not to exceed  $T_{jmax}$  (assumed as  $25^{\circ}\text{C}$  in Figure 14, 15).
- $t_{av}$  = Average time in avalanche.  
 $D$  = Duty cycle in avalanche =  $t_{av} \cdot f$   
 $Z_{thJC}(D, t_{av})$  = Transient thermal resistance, see Figures 13



$$P_{D(ave)} = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$$

$$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$$



$$E_{AS(AR)} = P_{D(ave)} \cdot t_{av}$$

Fig 15. Maximum Avalanche Energy vs. Temperature

**Fig. 16.** Threshold Voltage vs. Temperature**Fig. 17 -** Typical Recovery Current vs.  $di_F/dt$ **Fig. 18 -** Typical Recovery Current vs.  $di_F/dt$ **Fig. 19 -** Typical Stored Charge vs.  $di_F/dt$ **Fig. 20 -** Typical Stored Charge vs.  $di_F/dt$




**Fig 21.** Peak Diode Recovery  $dv/dt$  Test Circuit for N-Channel HEXFET® Power MOSFETs




**Fig 22a.** Unclamped Inductive Test Circuit


**Fig 22b.** Unclamped Inductive Waveforms




**Fig 23a.** Switching Time Test Circuit



**Fig 23b.** Switching Time Waveforms




**Fig 24a.** Gate Charge Test Circuit



**Fig 24b.** Gate Charge Waveform

## TO-220AB Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

- DIMENSIONING AND TOLERANCING AS PER ASME Y14.5 M- 1994.
- DIMENSIONS ARE SHOWN IN INCHES [MILLIMETERS].
- LEAD DIMENSION AND FINISH UNCONTROLLED IN L1.
- DIMENSION D, D1 & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PEAK SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
- DIMENSION b1, b3 & c1 APPLY TO BASE METAL ONLY.
- CONTROLLING DIMENSION : INCHES.
- THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS E,H1,D2 & E1
- DIMENSION E2 X H1 DEFINE A ZONE WHERE STAMPING AND SINGULATION IRRREGULARITIES ARE ALLOWED.
- OUTLINE CONFORMS TO JEDEC TO-220, EXCEPT A2 (max.) AND D2 (min.) WHERE DIMENSIONS ARE DERIVED FROM THE ACTUAL PACKAGE OUTLINE.

| SYMBOL | DIMENSIONS  |       | NOTES    |      |
|--------|-------------|-------|----------|------|
|        | MILLIMETERS |       |          |      |
|        | MIN.        | MAX.  |          |      |
| A      | 3.56        | 4.83  | .140     | .190 |
| A1     | 0.51        | 1.40  | .020     | .055 |
| A2     | 2.03        | 2.92  | .080     | .115 |
| b      | 0.38        | 1.01  | .015     | .040 |
| b1     | 0.38        | 0.97  | .015     | .038 |
| b2     | 1.14        | 1.78  | .045     | .070 |
| b3     | 1.14        | 1.73  | .045     | .068 |
| c      | 0.36        | 0.61  | .014     | .024 |
| c1     | 0.36        | 0.56  | .014     | .022 |
| D      | 14.22       | 16.51 | .560     | .650 |
| D1     | 8.38        | 9.02  | .330     | .355 |
| D2     | 11.68       | 12.88 | .460     | .507 |
| E      | 9.65        | 10.67 | .380     | .420 |
| E1     | 6.86        | 8.89  | .270     | .350 |
| E2     | —           | 0.76  | —        | .030 |
| e      | 2.54 BSC    | —     | .100 BSC |      |
| e1     | 5.08 BSC    | —     | .200 BSC |      |
| H1     | 5.84        | 6.86  | .230     | .270 |
| L      | 12.70       | 14.73 | .500     | .580 |
| L1     | 3.56        | 4.06  | .140     | .160 |
| QP     | 3.54        | 4.08  | .139     | .161 |
| Q      | 2.54        | 3.42  | .100     | .135 |

**LEAD ASSIGNMENTS**

|               |
|---------------|
| HEXFET        |
| 1.- GATE      |
| 2.- DRAIN     |
| 3.- SOURCE    |
| IGBTs, CoPACK |
| 1.- GATE      |
| 2.- COLLECTOR |
| 3.- Emitter   |
| DIODES        |
| 1.- ANODE     |
| 2.- CATHODE   |
| 3.- ANODE     |


## TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010

LOT CODE 1789

ASSEMBLED ON WW 19, 2000  
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead - Free"




TO-220AB packages are not recommended for Surface Mount Application.

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

## TO-262 Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
4. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSION E, L1, D1 & E1.
5. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
6. CONTROLLING DIMENSION: INCH.
7. OUTLINE CONFORM TO JEDEC TO-262 EXCEPT A1(max.), b(min.) AND D1(min.) WHERE DIMENSIONS DERIVED THE ACTUAL PACKAGE OUTLINE.

| SYMBOL | DIMENSIONS  |       |        |      | NOTES |  |
|--------|-------------|-------|--------|------|-------|--|
|        | MILLIMETERS |       | INCHES |      |       |  |
|        | MIN.        | MAX.  | MIN.   | MAX. |       |  |
| A      | 4.06        | 4.83  | .160   | .190 |       |  |
| A1     | 2.03        | 3.02  | .080   | .119 |       |  |
| b      | 0.51        | 0.99  | .020   | .039 |       |  |
| b1     | 0.51        | 0.89  | .020   | .035 | 5     |  |
| b2     | 1.14        | 1.78  | .045   | .070 |       |  |
| b3     | 1.14        | 1.73  | .045   | .068 | 5     |  |
| c      | 0.38        | 0.74  | .015   | .029 |       |  |
| c1     | 0.38        | 0.58  | .015   | .023 | 5     |  |
| c2     | 1.14        | 1.65  | .045   | .065 |       |  |
| D      | 8.38        | 9.65  | .330   | .380 | 3     |  |
| D1     | 6.86        | —     | .270   | —    | 4     |  |
| E      | 9.65        | 10.67 | .380   | .420 | 3,4   |  |
| E1     | 6.22        | —     | .245   | —    | 4     |  |
| e      | 2.54        | BSC   | .100   | BSC  |       |  |
| L      | 13.46       | 14.10 | .530   | .555 |       |  |
| L1     | —           | 1.65  | —      | .065 | 4     |  |
| L2     | 3.56        | 3.71  | .140   | .146 |       |  |

LEAD ASSIGNMENTS

HEXFET

1. GATE
2. DRAIN
3. SOURCE
4. DRAIN


IGBTs, CoPACK

1. GATE
2. COLLECTOR
3. Emitter
4. COLLECTOR


## TO-262 Part Marking Information

EXAMPLE: THIS IS AN IRL3103L  
LOT CODE 1789  
ASSEMBLED ON WW 19, 1997  
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead - Free"




OR



D<sup>2</sup>Pak (TO-263AB) Package Outline

Dimensions are shown in millimeters (inches)



## NOTES:



1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY AT DATUM H.
4. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSION E, L1, D1 & E1.
5. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
6. DATUM A & B TO BE DETERMINED AT DATUM PLANE H.
7. CONTROLLING DIMENSION: INCH.
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-263AB.

| SYMBOL | DIMENSIONS  |       |        |      | NOTES |
|--------|-------------|-------|--------|------|-------|
|        | MILLIMETERS |       | INCHES |      |       |
|        | MIN.        | MAX.  | MIN.   | MAX. |       |
| A      | 4.06        | 4.83  | .160   | .190 |       |
| A1     | 0.00        | 0.254 | .000   | .010 |       |
| b      | 0.51        | 0.99  | .020   | .039 |       |
| b1     | 0.51        | 0.89  | .020   | .035 | 5     |
| b2     | 1.14        | 1.78  | .045   | .070 |       |
| b3     | 1.14        | 1.73  | .045   | .068 | 5     |
| c      | 0.38        | 0.74  | .015   | .029 |       |
| c1     | 0.38        | 0.58  | .015   | .023 | 5     |
| c2     | 1.14        | 1.65  | .045   | .065 |       |
| D      | 8.38        | 9.65  | .330   | .380 | 3     |
| D1     | 6.86        | —     | .270   | —    | 4     |
| E      | 9.65        | 10.67 | .380   | .420 | 3,4   |
| E1     | 6.22        | —     | .245   | —    | 4     |
| e      | 2.54        | BSC   | .100   | BSC  |       |
| H      | 14.61       | 15.88 | .575   | .625 |       |
| L      | 1.78        | 2.79  | .070   | .110 |       |
| L1     | —           | 1.65  | —      | .066 | 4     |
| L2     | 1.27        | 1.78  | —      | .070 |       |
| L3     | 0.25        | BSC   | .010   | BSC  |       |
| L4     | 4.78        | 5.28  | .188   | .208 |       |

D<sup>2</sup>Pak (TO-263AB) Part Marking Information

EXAMPLE: THIS IS AN IRF530S WITH  
LOT CODE 8024  
ASSEMBLED ON WW 02, 2000  
IN THE ASSEMBLY LINE "L"


Note: "P" in assembly line position  
indicates "Lead - Free"

OR

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

## D<sup>2</sup>Pak (TO-263AB) Tape & Reel Information

Dimensions are shown in millimeters (inches)



Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>

Data and specifications subject to change without notice.  
 This product has been designed and qualified for the Industrial market.  
 Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
 TAC Fax: (310) 252-7903  
 Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 02/2009

## **IMPORTANT NOTICE**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

## **WARNINGS**

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.