



**ZXTN25040DFH**

**40V NPN MEDIUM POWER PLANAR TRANSISTOR IN SOT23**

**Features and Benefits**

- $BV_{CEO} > 40V$
- $I_C = 4A$  Continuous Collector Current
- Low Saturation Voltage  $V_{CE(sat)} < 55mV @ 1A$
- $R_{CE(sat)} = 35m\Omega$
- $h_{FE}$  characterised up to 10A
- High  $h_{FE}$  min 300 @ 1A
- 1.25W power dissipation
- 130V forward blocking voltage
- 6V reverse blocking voltage
- Complementary part number ZXTP25040DFH
- **“Lead-Free”, RoHS Compliant (Note 1)**
- **Halogen and Antimony Free. “Green” Device (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**


**Mechanical Data**

- Case: SOT23
- Case material: Molded Plastic. “Green” Molding Compound (Note 2) UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish; Solderable per MIL-STD-202, Method 208
- Weight: 0.008 grams (Approximate)


**Applications**

- MOSFET gate drivers
- Power switches
- Motor control
- DC fans
- DC-DC converters


SOT23



Top View



Device Symbol




Top View  
Pin Configuration

**Ordering Information** (Note 3)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZXTN25040DFHTA	1A4	7	8	3,000

- Notes:
1. No purposefully added lead.
  2. Diodes Inc's “Green” Policy can be found on our website at <https://www.diodes.com/>
  3. Devices with lot number starting from PID0155145 (March 2010) are “Green” products.

**Marking Information**



1A4 = Product Type Marking Code

**Maximum Ratings** @ $T_A = 25^\circ\text{C}$  unless otherwise specified


Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	130	V
Collector-Emitter Voltage (Forward Blocking)	$V_{CEX}$	130	V
Collector-Emitter Voltage	$V_{CEO}$	40	V
Emitter-Collector Voltage (Reverse Blocking)	$V_{ECO}$	6	V
Emitter-Base Voltage	$V_{EBO}$	7	V
Continuous Collector Current (Note 6)	$I_C$	4	A
Peak Pulse Current	$I_{CM}$	10	A
Base Current	$I_B$	1	A

**Thermal Characteristics** @ $T_A = 25^\circ\text{C}$  unless otherwise specified


Characteristic	Symbol	Value	Unit
Power Dissipation Linear Derating Factor	$P_D$ -	0.73	W mW/ $^\circ\text{C}$
		5.84	
		1.05	
		8.4	
		1.25	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	9.6	$^\circ\text{C}/\text{W}$
		1.81	
		14.5	
		171	
Thermal Resistance, Junction to Lead	$R_{\theta JL}$	119	$^\circ\text{C}/\text{W}$
		100	
		69	
		74.95	
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$

- Notes:
4. For a device surface mounted on 15mm X 15mm X 1.6mm FR4 PCB with high coverage of single sided 1 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
  5. For a device surface mounted on 25mm X 25mm X 1.6mm FR4 PCB with high coverage of single sided 2 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
  6. For a device surface mounted on 50mm X 50mm X 1.6mm FR4 PCB with high coverage of single sided 2 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
  7. As note 6 above, measured at  $t < 5$  seconds
  8. Thermal resistance from junction to solder-point (at the end of the collector lead).


**Typical Thermal Characteristics**




**Safe Operating Area**




**Safe Operating Area**



**Transient Thermal Impedance**



**Pulse Power Dissipation**








**Derating Curve**

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS</b>						
Collector-Base Breakdown Voltage	BV <sub>CB0</sub>	130	170	-	V	I <sub>C</sub> = 100μA
Collector-emitter breakdown voltage (forward blocking)	BV <sub>CEX</sub>	130	170	-	V	I <sub>C</sub> = 100μA; R <sub>BE</sub> < 1kΩ or -1V < V <sub>BE</sub> < 0.25V
Collector-Emitter Breakdown Voltage (base open) (Note 9)	BV <sub>CEO</sub>	40	63	-	V	I <sub>C</sub> = 10mA
Emitter-Base Breakdown Voltage	BV <sub>EBO</sub>	7	8.3	-	V	I <sub>E</sub> = 100μA
Emitter-collector breakdown voltage (reverse blocking)	BV <sub>ECX</sub>	6	7.4	-	V	I <sub>E</sub> = 100μA; R <sub>BC</sub> < 1kΩ or -0.25V < V <sub>BC</sub> < 0.25V
Emitter-collector breakdown voltage (base open)	BV <sub>ECO</sub>	6	7.4	-	V	I <sub>E</sub> = 100μA;
Collector-base Cut-off Current	I <sub>CB0</sub>	-	<1	50	nA	V <sub>CB</sub> = 100V
				20	μA	V <sub>CB</sub> = 100V, T <sub>A</sub> = 100°C
Collector-emitter Cut-off Current	I <sub>CEX</sub>	-	-	100	nA	V <sub>CE</sub> = 100V; R <sub>BE</sub> < 1kΩ or -1V < V <sub>BE</sub> < 0.25V
Emitter-base Cut-off Current	I <sub>EBO</sub>	-	<1	50	nA	V <sub>EB</sub> = 5.6V
<b>ON CHARACTERISTICS (Note 9)</b>						
Static Forward Current Transfer Ratio	h <sub>FE</sub>	300	450	900	-	I <sub>C</sub> = 10mA, V <sub>CE</sub> = 2V
		300	450	-		
		30	60	-		
		-	10	-		
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub>	-	45	55	mV	I <sub>C</sub> = 1A, I <sub>B</sub> = 100mA
		-	120	210		
		-	135	210		
		-	140	190		
Base-Emitter Saturation Voltage	V <sub>BE(sat)</sub>	-	960	1050	mV	I <sub>C</sub> = 4A, I <sub>B</sub> = 400mA
Base-Emitter On Voltage	V <sub>BE(on)</sub>	-	840	950	mV	I <sub>C</sub> = 4A, V <sub>CE</sub> = 2V
<b>SMALL SIGNAL CHARACTERISTICS (Note 9)</b>						
Transition Frequency	f <sub>T</sub>	-	190	-	MHz	I <sub>C</sub> = 50mA, V <sub>CE</sub> = 10V, f = 100MHz
Collector Output Capacitance	C <sub>obo</sub>	-	11.7	20	pF	V <sub>CB</sub> = 10V, f = 1MHz
Delay time	t <sub>d</sub>	-	64	-	ns	V <sub>CC</sub> = 10V, I <sub>C</sub> = 1A, I <sub>B1</sub> = I <sub>B2</sub> = 10mA
Rise time	t <sub>r</sub>	-	108	-	ns	
Storage time	t <sub>s</sub>	-	428	-	ns	
Fall time	t <sub>f</sub>	-	130	-	ns	

Notes: 9. Measured under pulsed conditions. Pulse width ≤ 300μs. Duty cycle ≤ 2%

**Typical Electrical Characteristics**




**Package Outline Dimensions**



Dim.	Millimeters		Inches		Dim.	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	-	1.12	-	0.044	e1	1.90 NOM		0.075 NOM	
A1	0.01	0.10	0.0004	0.004	E	2.10	2.64	0.083	0.104
b	0.30	0.50	0.012	0.020	E1	1.20	1.40	0.047	0.055
c	0.085	0.20	0.003	0.008	L	0.25	0.60	0.0098	0.0236
D	2.80	3.04	0.110	0.120	L1	0.45	0.62	0.018	0.024
e	0.95 NOM		0.037 NOM		-	-	-	-	-

**Note:** Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

**Suggested Pad Layout**



#### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

#### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)