


THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES,  
 ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED  
 WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES.  
 ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

ALL DIMENSIONS ARE REFERENCE ONLY

PART NO.

**RSA-3570-SS-047**

REV	DESCRIPTION	DWN	DATE	APPROVED
-	ENGINEERING RELEASE	JDM	9/25/06	JDMc



**SPECIFICATIONS:**

IMPEDANCE: 50 Ohms  
 FREQUENCY RANGE: 0-18 GHz  
 INSERTION LOSS(dB):  $1.07 + .01 \times \sqrt{f(\text{GHz})}$   
 INSULATION RESISTANCE: 5k M Ohms min.  
 TEMPERATURE RANGE: -65°C TO 165°C  
 FOR .047 SEMI RIGID, M17/151

1	BODY	1	SST 303	GOLD, 10μ"	000641	
2	INSULATOR	1	PTFE	---		
3	CONTACT	1	Be.Cu.	GOLD, 30μ"		
4	INSULATOR	1	PTFE	---		
5	SOLDER INSERT	1	BRASS	GOLD, 3μ"		
6						
7						
8						
9						
10					DRAWN JDM 11/21/06	
11					CHECKED	
12						
13					ORJ DRAWN C. ZUNIGA 11/21/06	
14						
#	DESCRIPTION	QTY	MATERIAL	FINISH	APPROVALS	DATE

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MILLIMETERS]  
 UNLESS OTHERWISE NOTED TOLERANCES ARE:  
 DECIMALS      DIAMETER

**RFconnectors**  
 DIVISION OF RF INDUSTRIES, LTD.

7610 MIRAMAR RD  
 SAN DIEGO, CA 92126  
 (858) 549-6340  
 (858) 549-6345 FAX

**SMA JACK**

FOUR HOLE FLANGE, SOLDER

SIZE	CABLE GROUP	DWG NO.	REV
A	SRO	RSA-3570-SS-047	-
SCALE: NTS		CAD FILE OUTLINE	SHEET 1 OF 1