



(P/N)	(STUD)	(H DIA)	(INS. DIA)
型番	サイズ	H-J法	被覆外径
171506-1	#8	4.34	2.03~3.18
-2	#10	5.00	2.03~3.18
-3	#8	4.34	2.67~3.56
-4	#10	5.00	2.67~3.56
<del>OBSELETE</del> -5	#12	5.66	2.03~3.18
-6	特別	5.79	2.67~3.56
-7	5mm	5.26	2.03~3.18
-8	5mm	5.26	2.67~3.56
<del>OBSELETE</del> 171506-9	#6	3.68	2.03~3.18

DIMENSIONS IN MM DO NOT SCALE PRINT

D1 OBSOLETE (F17-0514 F.N 4/7 6-16-93)		171506-1 BY AMP JAPAN		参考図面 (CUSTOMER COPY REFERENCE ONLY)	
D	REVISED (REV-B) P-DWG 2.4.4.5	MATERIAL 有光銅		AMP (JAPAN), LTD. Tokyo, Japan	
C	REVISED (REV-B) 2-DWG S.O 4/11/72	WIRE RANGE 0.26 ~ 1.04 mm AWG22-18		CLASS	
E	ADDED MARK H.S 4/11/72	INSULATION CL. 表参照		TYPE	
A	REVISED (REV-E) 2-DWG H.S 4/11/72	SCALE		LOC SIZE SH NO.	
O	ORIGINAL 1/17/72	TOLERANCE EXCEPT AS NOTED ±0.4 ±0.05 ±0.1		JAC-171506 D1	
LTR 変更 (REVISION RECORD) DR CHK DATE		REV NAME		9 型 端子 RING TERMINAL	