



**Data Sheet Supplement
Version 1.0**

Dynamic Differential Hall Effect Sensor

TLE4928C E6547

For all parameters not specified in this document the TLE4926C-HT E6547 data sheet is valid.



Type	Marking	Ordering Code	Package
TLE4928C E6547	28D8	SP000718274	PG-SSO-3-92

1.1 Absolute Maximum Ratings

No.	Parameter	Symbol	min.	typ.	max.	Unit	Conditions	
1.1.1	Junction temperature	T_j	-40			°C	-	
						155	°C	2000 h (not additive)
						165	°C	1000 h (not additive)
						175	°C	168 h (not additive)
						195	°C	3x1 h (additive to the other life times).

1.2 Operating Range

No.	Parameter	Symbol	min.	typ.	max.	Unit	Conditions	
1.2.1	Operating junction temperature	T_j	-40			°C	-	
						155	°C	2000 h (not additive)
						165	°C	1000 h (not additive)
						175	°C	168 h (not additive) reduced signal quality permissible (e.g. jitter).
1.2.2	Power on time	t_{on}			1	ms	Time to achieve specified accuracy After power on the output of the IC is always in high-state. After internal resets output is locked ¹ .	

1.3 AC/DC Characteristics

Note: Not part of production testing, verified by design and characterization.

No.	Parameter	Symbol	min	typ	max	Unit	Remarks
1.3.1	Frequency range	f	0.006		8	kHz	Operation below 6Hz ²

¹ Output of the IC is locked in present state (high-state or low-state) after an internal reset is launched. This reset happens typically every 195ms when there is no output switching in either case. See also 1.3.2. A voltage reset causes a release of the output and output is in high state after power on again.

² Output will switch if magnetic signal is changing more than $2x |\Delta B_{min}|$ within offset recalibration time even below 6Hz once per magnetic edge, increased phase error is possible.

1.3.2	Offset recalibration time after last output change	t_{reset}	165	195	225	ms	Valid for calibrated mode Output locked to state before recalibration
-------	----------------------------------------------------	--------------------	-----	-----	-----	----	--------------------------------------------------------------------------

Revision History:**November 2009**

Version 1.0

Previous Version: -	
Page	Subjects (major changes since last revision)
-	-

Infineon Technologies AG**© Infineon Technologies AIM SC****All Rights Reserved.**<http://www.infineon.com/products/sensors>**We Listen to Your Comments**

Any information within this document that you feel is wrong, unclear or missing at all?
Your feedback will help us to continuously improve the quality of this document.
Please send your proposal (including a reference to this document) to:

Sensors@infineon.com