


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00426	Connector, USB B receptacle	1	
2	50-00930	Connector, USB B mini male	1	
3	30-00099	Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 3.6mm, shielded, VW-1, PVC, 79A, USB 2.0, white	1	
4	24-00057	Overmold, jack, USB B	1	PVC, white
5	24-00025	Overmold, plug, USB mini B	1	PVC, white



Wiring diagram		
50-00426	Wire Color	50-00930
1	Red	1
2	White	2
3	Green	3
4	Black	5
Shell	Drain & Shield	Shell

Notes:

Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	9/21/2018	Initial release	AW <small>Digitally signed by AW Date: 2018.11.01 14:25:39 -07'00'</small>		
A1	1/29/2018	Corrected shield type	Verified:	Function test: no open, no short circuit, no intermittent	Size: Part number: A 10-00779
A2	10/24/2018	Removed label and updated USB B mini part number	GL <small>Digitally signed by GL Date: 2018.11.02 09:45:42 -07'00'</small>		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 100 mm, USB B receptacle to USB mini B 5P male, 28 AWG, 30-00099 wire, white	Scale: 1:1

5

4

3

2

1