

**MICRO-Interface
MI8A-I/O S SUBD15B**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

General ordering data

| | |
|------------|---|
| Type | MI8A-I/O S SUBD15B |
| Order No. | 8800220000 |
| Version | Adapter, MICRO-Interface, IEC 60603/DIN41612 plug-in connectors, Screw connection |
| GTIN (EAN) | 4032248497157 |
| Qty. | 10 pc(s). |

Data sheet

**MICRO-Interface
MI8A-I/O S SUBD15B**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|-------|------------|--------|
| Length | 32 mm | Width | 61 mm |
| Height | 42 mm | Net weight | 31.8 g |

Temperatures

| | | | |
|-----------------------|-----------|---------------------|--------------|
| Operating temperature | 0...+50°C | Storage temperature | -20...+85 °C |
|-----------------------|-----------|---------------------|--------------|

Connection data

| | | | |
|----------------------------|--|--------------------------------|----------------|
| Connection on control side | IEC 60603/DIN41612 plug-in connectors | Number of poles (control side) | 15-pole female |
| Supply voltage | max. 30 V AC/DC | | |

Ratings data

| | | | |
|-------------------------|---------|--------------------------|-------|
| Operating voltage | 30 V UC | Max. current per channel | 0.5 A |
| Total operating current | 2 A | | |

Insulation coordination (EN50178)

| | | | |
|-------------------------|--------------|--------------------------|-----------|
| According to | DIN EN 50178 | Rated insulation voltage | < 50 V AC |
| Surge voltage category | III | Pollution severity level | 2 |
| Insulation test voltage | 0.35 kVAC | | |

Supply connection

| | |
|--------------------|------------------|
| Type of connection | Screw connection |
|--------------------|------------------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001121 | UNSPSC | 30-21-18-01 |
| eClass 6.2 | 27-24-22-08 | eClass 7.1 | 27-24-22-08 |

Approvals

Approvals



| | |
|------|---------|
| ROHS | Conform |
|------|---------|