


R0.5 MAX. OR CORNER RELIEF (TYP) **RECOMMENDED MOUNTING CUTOUT**
SCALE 2:1

NOTES:

- MATERIALS:**
 ADAPTER BODY - POLYETHERIMIDE (BLACK)
 FLAMMABILITY: UL94 V-0
 SPRING CLIP - STAINLESS STEEL
 DUST PLUGS - POLYCARBONATE
 SURFACE RESISTIVITY: <1E12 ohm/sq
 TML: <1%
 FLAMMABILITY: UL94 V-0

2. KEY ORIENTATION - OPPOSED

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
SYMBOLS	DIMENSION UNITS	SCALE	CURRENT REV DESC:								
	mm	3:1									
▽ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 615471								
▽ = 0	ANGULAR TOL ± 0.5°		DRWN: IGUMIN		2019/04/11		 MTP ADAPTER, REDUCED FLANGE PRODUCT CUSTOMER DRAWING				
▽ = 0	4 PLACES ±		CHK'D: GGENCHANOK		2019/04/11						
▽ = 0	3 PLACES ±		APPR: GGENCHANOK		2019/04/11						
▽ = 0	2 PLACES ±		INITIAL REVISION:				DOCUMENT NUMBER				
▽ = 0	1 PLACE ±		DRWN: KPEVZNER		2006/07/10		SD-106181-0007		DOC TYPE	DOC PART	REVISION
▽ = 0	0 PLACES ±		APPR: IGUMIN		2006/07/11		PSD		001	C1	
■ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
▽ = 0			B-SIZE		106181	1061810007				1 OF 1	