

G3R40MT12J

1200 V 40 mΩ SiC MOSFET




Silicon Carbide MOSFET
N-Channel Enhancement Mode

V_{DS}	=	1200 V
$R_{DS(ON)}(Typ.)$	=	40 mΩ
$I_D(T_c = 100^\circ\text{C})$	=	47 A


Features

- G3R™ (3rd Generation) Technology
- Low Temperature Coefficient of $R_{DS(ON)}$
- Lower Q_G and Smaller $R_{G(INT)}$
- Low Device Capacitances (C_{OSS} , C_{RSS})
- LoRing™ - Electromagnetically Optimized Design
- Superior Cost-Performance Index
- Robust Body Diode with Low V_F and Low Q_{RR}
- 100% Avalanche (UIL) Tested

Package



TO-263-7



Advantages

- Compatible with Commercial Gate Drivers
- Low Conduction Losses at all Temperatures
- Faster and More Efficient Switching
- Lesser Switching Spikes and Lower Losses
- Reduced Ringing
- Better Power Density and System Efficiency
- Ease of Paralleling without Thermal Runaway
- Superior Robustness and System Reliability

Applications

- Solar Inverters
- EV/HEV Charging
- Motor Drives
- High Voltage DC-DC Converters
- Switched Mode Power Supplies
- UPS
- Smart Grid Transmission and Distribution
- Induction Heating and Welding

Absolute Maximum Ratings (At $T_c = 25^\circ\text{C}$ Unless Otherwise Stated)

Parameter	Symbol	Conditions	Values	Unit	Note
Drain-Source Voltage	$V_{DS(\text{max})}$	$V_{GS} = 0 \text{ V}$, $I_D = 100 \mu\text{A}$	1200	V	
Gate-Source Voltage (Dynamic)	$V_{GS(\text{max})}$		-10 / +22	V	
Gate-Source Voltage (Static)	$V_{GS(\text{op})-\text{ON}}$ $V_{GS(\text{op})-\text{OFF}}$	Recommended Operation	+15 to +18 -5 to -3	V	
Continuous Forward Current	I_D	$T_c = 25^\circ\text{C}$, $V_{GS} = -5 / +15 \text{ V}$ $T_c = 100^\circ\text{C}$, $V_{GS} = -5 / +15 \text{ V}$ $T_c = 135^\circ\text{C}$, $V_{GS} = -5 / +15 \text{ V}$	66 47 34	A	Fig. 15
Pulsed Drain Current	$I_{D(\text{pulse})}$	$t_P \leq 3 \mu\text{s}$, $D \leq 1\%$, $V_{GS} = 15 \text{ V}$, Note 1	150	A	Fig. 14
Power Dissipation	P_D	$T_c = 25^\circ\text{C}$	330	W	Fig. 16
Non-Repetitive Avalanche Energy	E_{AS}	$L = 2.4 \text{ mH}$, $I_{AS} = 17.5 \text{ A}$	374	mJ	
Operating and Storage Temperature	T_j , T_{stg}		-55 to 175	°C	

Thermal/Package Characteristics

Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Thermal Resistance, Junction - Case	R_{thJC}			0.45		°C/W	Fig. 13
Weight	W_T			1.45		g	



Electrical Characteristics (At $T_C = 25^\circ\text{C}$ Unless Otherwise Stated)

Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	V_{DSS}	$V_{GS} = 0 \text{ V}, I_D = 100 \mu\text{A}$	1200			V	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 1200 \text{ V}, V_{GS} = 0 \text{ V}$		1		μA	
Gate Source Leakage Current	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = 22 \text{ V}$ $V_{DS} = 0 \text{ V}, V_{GS} = -10 \text{ V}$		100	-100	nA	
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 18.0 \text{ mA}$ $V_{DS} = V_{GS}, I_D = 18.0 \text{ mA}, T_j = 175^\circ\text{C}$	1.8	2.70	2.05	V	Fig. 9
Transconductance	g_{fs}	$V_{DS} = 10 \text{ V}, I_D = 35 \text{ A}$ $V_{DS} = 10 \text{ V}, I_D = 35 \text{ A}, T_j = 175^\circ\text{C}$		16.1	18.1	S	Fig. 4
		$V_{GS} = 15 \text{ V}, I_D = 35 \text{ A}$		40			
Drain-Source On-State Resistance	$R_{DS(\text{ON})}$	$V_{GS} = 15 \text{ V}, I_D = 35 \text{ A}, T_j = 175^\circ\text{C}$ $V_{GS} = 18 \text{ V}, I_D = 35 \text{ A}$ $V_{GS} = 18 \text{ V}, I_D = 35 \text{ A}, T_j = 175^\circ\text{C}$		57	34	45	mΩ
				50			
Input Capacitance	C_{iss}			2897			
Output Capacitance	C_{oss}			88		pF	Fig. 11
Reverse Transfer Capacitance	C_{rss}			7.1			
C_{oss} Stored Energy	E_{oss}			34		μJ	Fig. 12
C_{oss} Stored Charge	Q_{oss}			128		nC	
Effective Output Capacitance (Energy Related)	$C_{o(er)}$			106		pF	Note 2
Effective Output Capacitance (Time Related)	$C_{o(tr)}$			160			
Gate-Source Charge	Q_{gs}	$V_{DS} = 800 \text{ V}, V_{GS} = -5 / +15 \text{ V}$		29			
Gate-Drain Charge	Q_{gd}	$I_D = 35 \text{ A}$		28		nC	Fig. 10
Total Gate Charge	Q_g	Per IEC607478-4		88			
Internal Gate Resistance	$R_{G(\text{int})}$	$f = 1 \text{ MHz}, V_{AC} = 25 \text{ mV}$		1.2		Ω	
Turn-On Switching Energy (Body Diode)	E_{on}	$T_j = 25^\circ\text{C}, V_{GS} = -5/+15 \text{ V}, R_{G(\text{ext})} = 4 \Omega, L = 40.0 \mu\text{H}, I_D = 35 \text{ A}, V_{DD} = 800 \text{ V}$		238		μJ	Fig. 22,26
Turn-Off Switching Energy (Body Diode)	E_{off}			66			
Turn-On Delay Time	$t_{d(on)}$			27			
Rise Time	t_r	$V_{DD} = 800 \text{ V}, V_{GS} = -5/+15 \text{ V}$		15			
Turn-Off Delay Time	$t_{d(off)}$	$R_{G(\text{ext})} = 4 \Omega, L = 40.0 \mu\text{H}, I_D = 35 \text{ A}$		18		ns	Fig. 24
Fall Time	t_f	Timing relative to V_{DS} , Inductive load		10			

Note 1: Pulse Width t_p Limited by $T_{j(\text{max})}$

Note 2: $C_{o(er)}$, a lumped capacitance that gives same stored energy as C_{oss} while V_{DS} is rising from 0 to 800V.
 $C_{o(tr)}$, a lumped capacitance that gives same charging times as C_{oss} while V_{DS} is rising from 0 to 800V.




Reverse Diode Characteristics

Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Diode Forward Voltage	V_{SD}	$V_{GS} = -5 \text{ V}, I_{SD} = 17 \text{ A}$		4.8		V	Fig. 17-18
		$V_{GS} = -5 \text{ V}, I_{SD} = 17 \text{ A}, T_j = 175^\circ\text{C}$		4.3			
Continuous Diode Forward Current	I_S	$V_{GS} = -5 \text{ V}, T_c = 100^\circ\text{C}$	29			A	
Diode Pulse Current	$I_{S(pulse)}$	$V_{GS} = -5 \text{ V}$, Note 1		116		A	
Reverse Recovery Time	t_{rr}			19		ns	
Reverse Recovery Charge	Q_{rr}	$V_{GS} = -5 \text{ V}, I_{SD} = 35 \text{ A}, V_R = 800 \text{ V}$ $dif/dt = 1000 \text{ A}/\mu\text{s}, T_j = 25^\circ\text{C}$		120		nC	
Peak Reverse Recovery Current	I_{rrm}			5		A	
Reverse Recovery Time	t_{rr}			29		ns	
Reverse Recovery Charge	Q_{rr}	$V_{GS} = -5 \text{ V}, I_{SD} = 35 \text{ A}, V_R = 800 \text{ V}$ $dif/dt = 1000 \text{ A}/\mu\text{s}, T_j = 175^\circ\text{C}$		300		nC	
Peak Reverse Recovery Current	I_{rrm}			9		A	


G3R40MT12J
1200 V 40 mΩ SiC MOSFET

Figure 1: Output Characteristics ($T_j = 25^\circ\text{C}$)




$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

Figure 2: Output Characteristics ($T_j = 175^\circ\text{C}$)




$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

Figure 3: Output Characteristics ($V_{GS} = 15 \text{ V}$)



$I_D = f(V_{DS}, T_j)$; $t_P = 250 \mu\text{s}$


Figure 4: Transfer Characteristics ($V_{DS} = 10 \text{ V}$)



$I_D = f(V_{GS}, T_j)$; $t_P = 100 \mu\text{s}$


G3R40MT12J
1200 V 40 mΩ SiC MOSFET

Figure 5: On-State Resistance v/s Temperature




$$R_{DS(ON)} = f(T_j, V_{GS}); t_P = 250 \mu\text{s}; I_D = 35 \text{ A}$$

Figure 6: On-State Resistance v/s Drain Current




$$R_{DS(ON)} = f(T_j, I_{DS}); t_P = 250 \mu\text{s}; V_{GS} = 15 \text{ V}$$

Figure 7: Normalized On-State Resistance v/s Temperature



$$R_{DS(ON)} = f(T_j); t_P = 250 \mu\text{s}; I_D = 35 \text{ A}; V_{GS} = 15 \text{ V}$$


Figure 8: On-State Resistance v/s Gate Voltage



$$R_{DS(ON)} = f(T_j, V_{GS}); t_P = 250 \mu\text{s}; I_D = 35 \text{ A}$$


G3R40MT12J
1200 V 40 mΩ SiC MOSFET

Figure 9: Threshold Voltage Characteristics




$V_{GS(th)} = f(T_j)$; $V_{DS} = V_{GS}$; $I_D = 18.0$ mA

Figure 10: Gate Charge Characteristics




$I_D = 35$ A; $V_{DS} = 800$ V; $T_c = 25^\circ\text{C}$

Figure 11: Capacitance v/s Drain-Source Voltage



$f = 1$ MHz; $V_{AC} = 25$ mV


Figure 12: Output Capacitor Stored Energy



$E_{oss} = f(V_{DS})$


G3R40MT12J
1200 V 40 mΩ SiC MOSFET

Figure 13: Transient Thermal Impedance




$$Z_{th,ic} = f(t_p, D); D = t_p/T$$

Figure 14: Safe Operating Area ($T_c = 25^{\circ}\text{C}$)




$$I_D = f(V_{DS}, t_p); T_j \leq 175^{\circ}\text{C}; D = 0$$

Figure 15: Current De-rating Curve



$$V_{GS} = 15\text{ V}; I_D = f(T_c); T_j \leq 175^{\circ}\text{C}$$

Figure 16: Power De-rating Curve




$$P_D = f(T_c); T_j \leq 175^{\circ}\text{C}$$




G3R40MT12J
1200 V 40 mΩ SiC MOSFET

Figure 17: Body Diode Characteristics ($T_j = 25^\circ\text{C}$)




$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

Figure 18: Body Diode Characteristics ($T_j = 175^\circ\text{C}$)




$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

Figure 19: Third Quadrant Characteristics ($T_j = 25^\circ\text{C}$)



$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

Figure 20: Third Quadrant Characteristics ($T_j = 175^\circ\text{C}$)




$I_D = f(V_{DS}, V_{GS})$; $t_P = 250 \mu\text{s}$

G3R40MT12J


1200 V 40 mΩ SiC MOSFET

Figure 21: Inductive Switching Energy v/s Drain Current ($V_{DD} = 600V$)




$T_j = 25^\circ C; V_{GS} = -5/+15V; R_{G(ext)} = 4 \Omega; L = 40.0\mu H$

Figure 22: Inductive Switching Energy v/s Drain Current ($V_{DD} = 800V$)




$T_j = 25^\circ C; V_{GS} = -5/+15V; R_{G(ext)} = 4 \Omega; L = 40.0\mu H$

Figure 23: Inductive Switching Energy v/s $R_{G(ext)}$ ($V_{DD} = 800V$)



$T_j = 25^\circ C; V_{GS} = -5/+15V; I_{DS} = 35 A; L = 40.0\mu H$


Figure 24: Switching Time v/s $R_{G(ext)}$ ($V_{DD} = 800V$)



$T_j = 25^\circ C; V_{GS} = -5/+15V; I_{DS} = 35 A; L = 40.0\mu H$


G3R40MT12J
1200 V 40 mΩ SiC MOSFET

**Figure 25: Inductive Switching Energy v/s Temperature
 $(V_{DD} = 800V)$**




$T_j = 25^\circ\text{C}$; $V_{GS} = -5/+15\text{V}$; $R_{G(\text{ext})} = 4 \Omega$; $I_{DS} = 35 \text{ A}$; $L = 40.0\mu\text{H}$

**Figure 26: dV/dt v/s $R_{G(\text{ext})}$
 $(V_{DD} = 800V)$**




$T_j = 25^\circ\text{C}$; $V_{GS} = -5/+15\text{V}$; $I_{DS} = 35 \text{ A}$; $L = 40.0\mu\text{H}$


Gate Charge Circuit




Gate Charge Waveform




Switching Time Circuit




Switching Time Waveform




Switching Energy Circuit




Switching Energy Waveform



Reverse Recovery Circuit




Reverse Recovery Waveform




Package Dimensions


TO-263-7 Package Outline



Recommended Solder Pad Layout



Package View



NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS.
3. THE SOURCE AND KELVIN-SOURCE PINS ARE NOT INTERCHANGABLE. THEIR EXCHANGE MIGHT LEAD TO MALFUNCTION.

Compliance

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS 2), as adopted by EU member states on January 2, 2013 and amended on March 31, 2015 by EU Directive 2015/863. RoHS Declarations for this product can be obtained from your GeneSiC representative.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a GeneSiC representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Disclaimer

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice. GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

Related Links

- SPICE Models: https://www.genesicsemi.com/sic-mosfet/G3R40MT12J/G3R40MT12J_SPICE.zip
- PLECS Models: https://www.genesicsemi.com/sic-mosfet/G3R40MT12J/G3R40MT12J_PLECS.zip
- CAD Models: https://www.genesicsemi.com/sic-mosfet/G3R40MT12J/G3R40MT12J_3D.zip
- Gate Driver Reference: <https://www.genesicsemi.com/technical-support>
- Evaluation Boards: <https://www.genesicsemi.com/technical-support>
- Reliability: <https://www.genesicsemi.com/reliability>
- Compliance: <https://www.genesicsemi.com/compliance>
- Quality Manual: <https://www.genesicsemi.com/quality>

Revision History

- Rev 23/Feb: Updated with Most Recent Data
- Supersedes: Rev 20/Jun, Rev 20/Aug, Rev 21/Jan, Rev 21/May



www.genesicsemi.com/sic-mosfet/