




LVO-MCL-22-AN

Ruland LVO-MCL-22-AN, 22mm One-Piece Shaft Collar with Clamping Lever, Anodized Aluminum Collar with Zinc Plated Lever, 42mm OD, 15mm Width





Description

Ruland LVO-MCL-22-AN is a one-piece quick clamping shaft collar with clamping lever with a 22mm bore, 42mm OD, and 15mm width. It is made from MCL-22-AN and LF45-CL-M6:18-ZS. The clamp style design does not mar the shaft, is easy to remove, and is indefinitely adjustable. The threaded stud on the lever is used in place of standard collar hardware. When combined, the two parts create a shaft collar that requires no tools to install, remove, or reposition and is ideally suited for packaging, printing, and other applications where frequent setup changes and adjustments are needed. Once the lever is installed in the shaft collar, users simply turn the lever until they meet their desired torque. The adjustable lever can be reposition by the user without the loss of holding power by lifting the handle and twisting it 40° to lock it in a new position. This allows for use in space constrained environments where 360° rotation is not possible to fully seat the lever. MCL-22-AN is made from high-strenth 2024 aluminum with a black anodized finish. LF45-CL-M6:18-ZS has a zinc plated steel handle and stainless steel threaded stud. This material combination allows for a lightweight durable quick clamping and release component that is suitable for most industrial applications and has higher corrosion resistance properties than types with no anodize. The lever is orange for safety and ease of identification. MCL-22-AN is manufactured by Ruland and LF45-CL-M6:18-ZS is manufactured by Otto Ganter. LVO-MCL-22-AN is RoHS3 and REACH compliant.

Product Specifications

	r rouuci opecifications			
Width (W)15 mmWidth Tolerance+0.076 mm / -0.254 mmLever Length L145 mmLever Height H238.5 mmHub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque9.6 NmScrew Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Bore (B)	22 mm	Bore Tolerance	+0.050 mm / +0.012 mm
Lever Length L145 mmLever Height H238.5 mmHub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque9.6 NmScrew Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Outer Diameter (OD)	42 mm	Center to Lever Top H1	38.8 mm
Hub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque9.6 NmScrew Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Width (W)	15 mm	Width Tolerance	+0.076 mm / -0.254 mm
Recommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque9.6 NmScrew Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-QCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Lever Length L1	45 mm	Lever Height H2	38.5 mm
Hex Wrench Size5.0 mmSeating Torque9.6 NmScrew Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine sublity for a particular application	Hub Diameter DH	13 mm	Sleeve Length L2	18 mm
Screw Location (R)16.00 mmNumber of Screws1 eaCollar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-QCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Recommended Shaft Tolerance	+0.000 mm / -0.013 mm	Thread TH	M6
Collar Part NumberMCL-22-ANLever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Hex Wrench Size	5.0 mm	Seating Torque	9.6 Nm
Collar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Screw Location (R)	16.00 mm	Number of Screws	1 ea
Handle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitbility for a particular application	Collar Part Number	MCL-22-AN	Lever Part Number	LF45-CL-M6:18-ZS-O
Handle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Collar Material	Aluminum	Collar Finish	Black Anodized
Manufacturer Ruland Manufacturing Country of Origin Shaft Collar - USA Lever - Germany Weight (lbs) 0.182300 UPC 634529293669 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Handle Color	Orange	Handle Material	Zinc
Weight (lbs) 0.182300 UPC 634529293669 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Handle Finish	Powder Coated	Insert and Screw Material	303 Stainless Steel
Weight (lbs)0.182300UPC634529293669Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Manufacturer	Ruland Manufacturing	Country of Origin	Shaft Collar - USA
Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application				Lever - Germany
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Weight (lbs)	0.182300	UPC	634529293669
	Tariff Code	8483.60.8000	UNSPC	31162811
Prop 65	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	AWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), known		

to the State of California to cause cancer