

MALE INSERT FRONT VIEW		
3 POLE	4 POLE	5 POLE
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK 5 GREY

ENTER DESCRIPTION EC NO: WEU2010-0057 DRW: BWOODMAN_MEU 2009/08/19 CHKD: APPR: JFMURPHY 2009/08/21	DESCRIPTION QUALITY SYMBOLS ▼=0 ▽=0
--	--

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	INCH
4 PLACES ±	± .005
3 PLACES ±	± .005
2 PLACES ±	± .01
1 PLACE ±	± .03
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	




DIMENSION STYLE	
IN/MM	
DRAWN BY	DATE
BWOODMAN	18/08/09
CHECKED BY	DATE
RSTONE	18/08/09
APPROVED BY	DATE
JFMURPHY	18/08/09
MATERIAL NO.	DOCUMENT NO.
SEE CHART	SD-120027-002

SCALE 5:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
TITLE NC 3P M/MP 2M COUPLER 24AWG PU		
MOLEX INCORPORATED		SHEET NO. 1 OF 2
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

ASSEMBLY		
3 POLE	4 POLE	5 POLE

SL.No	DESCRIPTION	MATERIAL	FINISH	QTY		
1	STAMP & FORM CONTACT	COPPER ALLOY	GOLD PLATED	3		
2	SCREW MACHINE CONTACT	COPPER ALLOY	GOLD PLATED		4	5
3	SLEEVE	BRASS	NICKEL PLATED	1	1	1
4	COUPLING NUT	BRASS	NICKEL PLATED			
5	LABEL	PLASTIC FILM	BLACK/YELLOW			
6	OVER MOLD	TPE	YELLOW			
7	CABLE, 24 AWG, 3 CONDUCTOR	PUR JACKET	YELLOW	1		
	CABLE, 24 AWG, 4 CONDUCTOR	PUR JACKET	YELLOW		1	
	CABLE, 24 AWG, 5 CONDUCTOR	PUR JACKET	YELLOW			1
8	INSERT MALE 3 POLE	PUR	BLACK	1		
	INSERT MALE 4 POLE	PUR	BLACK		1	
	INSERT MALE 5 POLE	PUR	BLACK			1

PART NUMBER	DESCRIPTION	FINISHED LENGTH
1200270911	403006P03M020	2M +90MM -0 [6' 6" +3.5" -0]
1200270453	403006P03M040	4M +150MM -0 [13' 1" +6" -0]
1200860474	403006P03M050	5M +150MM -0 [16' 4" +6" -0]
1200860583	403006P03M060	6M +150MM -0 [19' 7" +6" -0]
1200270933	403006P03M100	10M +300MM -0 [32' 4" +12" -0]
1200270960	404006P03M020	2M +90MM -0 [6' 6" +3.5" -0]
1200860584	404006P03M040	4M +150MM -0 [13' 1" +6" -0]
1200271017	404006P03M050	5M +150MM -0 [16' 4" +6" -0]
1200860585	404006P03M060	6M +150MM -0 [19' 7" +6" -0]
1200271137	404006P03M100	10M +300MM -0 [32' 4" +12" -0]
1200270752	405006P03M020	2M +90MM -0 [6' 6" +3.5" -0]
1200860586	405006P03M040	4M +150MM -0 [13' 1" +6" -0]
1200270657	405006P03M050	5M +150MM -0 [16' 4" +6" -0]
1200860587	405006P03M060	6M +150MM -0 [19' 7" +6" -0]
1200860588	405006P03M100	10M +300MM -0 [32' 4" +12" -0]

ENTER DESCRIPTION EC NO: WEU2010-0057 DRWN: BWOODMAN_WEU2009/08/19 CHKD: APPR: JFMURPHY 2009/08/21 REV: A	QUALITY SYMBOLS  = 0  = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM	SCALE 5:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION		
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± .01 1 PLACE ± 0.3 ± ---	mm INCH ± --- ± --- ± --- ± --- ± --- ± ---	DRAWN BY BWOODMAN	DATE 18/08/09	TITLE NC 3P M/MP 2M COUPLER 24AWG PU			
		ANGULAR ±1/2°		CHECKED BY RSTONE	DATE 18/08/09	MOLEX INCORPORATED			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY JFMURPHY	DATE 18/08/09	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-120027-002	SHEET NO. 2 OF 2