


CP4LG2.5



4 Level Terminal Block
Bottom Ground

Dimensions & Weight

Width / Length	5 mm / 118.6 mm
Height w DIN Rail	35 x 7.5 mm
	35 x 15 mm
Weight per piece	26.5 g

Technical Data/Ratings

Approvals		
Wire Size (solid / stranded)	22-12 AWG	0.34-2.5 mm ²
Voltage Rating	300 V	500V
Current Rating	20 A (Top 3 Levels)	24 A (Top 3 Levels)
Insulation Material	Polyamide 66	

Installation Instructions

Wire Stripping Length	10 mm
Screwdriver	SCM0.4/2.5 (0.4 x 2.5 mm blade)

Terminal Blocks	Cat. No.	Std. Pk.
Ground/ Earth Yellow / Green	CP4LG2.5	30

Jumpers		Cat. No.	Imax	Std. Pk.
Shorting Link/	2 pole	CA801/A2	24A	100
Jumpers	3 pole	CA801/A3	24A	100
	4 pole	CA801/A4	24A	100
	10 pole	CA801/A10	24A	10

Accessories	Cat. No.	Std. Pk.
End Plate	EPCP4LG2.5	30
DIN Rail	2511120	20
	CA701-15/S	20
End Stop	CA202 / CA103	50
Marking Tag	MT2G	1 Pk. (100 tags)