

# Replacement die - CRIMPFOX-M 10/DIE - 1212080

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Die, for Crimpfox-M, for ferrules 0.25 - 10 mm<sup>2</sup>, packed in a serial storage box

## Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 280 (CL2-2011)
GTIN	 4 046356 454506
Custom tariff number	82032000
Country of origin	SWEDEN

## Technical data

### General

Length (b)	114 mm
Height	25.5 mm
Width (a)	75 mm
Color	black
Weight	86 g
Die station	Crimping position 1
Min. cross section	0.25 mm <sup>2</sup>
Max. cross section	0.75 mm <sup>2</sup>
AWG min	24
AWG max	20
Die station	Crimping position 2
Min. cross section	1 mm <sup>2</sup>
Max. cross section	1.5 mm <sup>2</sup>
AWG min	18
AWG max	16
Die station	Crimping position 3
Max. cross section	2.5 mm <sup>2</sup>
AWG max	14
Die station	Crimping position 4
Max. cross section	4 mm <sup>2</sup>

# Replacement die - CRIMPFOX-M 10/DIE - 1212080

## Technical data

### General

AWG max	12
Die station	Crimping position 5
Max. cross section	10 mm <sup>2</sup>
AWG max	10
Compression	Trapezoidal crimp
Type of contact	Ferrules

## Classifications

### eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811

### etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

### unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Approvals

### Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

## Replacement die - CRIMPFOX-M 10/DIE - 1212080

### Approvals

#### Approval details

GOST 