

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification  
ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>  
Prop 65 Statement: <https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

**Footnote:**

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

**Limitation of Use:**

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.  
Contents of this document are subject to change without prior notice.

**Customer Approval of Specification:**

Please approve, sign and send back to GlobTek so we can complete order processing.  
A delay in receipt of this form will delay delivery schedule.

Company Name: _____	Customer P/N: _____
Quote Number: _____	Date: _____
Authorized Representative Name: _____	Authorized Representative Signature: _____

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	
Part No./Ordering No. PZ0800100-2M5BK13H(R)		Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

## REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
N	Add UKCA and CE marking to the IEC320/C13 connector	bsiep	07/15/2021	QA
M	Update to SF format; add Singapore, Malaysia, Hong Kong, Saudi Arabia, and Gulf States approvals. Connector approval updated from individual EU approvals to ENEC-VDE.	bsiep	10/09/2020	QA
L	UPDATE ASTA LICENSE	jsund	02/02/2012	QA

**Cordset Information:**

CordsetColor:GlobTek Black


Cord Length (mm):2500

**NOTES:**

BS 1363A fused @ 10A

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black
	Model No. Power Cord
Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N


CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black
	Model No. Power Cord
Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

CABLE IMAGE


















PROPRIETARY INFORMATION

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	Part No./Ordering No. PZ0800100-2M5BK13H(R)
		Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A Code:PZ0800 Description:UK Plug (Type G), BS1363A, Fused at 10A Rating (V):250 Rating (A):10.0 Gender:Male Overmolded:Yes	Cable Code:427 Description:GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227 Color:GlobTek Black Wire Gauge(AWG):1.0mmsq Cond:3 Type:H05VV-F Temperature:70° C Amps:10 Volts:500 OD:7.1 ConductorsColors:BLU/BRN/GRN-YW	End B Code:701-VDE-ENEC-CE-UKCA Description:IEC320-C13 Rating (V):250 Rating (A):10.0 Gender:Female Overmolded:Yes
---	--	--

Overall cable rating:250VAC 10A

Plug Approvals	Cable Approvals	Connector Approvals
 United Kingdom ASTA Diamond Approval Mark   SAFETY MARK   Saudi Arabia SASO safety mark (file # only -- SASO 2203)  Malaysia (File number)	 UL  DIN  NEMA  VDE  IEC  CE  CCC  TUV  BSI European approvals  BS1363/A plug	 EN 10  VDE ENEC-VDE   UK CA UKCA Certification

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	Part No./Ordering No. PZ0800100-2M5BK13H(R)
		Rev N


CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

		CE Certification
AGENCY ONLINE DOCUMENTS	<a href="http://en.globtek.com/cordsets/">http://en.globtek.com/cordsets/</a>	
RoHS/RoHS3 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/01t30000002p98nAAA">https://www.globtek.com/pdf/rohs_cert/01t30000002p98nAAA</a>	
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>	
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>	
Prop 65 Statement	<a href="https://en.globtek.com/prop-65-statement.pdf">https://en.globtek.com/prop-65-statement.pdf</a>	
CE.UKCA.Cord	<a href="https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t30000002p98n">https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t30000002p98n</a>	
IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.		

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	Rev N
Part No./Ordering No. PZ0800100-2M5BK13H(R)		Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:200  
 Description:200 +/- 20mm  
 Image:



Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):