

TRI-STATE OCTAL BUFFERS

The SN54/74LS795 thru SN54/74LS798 device types provide a second source for the 71/81LS95 thru 71/81LS98 series. These devices are octal low power Schottky versions of the 70/8095 thru 70/8098 3-STATE Hex Buffers. The LS795 and LS797 are noninverting and the LS796 and LS798 are inverting functions. On each buffer, one of the two inputs is used as a control line to gate the output into the high impedance state, while the other input passes the data through the buffer. On the LS795 and LS796 access is through a 2-input NOR gate, with all eight 3-STATE enable lines common. On the LS797 and LS798, four buffers are enabled from one common line and the other four buffers from another common line. On all device types the 3-STATE condition is achieved by applying a high logic level to the enable pins.

TRUTH TABLES

LS795

| INPUTS | | | OUTPUT |
|--------|-------------|---|--------|
| G1 | \bar{G}_2 | A | Y |
| H | X | X | Z |
| X | H | X | Z |
| L | L | H | H |
| L | L | L | L |

LS796

| INPUTS | | | OUTPUT |
|-------------|-------------|---|--------|
| \bar{G}_1 | \bar{G}_2 | A | Y |
| H | X | X | Z |
| X | H | X | Z |
| L | L | H | L |
| L | L | L | H |

LS797

| INPUTS | | OUTPUT |
|-----------|---|--------|
| \bar{G} | A | Y |
| H | X | Z |
| L | H | H |
| L | L | L |

LS798

| INPUTS | | OUTPUT |
|-----------|---|--------|
| \bar{G} | A | Y |
| H | X | Z |
| L | H | L |
| L | L | H |

GUARANTEED OPERATING RANGES

| Symbol | Parameter | | Min | Typ | Max | Unit |
|-----------------|-------------------------------------|----------|-------------|------------|--------------|------|
| V _{CC} | Supply Voltage | 54 74 | 4.5 4.75 | 5.0 5.0 | 5.5 5.25 | V |
| T _A | Operating Ambient Temperature Range | 54 74 | -55 0 | 25 25 | 125 70 | °C |
| I _{OH} | Output Current — High | 54 74 | | | -2.6 -5.0 | mA |
| I _{OL} | Output Current — Low | 54 74 | | | 8.0 16 | mA |


**SN54/74LS795
SN54/74LS796
SN54/74LS797
SN54/74LS798**

TRI-STATE OCTAL BUFFERS


LOW POWER SCHOTTKY



J SUFFIX
CERAMIC
CASE 732-03



N SUFFIX
PLASTIC
CASE 738-03







DW SUFFIX
SOIC
CASE 751D-03

ORDERING INFORMATION

SN54LSXXXJ Ceramic
SN74LSXXXN Plastic
SN74LSXXXDW SOIC

**SN54/74LS795 • SN54/74LS796
SN54/74LS797 • SN54/74LS798**

LOGIC DIAGRAMS



SN54/74LS795 THRU SN54/74LS798

DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

| Symbol | Parameter | Limits | | | Unit | Test Conditions |
|------------------|--|--------|-------|------|------|---|
| | | Min | Typ | Max | | |
| V _{IH} | Input HIGH Voltage | 2.0 | | | V | Guaranteed Input HIGH Voltage for All Inputs |
| V _{IL} | Input LOW Voltage | 54 | | 0.7 | V | Guaranteed Input LOW Voltage for All Inputs |
| | | 74 | | 0.8 | | |
| V _{IK} | Input Clamp Diode Voltage | | -0.65 | -1.5 | V | V _{CC} = MIN, I _{IN} = -18 mA |
| V _{OH} | Output HIGH Voltage | 54 | 2.5 | 3.5 | V | V _{CC} = MIN, I _{OH} = MAX |
| | | 74 | 2.7 | 3.5 | | |
| V _{OL} | Output LOW Voltage | 54, 74 | | 0.25 | V | I _{OL} = 8.0 mA |
| | | | | 0.35 | V | I _{OL} = 16 mA |
| I _{OZH} | Output Off Current — HIGH | | | 20 | μA | V _{CC} = MAX, V _{OUT} = 2.7 V |
| I _{OZL} | Output Off Current — LOW | | | -20 | μA | V _{CC} = MAX, V _{OUT} = 0.4 V |
| I _{IH} | Input HIGH Current | | | 20 | μA | V _{CC} = MAX, V _{IN} = 2.7 V |
| | | | | -0.1 | mA | V _{CC} = MAX, V _{IN} = 7.0 V |
| I _{IL} | Input LOW Current A Input, Both G at 0.4 V G Input | | | -0.4 | mA | V _{CC} = MAX, V _{IN} = 0.4 V |
| | | | | -0.4 | mA | V _{CC} = MAX, V _{IN} = 0.5 V |
| I _{OS} | Short Circuit Current (Note 1) | -30 | | -130 | mA | V _{CC} = MAX |
| I _{CC} | Power Supply Current LS795/LS797 | | | 26 | mA | V _{CC} = MAX |
| | LS795/LS798 | | | 21 | mA | |

Note 1: Not more than one output should be shorted at a time, nor for more than 1 second.

5

AC CHARACTERISTICS (T_A = 25°C)

| Symbol | Parameter | Limits | | | | | | Unit | Test Conditions | | |
|--------------------------------------|---------------------|-------------|----------|----------|-------------|-----------|----------|------|---|--|--|
| | | LS795/LS797 | | | LS796/LS798 | | | | | | |
| | | Min | Typ | Max | Min | Typ | Max | | | | |
| t _{PLH} t _{PHL} | Propagation Delay | | 11 15 | 16 22 | | 6.0 13 | 10 17 | ns | V _{CC} = 5.0 V C _L = 15 pF | | |
| t _{PZH} t _{PZL} | Output Enable Time | | 16 13 | 25 20 | | 17 16 | 27 25 | ns | | | |
| t _{PHZ} t _{PLZ} | Output Disable Time | | 13 19 | 20 27 | | 13 18 | 20 27 | ns | C _L = 5.0 pF | | |