











RoHS Compliant



PX-279/PX-275

PCIe 8xRS232 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 8 port RS232
- PCI Express x1, x4, x8 x16 lane slots socket
- 32 Byte Tx and 32 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PX-279: PCIe 8xRS232 1MBaud

PX-275: PCle 8xRS232 DB25 1MBaud



Description

PCI Express Card providing eight RS232 serial ports connected using 9 pin cables. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 2000, XP, Server 2003, Vista, Server 2008 and Windows 7.

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows Server 2003 32 bit 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER Description PCIe 8xRS232 1MBaud PCIe 8xRS232 DB25 1MBaud

Code PX-279 PX-275

PX-279/PX-275



PCle 8xRS232 1MBaud

PX-279/PX-275: Full Specification

17(275)17(275). Tuli specific	ation	17/273/17/273. Full Specification		
Port	Ports	8 x RS232		
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	DB9 Connector - 9 Pin Male		
Pin 2 RXD Pin 1 Pin 5 Pin 3 TXD	FIFO size	32 RX FIFO + 32 TX FIFO		
Pin 4 DTR Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard		
Fin 7 RTS Pin 6 Pin 9 RT Pin 9 RT Pin 9 RT Pin 6 Pin 9 RT Pin 6 Pin 9 PT PT PT PT PT PT PT	Cable	8 port cable 78 way D to 8x9 Pin Male		
Port Settings	Baud Rate	921,600		
921,600	Data Bits	5,6,7 or 8		
>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Parity	Odd, Even, None, Mark or Space		
baud	Stop Bits	1, 1.5 or 2		
	Flow Control	RTS/CTS, DSR/DTR, XON/XOFF		
	Tx/Rx Modes	Point to Point		
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions		
Fig. 1 (DCD) RS222 Pinost (9 Fin Male)		Windows Server 2008 32 bit 64 bit Editions		
Fig. 2 (200) Fig. 3 (200) Fig. 4 (201) Fig. 5 (200) Fig. 6 (200) Fig. 6 (200) Fig. 6 (200) Fig. 6 (200) Fig. 7 (200) Fig. 7 (200) Fig. 7 (200) Fig. 8 (200) Fig. 8 (200) Fig. 9 (200) Fig. 1 (200) Fig.		Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions		
Find CTS Find F		Windows XP 32 bit 64 bit Editions		
	BUS	PCI Express x1, x4, x8 x16 lane slots		
Approvals	Other Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE ROHS METL EMC: CE TAA		
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit editions Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions		
General	PCB Layers	4		
	Power Consumption	490mA @ 3.3V, 210mA @ 12V		
	Weight	0.12 kg		
	Size	165l x 18w x 120h mm		
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities		
	Card	PCIe 8xRS232 1MBaud		
		8 port cable 78 way D to 8x9 Pin Male		
Product Support	Warranty	Lifetime (online registration required)		
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly		
		staff who work in and alongside the Product Development Team		
Additional	OEM option	Available for bulk buy OEM		
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"		
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com		

Other PCI Express Cards: 1 Port RS232 | 2 Port RS232 | 4 Port RS232 | 8 Port RS232 | 1 Port RS422/485 | 2 Port RS422/485 | 4 Port RS422/485 Other Brainboxes Ranges: PCI | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial