

## SCSI/Fibre Channel - 3-ft. SCSI Cable HD68M to centronic 50M Double Shielded

MODEL NUMBER: **S432-003**



### Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors

### System Requirements

- Any external device or SCSI controller card requiring a HD68 or C50 interface

### Package Includes

- 3-ft. SCSI cable HD68M to Centronic 50M double shielded

### Description

Multi-platform SCSI III to I external peripheral cable HD68M/C50M. This 3ft cable is designed to connect two SCSI III (fast and wide) or SCSI I devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

### Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

## Specifications

OVERVIEW	
UPC Code	037332014177
PHYSICAL	
Cable Length (ft.)	3
Cable Length (m)	0.91
Shipping Dimensions (hwd / in.)	11.75 x 7.00 x 0.75

Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 1.90
Shipping Weight (lbs.)	0.58
Shipping Weight (kg)	0.26
<b>CONNECTIONS</b>	
Side A - Connector 1	HD68 (MALE)
Side B - Connector 1	CENTRONICS 50 (MALE)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty