THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ; - .
© COPYRIGHT – TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REVISED PER ECO-08-023819	25SEP08	HMR	MS
	C	REVISED PER ECO-17-001163	27APR2017	RK	PO





P.C.LAYOUT

SPECIFICATIONS

MATERIALS:
CASE, PPS UL94V-0, BLACK
COVER, PBT UL94V-0, BLACK
ACTUATOR, 46 NYLON UL94V-0, WHITE
TERMINAL/FIXED CONTACT- COPPER ALLOY- GOLD OVER NICKEL PLATE
MOVING CONTACT- COPPER ALLOY- GOLD FLASH OVER NICKEL PLATE
HOLDER, COPPER ALLOY, TIN OVER NICKEL FINISH

ELECTRICAL:
RATING- 1a max non-switching
0.1µA (1mV) min switching
DC 5V 10mA INITIAL
CONTACT RESISTANCE- 50milliohm max. (300 milliohms after test)
INSULATION RESISTANCE- 100Megohms min. at 100V DC
DIELECTRIC STRENGTH- 300V RMS@SEA LEVEL
LIFE EXPECTANCY- 1,000 CYCLES

MECHANICAL:
ACTUATION FORCE- 2.45 +/-1.47N (245 +/-147 GF)
TRAVEL- 33°

ENVIRONMENTAL:
OPERATING TEMPERATURE- -30 TO +85 DEGREES C
STORAGE TEMPERATURE- -45 TO +100 DEGREES C
RESISTANCE TO SOLDER HEAT- 265 +/-3°C for 8 +/-2 seconds
SOLDERABILITY PER JIS-C-0050 & JIS-C-0053

1 ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)

2 SWITCH SUPPLIED IN THE "OFF" POSITION AND SHOULD BE SOLDERED IN THE "OFF" POSITION.

DIM P	DIM L	T&B P/N	PART NUMBER
OBSOLETE	25.40 (1.000)	28.60 (1.126)	STR10	1977105-5
	20.32 (.800)	23.52 (.926)	STR08	1977105-4
	15.24 (.600)	18.44 (.726)	STR06	1977105-3
	10.16 (.400)	13.36 (.526)	STR04	1977105-2
	5.08 (.200)	8.28 (.326)	STR02	1977105-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± 0.30[.012]
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL: SEE SPECIFICATIONS
FINISH: –

DWN M.BINNER 16MAY07
CHK M.SARVER 16MAY07
APVD M.SARVER 16MAY07
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

TE Connectivity

NAME: SIP SWITCH (STR02 – 10 SERIES)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-1977105	—

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 1 | REV C