

### product type designation



### Antenna ANT795-4MA

ANT795-4MA WLAN antenna with omnidirectional Characteristic, Radially rotatable, with additional joint, incl. RSMA connector: 3/5 dBi, IP30 (-20-+60°C), 2.4/5 GHz; Wi-Fi compliance and Observe national approvals; Direct mounting on SCALANCE W with RSMA connection system; scope of delivery: 1x ANT795-4MA, compact instructions as hard copy German/English

radio frequencies	
type of wireless network / is supported	WLAN
operating frequency	
<ul style="list-style-type: none"> <li>for WLAN in 2.4 GHz frequency band</li> </ul>	2.4 ... 2.4835 GHz
<ul style="list-style-type: none"> <li>for WLAN in 5 GHz frequency band 1</li> </ul>	5.15 ... 5.35 GHz
<ul style="list-style-type: none"> <li>for WLAN in 5 GHz frequency band 2</li> </ul>	5.725 ... 5.85 GHz
electrical data	
impedance	50 Ω
polarization	linear vertical
radiation characteristic	omnidirectional
antenna gain compared to spherical radiator	
<ul style="list-style-type: none"> <li>of the WLAN antenna / in the 2.4 GHz frequency band</li> </ul>	3 dB
<ul style="list-style-type: none"> <li>of the WLAN antenna / in the 5 GHz frequency band</li> </ul>	5 dB
standing wave ratio (VSWR) / maximum	2
radiating angle of the antenna	
<ul style="list-style-type: none"> <li>in the 2.4 GHz frequency band / horizontal</li> </ul>	360°
<ul style="list-style-type: none"> <li>in the 5 GHz frequency band / horizontal</li> </ul>	360°
number of electrical connections / of the antenna	1
type of electrical connection / of the antenna	R-SMA Connector
design of plug-in connection	male, variable 0-90°
angle of inclination / downward / maximum	0°
mechanical data	
material	
<ul style="list-style-type: none"> <li>of outer shell</li> </ul>	Polycarbonate
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-20 ... +65 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-20 ... +65 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-20 ... +65 °C
protection class IP	IP30
design, dimensions and weights	
width	35 mm
height	160 mm
depth	13 mm
net weight	29 g

fastening method	
<ul style="list-style-type: none"> <li>• mast mounting</li> <li>• wall mounting</li> <li>• roof mounting</li> <li>• directly on the device</li> </ul>	<p>No</p> <p>No</p> <p>No</p> <p>Yes</p>
<b>product features, product functions, product components / general</b>	
product feature / silicon-free	Yes
<b>standards, specifications, approvals</b>	
certificate of suitability	
<ul style="list-style-type: none"> <li>• RoHS conformity</li> </ul>	Yes
product conformity	UL 94-HB
wireless approval	Current national approvals can be found on the Internet under <a href="http://www.siemens.com/funkzulassungen">www.siemens.com/funkzulassungen</a>
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAX-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<p><a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a></p> <p><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></p> <p><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></p> <p><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></p> <p><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></p> <p><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>
<b>last modified:</b>	12/16/2020 