0.25 METER LENGTH



Connector A 901-9872 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 142191 SMB Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle		Connector A			Cable		Connector B		
100° 45° 225° 270° 270° D-Flat Bulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	901-9872 SMA R/A PLUG RG174 500 SMA Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold None Brass Gold 12.4 GHz SMA Plug Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 0.25 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	142191 SMB Clamp BHD JK RG316 RG174 500 SMB Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Brass Gold 4 GHz SMB Jack Straight BHD 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY			THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-RA-PL/SMB-ST-JK G174 0.25M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	