

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

APPLICABLE STANDARD		250V AC		CURRENT		3A	
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE1)		STORAGE TEMPERATURE RANGE	-10°C TO +60 °C(NOTE3)		
	OPERATING HUMIDITY RANGE	20% TO 80%(NOTE2)		STORAGE HUMIDITY RANGE	20% TO 70%(NOTE3)		
	APPLICABLE CONNECTOR	DF1B-*S-2.5R					

**SPECIFICATIONS**

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

<b>CONSTRUCTION</b>		TEST METHOD			REQUIREMENTS			QT	AT
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.			×	×	×	×	
MARKING	CONFIRMED VISUALLY.				×	×	×	×	

**ELECTRIC CHARACTERISTICS**

CONTACT RESISTANCE	100mA (DC OR 1000 Hz).	30mΩ MAX.	×	—
INSULATION RESISTANCE	500V DC.	1000MΩ MIN.	×	—
VOLTAGE PROOF	650V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	×	—

**MECHANICAL CHARACTERISTICS**

CONTACT INSERTION AND EXTRACTION FORCES	<input type="checkbox"/> 0.635 ± 0.002 BY STEEL GAUGE.	INSERTION FORCE 4.4N MAX EXTRACTION FORCE 0.4N MIN	×	—
MECHANICAL OPERATION	50 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—
VIBRATION	FREQUENCY 10 TO 55 HZ, SINGLE AMPITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs.	×	—
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—

**ENVIRONMENTAL CHARACTERISTICS**

DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → -5 TO 35 → +85 → -5 TO 35 °C TIME 30 → 10 TO 15 → 30 → 10 TO 15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—

REMARKS		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
NOTE1: INCLUDING THE TEMPERATURE RISE BY CURRENT.						
NOTE2: NO CONDENSING.						
NOTE3: APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.						
Unless otherwise specified, refer to JIS C 5402						

04.03.05	04.03.05	04.03.08	04.03.09	
<i>T. Kumagawa</i>	<i>T. Kumagawa</i>	<i>T. Miyagaki</i>	<i>T. Oae</i>	

Note QT: Qualification Test AT: Assurance Test X: Applicable Test

<b>HRS</b>	HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.	DF1B- * P-2.5DS(01)
CODE NO. (OLD)	DRAWING NO.	ELC4-162412-01	PART NO.	CL541
CL				1/1

TO	

