

Surface Mount ThermistorsLeadless Top Bottom Terminated Chip Thermistor

BC Series Leadless Top/Bottom Terminated Chip Thermistors



Dimensions



Dimensions shown in inches.

| Α | В | С |
|---------|---------|---------|
| See Dim | See Dim | See Dim |
| "L" | "W" | "T" |

Description

Littelfuse leadless top/bottom terminated chip thermistor elements are designed for use on hybrid substrates, integrated circuits and printed circuit boards. They have silver metallization on their top and bottom surfaces which are suitable for various contact techniques including epoxy or solder. Other metallization materials are available as well. Since they are manufactured using the most advanced equipment and technology available, their dimensional parameters are extremely uniform, making the devices especially suitable for use with automatic handling and placement equipment.


Options

- Non-standard resistance values and tolerances
- Special lead materials and lengths
- Special encapsulants or probe housings
- Tape and reel packaging

Features

- Surface mountable
- Small size
- Very low profile
- Low cost
- Rapid response time

Part Numbering System



Note: Not all combinations of Part Number codes are available. Contact Littelfuse for details.



BC Series Leadless Top/Bottom Terminated Chip Thermistors

Specifications

| Part Number | Resistance Ohms @25°C | *Resistance Tol. ± % @ 25°C | R-T Curve | Temperature Coefficient (%/°C) @ 25°C | Beta (K) 0-50°C | Dissipation Constant, Nominal (mW/°C) | Thermal Time Constant, Max Still Air (seconds) | Temperature Rating (°C) |
|----------------|-----------------------------|-----------------------------------|--------------|---|--------------------|--|--|-------------------------------|
| BC101B1K | 100 | 10 | В | -3.31 | 2941 | 1 | 2 | -55 to +150 |
| BC501B1K | 500 | 10 | В | -3.31 | 2941 | 1 | 2 | -55 to +150 |
| BC102F1K | 1000 | 10 | F | -3.86 | 3419 | 1 | 2 | -55 to +150 |
| BC222J1K | 2252 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC302J1K | 3000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC502J1K | 5000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC103J1K | 10000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC203J1K | 20000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC303J1K | 30000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC503J1K | 50000 | 10 | J | -4.4 | 3892 | 1 | 2 | -55 to +150 |
| BC104R1K | 100000 | 10 | R | -4.68 | 4140 | 1 | 2 | -55 to +150 |

^{*}Resistance tolerances of \pm 1%, 2%, and 5% are available upon request

Packaging

| Packaging Option | Packaging Code | Standard |
|------------------|----------------|----------|
| ESD Waffle Pack | -WF | NA |

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littlefuse.com/disclaimer-electronics