



power contactor, AC-3 25 A, 11 kW / 400 V 1 NO + 1 NC, 72 V DC, 3-pole, Size S0 screw terminal

|                                                                                                                                                                                                                                         |                                                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| <b>product brand name</b>                                                                                                                                                                                                               | SIRIUS                                               |
| <b>product designation</b>                                                                                                                                                                                                              | Power contactor                                      |
| <b>product type designation</b>                                                                                                                                                                                                         | 3RT2                                                 |
| <b>General technical data</b>                                                                                                                                                                                                           |                                                      |
| <b>size of contactor</b>                                                                                                                                                                                                                | S0                                                   |
| <b>product extension</b>                                                                                                                                                                                                                |                                                      |
| <ul style="list-style-type: none"> <li>function module for communication</li> <li>auxiliary switch</li> </ul>                                                                                                                           | <p>No</p> <p>Yes</p>                                 |
| <b>power loss [W] for rated value of the current</b>                                                                                                                                                                                    |                                                      |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> <li>at AC in hot operating state per pole</li> <li>without load current share typical</li> </ul>                                                               | <p>5.7 W</p> <p>1.9 W</p> <p>5.9 W</p>               |
| <b>insulation voltage</b>                                                                                                                                                                                                               |                                                      |
| <ul style="list-style-type: none"> <li>of main circuit with degree of pollution 3 rated value</li> <li>of auxiliary circuit with degree of pollution 3 rated value</li> </ul>                                                           | <p>690 V</p> <p>690 V</p>                            |
| <b>surge voltage resistance</b>                                                                                                                                                                                                         |                                                      |
| <ul style="list-style-type: none"> <li>of main circuit rated value</li> <li>of auxiliary circuit rated value</li> </ul>                                                                                                                 | <p>6 kV</p> <p>6 kV</p>                              |
| maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1                                                                                                                                   | 400 V                                                |
| <b>shock resistance at rectangular impulse</b>                                                                                                                                                                                          |                                                      |
| <ul style="list-style-type: none"> <li>at DC</li> </ul>                                                                                                                                                                                 | 10g / 5 ms, 7,5g / 10 ms                             |
| <b>shock resistance with sine pulse</b>                                                                                                                                                                                                 |                                                      |
| <ul style="list-style-type: none"> <li>at DC</li> </ul>                                                                                                                                                                                 | 15g / 5 ms, 10g / 10 ms                              |
| <b>mechanical service life (switching cycles)</b>                                                                                                                                                                                       |                                                      |
| <ul style="list-style-type: none"> <li>of contactor typical</li> <li>of the contactor with added electronically optimized auxiliary switch block typical</li> <li>of the contactor with added auxiliary switch block typical</li> </ul> | <p>10 000 000</p> <p>5 000 000</p> <p>10 000 000</p> |
| <b>reference code according to IEC 81346-2</b>                                                                                                                                                                                          | Q                                                    |
| <b>Substance Prohibitance (Date)</b>                                                                                                                                                                                                    | 10/01/2009                                           |
| <b>Ambient conditions</b>                                                                                                                                                                                                               |                                                      |
| installation altitude at height above sea level maximum                                                                                                                                                                                 | 2 000 m                                              |
| <b>ambient temperature</b>                                                                                                                                                                                                              |                                                      |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>                                                                                                                                              | <p>-25 ... +60 °C</p> <p>-55 ... +80 °C</p>          |
| <b>relative humidity minimum</b>                                                                                                                                                                                                        | 10 %                                                 |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>                                                                                                                                                                   | 95 %                                                 |

## Main circuit

|                                                                        |                    |
|------------------------------------------------------------------------|--------------------|
| <b>number of poles for main current circuit</b>                        | 3                  |
| <b>number of NO contacts for main contacts</b>                         | 3                  |
| <b>operating voltage</b>                                               |                    |
| • at AC-3 rated value maximum                                          | 690 V              |
| • at AC-3e rated value maximum                                         | 690 V              |
| <b>operational current</b>                                             |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 40 A               |
| • at AC-1                                                              |                    |
| — up to 690 V at ambient temperature 40 °C rated value                 | 40 A               |
| — up to 690 V at ambient temperature 60 °C rated value                 | 35 A               |
| • at AC-3                                                              |                    |
| — at 400 V rated value                                                 | 25 A               |
| — at 500 V rated value                                                 | 18 A               |
| — at 690 V rated value                                                 | 13 A               |
| • at AC-3e                                                             |                    |
| — at 400 V rated value                                                 | 25 A               |
| — at 500 V rated value                                                 | 18 A               |
| — at 690 V rated value                                                 | 13 A               |
| • at AC-4 at 400 V rated value                                         | 15.5 A             |
| • at AC-5a up to 690 V rated value                                     | 35.2 A             |
| • at AC-5b up to 400 V rated value                                     | 20.7 A             |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=20 rated value                  | 20.2 A             |
| — up to 400 V for current peak value n=20 rated value                  | 20.2 A             |
| — up to 500 V for current peak value n=20 rated value                  | 20.2 A             |
| — up to 690 V for current peak value n=20 rated value                  | 12.9 A             |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=30 rated value                  | 13.5 A             |
| — up to 400 V for current peak value n=30 rated value                  | 13.5 A             |
| — up to 500 V for current peak value n=30 rated value                  | 13.5 A             |
| — up to 690 V for current peak value n=30 rated value                  | 13 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 10 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value                                                 | 9 A                |
| • at 690 V rated value                                                 | 9 A                |
| <b>operational current</b>                                             |                    |
| • <b>at 1 current path at DC-1</b>                                     |                    |
| — at 24 V rated value                                                  | 35 A               |
| — at 110 V rated value                                                 | 4.5 A              |
| — at 220 V rated value                                                 | 1 A                |
| — at 440 V rated value                                                 | 0.4 A              |
| — at 600 V rated value                                                 | 0.25 A             |
| • <b>with 2 current paths in series at DC-1</b>                        |                    |
| — at 24 V rated value                                                  | 35 A               |
| — at 110 V rated value                                                 | 35 A               |
| — at 220 V rated value                                                 | 5 A                |
| — at 440 V rated value                                                 | 1 A                |
| — at 600 V rated value                                                 | 0.8 A              |
| • <b>with 3 current paths in series at DC-1</b>                        |                    |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                        | 35 A<br>35 A<br>35 A<br>2.9 A<br>1.4 A                                                                                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                          | 20 A<br>2.5 A<br>1 A<br>0.09 A<br>0.06 A                                                                                                                                                                                                                                                                      |
| <ul style="list-style-type: none"> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                             | 35 A<br>15 A<br>3 A<br>0.27 A<br>0.16 A                                                                                                                                                                                                                                                                       |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                             | 35 A<br>35 A<br>10 A<br>0.6 A<br>0.6 A                                                                                                                                                                                                                                                                        |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-2 at 400 V rated value</li> <li>● at AC-3               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul> | 11 kW<br>5.5 kW<br>11 kW<br>11 kW<br>11 kW<br>5.5 kW<br>11 kW<br>11 kW<br>11 kW                                                                                                                                                                                                                               |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                    | 4.4 kW<br>7.7 kW                                                                                                                                                                                                                                                                                              |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                  | 8 kVA<br>13.9 kVA<br>17.4 kVA<br>15.4 kVA                                                                                                                                                                                                                                                                     |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                  | 5.3 kVA<br>9.3 kVA<br>11.6 kVA<br>15.5 kVA                                                                                                                                                                                                                                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>                                                                                                | 375 A; Use minimum cross-section acc. to AC-1 rated value<br>299 A; Use minimum cross-section acc. to AC-1 rated value<br>200 A; Use minimum cross-section acc. to AC-1 rated value<br>128 A; Use minimum cross-section acc. to AC-1 rated value<br>106 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at DC</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1 500 1/h                                                                                                                                                                                                                                                                                                     |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>● at AC-1 maximum</li> <li>● at AC-2 maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                      | 1 000 1/h<br>750 1/h                                                                                                                                                                                                                                                                                          |

|                                                                                                                                                                                                                                                                    |                                                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at AC-3 maximum</li> </ul>                                                                                                                                                                                                | 750 1/h                                         |
| <ul style="list-style-type: none"> <li>• at AC-3e maximum</li> </ul>                                                                                                                                                                                               | 750 1/h                                         |
| <ul style="list-style-type: none"> <li>• at AC-4 maximum</li> </ul>                                                                                                                                                                                                | 250 1/h                                         |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                    |                                                 |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                               | DC                                              |
| <b>control supply voltage at DC</b>                                                                                                                                                                                                                                |                                                 |
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>                                                                                                                                                                                                    | 72 V                                            |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b>                                                                                                                                                                              |                                                 |
| <ul style="list-style-type: none"> <li>• initial value</li> </ul>                                                                                                                                                                                                  | 0.8                                             |
| <ul style="list-style-type: none"> <li>• full-scale value</li> </ul>                                                                                                                                                                                               | 1.1                                             |
| <b>closing power of magnet coil at DC</b>                                                                                                                                                                                                                          | 5.9 W                                           |
| <b>holding power of magnet coil at DC</b>                                                                                                                                                                                                                          | 5.9 W                                           |
| <b>closing delay</b>                                                                                                                                                                                                                                               |                                                 |
| <ul style="list-style-type: none"> <li>• at DC</li> </ul>                                                                                                                                                                                                          | 50 ... 170 ms                                   |
| <b>opening delay</b>                                                                                                                                                                                                                                               |                                                 |
| <ul style="list-style-type: none"> <li>• at DC</li> </ul>                                                                                                                                                                                                          | 15 ... 17.5 ms                                  |
| <b>arcing time</b>                                                                                                                                                                                                                                                 | 10 ... 10 ms                                    |
| <b>control version of the switch operating mechanism</b>                                                                                                                                                                                                           | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>                                                                                                                                                                                                                                           |                                                 |
| number of NC contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                 | 1                                               |
| number of NO contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                 | 1                                               |
| operational current at AC-12 maximum                                                                                                                                                                                                                               | 10 A                                            |
| <b>operational current at AC-15</b>                                                                                                                                                                                                                                |                                                 |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> </ul>                                                                                                                                                                                           | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>                                                                                                                                                                                           | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 500 V rated value</li> </ul>                                                                                                                                                                                           | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                           | 1 A                                             |
| <b>operational current at DC-12</b>                                                                                                                                                                                                                                |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                                                                                                                                                                            | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>                                                                                                                                                                                            | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                                                                                                                                                                            | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                                                                                                                                                                           | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>                                                                                                                                                                                           | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                                                                                                                                                                           | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                           | 0.15 A                                          |
| <b>operational current at DC-13</b>                                                                                                                                                                                                                                |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                                                                                                                                                                            | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>                                                                                                                                                                                            | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                                                                                                                                                                            | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                                                                                                                                                                           | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>                                                                                                                                                                                           | 0.9 A                                           |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                                                                                                                                                                           | 0.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                           | 0.1 A                                           |
| <b>contact reliability of auxiliary contacts</b>                                                                                                                                                                                                                   | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                              |                                                 |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                                                                                                                                                                                                |                                                 |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> </ul>                                                                                                                                                                                           | 21 A                                            |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                           | 22 A                                            |
| <b>yielded mechanical performance [hp]</b>                                                                                                                                                                                                                         |                                                 |
| <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> </ul>                                                                        | 2 hp<br>3 hp                                    |
| <ul style="list-style-type: none"> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> <li>— at 460/480 V rated value</li> <li>— at 575/600 V rated value</li> </ul> </li> </ul> | 5 hp<br>7.5 hp<br>15 hp<br>20 hp                |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | A600 / P600                                                                                                                                                                                                                                                        |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                    |
| <b>design of the fuse link</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of assignment 2 required</li> </ul> </li> <li>● for short-circuit protection of the auxiliary switch required</li> </ul>                                                                                                                                                                                                         | gG: 100 A (690 V, 100 kA), aM: 50 A (690 V, 100 kA), BS88: 100 A (415 V, 80 kA)<br>gG: 35A (690V, 100kA), aM: 20A (690V, 100kA), BS88: 35A (415V, 80kA)<br>gG: 10 A (500 V, 1 kA)                                                                                  |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                    |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                                                                                                                               |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715                                                                                                                                                                             |
| <ul style="list-style-type: none"> <li>● side-by-side mounting</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Yes                                                                                                                                                                                                                                                                |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 85 mm                                                                                                                                                                                                                                                              |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 45 mm                                                                                                                                                                                                                                                              |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 107 mm                                                                                                                                                                                                                                                             |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>● for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>● for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                                                                                                                                      |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                    |
| <b>type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● for main current circuit</li> <li>● for auxiliary and control circuit</li> <li>● at contactor for auxiliary contacts</li> <li>● of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                                            | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals                                                                                                                                                                       |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● for main contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>● at AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                                                  | 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )<br>2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )<br>2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup><br>2x (16 ... 12), 2x (14 ... 8) |
| <b>connectable conductor cross-section for main contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● solid</li> <li>● stranded</li> <li>● finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                             | 1 ... 10 mm <sup>2</sup><br>1 ... 10 mm <sup>2</sup><br>1 ... 10 mm <sup>2</sup>                                                                                                                                                                                   |
| <b>connectable conductor cross-section for auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● solid or stranded</li> <li>● finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                     | 0.5 ... 2.5 mm <sup>2</sup><br>0.5 ... 2.5 mm <sup>2</sup>                                                                                                                                                                                                         |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>● at AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                                         | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14)                                                                                   |

|                                                                                                         |                       |
|---------------------------------------------------------------------------------------------------------|-----------------------|
| <b>AWG number as coded connectable conductor cross section</b>                                          |                       |
| <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul> | 16 ... 8<br>20 ... 14 |

| Safety related data                                                                                                                                   |                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <b>product function</b>                                                                                                                               |                                                  |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> </ul>                                                         | Yes                                              |
| B10 value with high demand rate according to SN 31920                                                                                                 | 450 000                                          |
| <b>proportion of dangerous failures</b>                                                                                                               |                                                  |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul> | 40 %<br>73 %                                     |
| failure rate [FIT] with low demand rate according to SN 31920                                                                                         | 100 FIT                                          |
| T1 value for proof test interval or service life according to IEC 61508                                                                               | 20 y                                             |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                        | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>                                                                                           | finger-safe, for vertical contact from the front |
| <b>suitability for use</b>                                                                                                                            |                                                  |
| <ul style="list-style-type: none"> <li>• safety-related switching OFF</li> </ul>                                                                      | Yes                                              |

**Certificates/ approvals**

**General Product Approval**



[Confirmation](#)



[KC](#)



| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

**Marine / Shipping**



| other | Dangerous Good |
|-------|----------------|
|-------|----------------|

[Confirmation](#)

[Environmental Confirmations](#)



[Transport Information](#)

**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RT2026-1BJ80>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RT2026-1BJ80>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2026-1BJ80>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2026-1BJ80&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2026-1BJ80&lang=en)

Characteristic: Tripping characteristics,  $I^2t$ , Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2026-1BJ80/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2026-1BJ80&objecttype=14&gridview=view1>

last modified:

6/2/2022 