


**Part Number: AB38S-Q**  
**AEC-Q101 Certified - 1 Form A - PhotoDMOS Relays**  
**Product Data Sheet**

**AEC-Q101**

**600 VOLTS**

**PICTURE**



Drawings not to scale.  
 All dimensions in mm nominal. Pitch: 2.54 mm

**✓RoHS Compliant**

**FEATURES**


- **TOWARD** PhotoDMOS Relays
- AEC-Q101 Certification for Automotive Applications
- 600 Volt, 70 mA
- On-Resistance 60 Ω Max.
- I/O Breakdown Voltage: SOP 1500 Vrms Min.
- Max LED Current 3.0 mA
- Tape and Reel, add R1 (Example: AB38S-Q-R1)

**PART IDENTIFICATION**


	SOP TYPE	QUANTITY
AB38S-Q	Tape & Reel	Tube 100
	Feed direction: Pin No. 3, 4	Tape 1000
	AB38S-Q-R1	

**CIRCUIT DIAGRAM**

(TOP VIEW)



- 1: Anode (LED)
- 2: Cathode (LED)
- 3, 4: Drain (MOSFET)



- Recommended Soldering Pattern For Reflow Soldering

Drawings not to scale.  
 All dimensions in mm nominal.

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

**Phone: (1) 973 777 6900**

**www.comus-intl.com**

**Fax: (1) 973 777 8405**

Belgium: + 32 (0)12 390400 - Comus Europe Ltd (Assemtech) UK: +44 (0) 1255 862236 - Germany: +49 (0)911 923 15 943 - Netherlands: +31(0)45 54 39 345 - India: +(91) (44) 42023510

©2016 Copyright Comus International, 454 Allwood Road, Clifton NJ 07012, USA

Rev: 0 - Date: Sept/1/2016 - Signature: BR

An ISO 9001 Certified Company

**Part Number: AB38S-Q**  
**AEC-Q101 Certified - 1 Form A - PhotoDMOS Relays**  
**Product Data Sheet**

**AEC-Q101**

**600 VOLTS**

ABSOLUTE MAXIMUM RATINGS			AMBIENT TEMPERATURE: 25°C
ITEM	SYMBOL	VALUE	
Input	Continuous LED Current	$I_F$	50 mA
	Peak LED Current	$I_{FP}$	500 mA
	LED Reverse Voltage	$V_R$	5 V
	Input Power Dissipation	$P_{In}$	75 mW
Output	Load Voltage	$V_L$	600 V (AC peak or DC)
	Load Current	$I_L$	70 mA
	Peak Load Current (1 ms, 1 shot)	$I_{Peak}$	200 mA
	Output Power Dissipation	$P_{Out}$	300 mW
Total Power Dissipation	$P_T$	350 mW	
I/O Breakdown Voltage	$V_{I/O}$	1500 Vrms Min	
Operating Temperature	$T_{Opr}$	-40°C ~ +105°C	
Storage Temperature	$T_{Stg}$	-40°C ~ +125°C	

ELECTRICAL SPECIFICATIONS							AMBIENT TEMPERATURE: 25°C
ITEM	SYMBOL	MIN	TYP	MAX	UNITS	CONDITIONS	
Input	LED Forward Voltage	$V_F$	0.9	1.17	1.3	V	$I_F = 10 \text{ mA}$
	Operation LED Current	$I_{F On}$		1	5	mA	
	Recovery LED Voltage	$V_{F Off}$	0.5	1		V	
Output	On-Resistance Drain to Drain	$R_{On}$		40	60	$\Omega$	$I_F = 5 \text{ mA}$ , $I_L = \text{Rated Current}$ Time to flow is within 1 sec.
	Off-State Leakage Current	$I_{Leak}$			1	$\mu\text{A}$	$V_L = 600 \text{ V}$
	Output Capacitance	$C_{Out}$		47		pF	$V_L = 0 \text{ V}$ , $f = 1 \text{ MHz}$
Transmission	Turn-On Time	$T_{On}$		0.2	0.5	ms	$I_F = 5 \text{ mA}$
	Turn-Off Time	$T_{Off}$		0.08	0.2	ms	$I_L = \text{Rated Current}$
Coupled	I/O Insulation Resistance	$R_{I/O}$	$10^9$			$\Omega$	
	I/O Capacitance	$C_{I/O}$		1.3		pF	$f = 1 \text{ MHz}$

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

**Phone: (1) 973 777 6900**

**www.comus-intl.com**

**Fax: (1) 973 777 8405**

Belgium: + 32 (0)12 390400 - Comus Europe Ltd (Assemtech) UK: +44 (0) 1255 862236 - Germany: +49 (0)911 923 15 943 - Netherlands: +31(0)45 54 39 345 - India: +(91) (44) 42023510

©2016 Copyright Comus International, 454 Allwood Road, Clifton NJ 07012, USA













Rev: 0 - Date: Sept/1/2016 - Signature: BR

An ISO 9001 Certified Company

**Part Number: AB38S-Q**  
**AEC-Q101 Certified - 1 Form A - PhotoDMOS Relays**  
**Product Data Sheet**

**AEC-Q101**      **600 VOLTS**

**GRAPHS**



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

**Phone: (1) 973 777 6900      www.comus-intl.com      Fax: (1) 973 777 8405**