



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
4. NO CONTACTS ON POS. A1 + A2
5. P.C.B. HOLE DRILLINGS SEE SHEET 2
6. CONNECTOR IS PART MARKED: 3027W2SAR99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale: 2:1 (5:1)
				dim. in mm		material: SEE NOTES
				date	name	title: D-SUB COMBINATION FEMALE 27W2S
				drawn 02.05.14	Henneboel	dwg no: 13K1A4667
				appd. 02.05.14	Schmidt	
				norm		DIN-A3
				d-old		sh: 1/2
			rev. a	Original	part no: 3027W2SAR99A10X	
			description	date	name	



