

# SiT9347

220 MHz to 725 MHz Endura™ Series Ultra-low Jitter Differential Oscillator



## Description

The [SiT9347](#) is a 220.000001 MHz to 725 MHz differential MEMS XO engineered for low-jitter, high reliability applications. Utilizing SiTime's unique DualMEMS® temperature sensing and TurboCompensation® technology, the SiT9347 delivers exceptional dynamic performance by providing resistance to airflow, thermal gradients, shock and vibration. This device also integrates multiple on-chip regulators to filter power supply noise, eliminating the need for a dedicated external LDO.

The SiT9347 can be factory programmed for any combination of frequency, stability, voltage, and output signaling. Programmability enables designers to optimize clock configurations while eliminating long lead times and customization costs associated with quartz devices where each frequency is custom built.

The wide frequency range and programmability makes this device ideal for aerospace, industrial and defense applications that require a variety of frequencies and operate in noisy environments.

Refer to [Manufacturing Notes](#) for proper reflow profile, tape and reel dimension, and other manufacturing related information.

## Features

- 0.1 ppb/g acceleration sensitivity for harsh environments
- Any frequency between 220.000001 MHz and 725 MHz, accurate to 6 decimal places.  
For HCSL output signaling, maximum frequency is 500 MHz. [Contact SiTime](#) for higher frequency options.  
(For additional frequencies, refer to [SiT9346](#) datasheets)
- LVPECL, Low-swing LVPECL, LVDS and HCSL output signaling
- 0.1 ps RMS phase jitter (random) for Ethernet applications
- Frequency stability as low  $\pm 10$  ppm
- Wide temperature range from  $-40^{\circ}\text{C}$  to  $105^{\circ}\text{C}$   
[Contact SiTime](#) for higher temperature range options
- Industry-standard packages:  $3.2 \times 2.5 \text{ mm}^2$ ,  $7.0 \times 5.0 \text{ mm}^2$  and  $5.0 \times 3.2 \text{ mm}^2$  package

## Applications

- Airborne Communications
- Command and Control
- Field Communications
- Airframe/Engine Management Control
- Radar
- SATCOM



Order  
samples



Buy at  
SiTimeDirect



Green  
solutions



Lifetime  
warranty

## Block Diagram




Figure 1. SiT9347 Block Diagram

## Package Pinout





Figure 2. Pin Assignments (Top view)  
(Refer to [Table 6](#) for Pin Descriptions)

## Ordering Information

**SiT9347AC-1 B2A33E322.265625T**



### Notes:

1. Bulk is available for sampling only, (up to 24 u).
2. [Contact SiTime](#) for higher frequency HCSL options.

**Table 1. Ordering Codes for Supported Tape & Reel Packing Method**

| Device Size<br>(mm x mm) | 8 mm T&R<br>(3ku) | 8 mm T&R<br>(1ku) | 12 mm T&R<br>(3ku) | 12 mm T&R<br>(1ku) | 12 mm T&R<br>(<250pcs) | 16 mm T&R<br>(3ku) | 16 mm T&R<br>(1ku) |
|--------------------------|-------------------|-------------------|--------------------|--------------------|------------------------|--------------------|--------------------|
| 7.0 x 5.0                | —                 | —                 | —                  | —                  | —                      | T                  | Y                  |
| 5.0 x 3.2                | —                 | —                 | T                  | Y                  | F                      | —                  | —                  |
| 3.2 x 2.5                | D                 | E                 | —                  | —                  | —                      | —                  | —                  |

## TABLE OF CONTENTS

|   |    |
|---|----|
| Description .....   | 1  |
| Features .....  | 1  |
| Applications .....  | 1  |
| Block Diagram .....                                       | 1  |
| Package Pinout .....                                      | 1  |
| Ordering Information .....                                | 2  |
| Electrical Characteristics .....                          | 2  |
| Waveform Diagrams .....                                   | 6  |
| Timing Diagrams .....                                     | 7  |
| Termination Diagrams .....                                | 8  |
| LVPECL and Low-swing LVPECL .....                         | 8  |
| LVDS .....  | 9  |
| HCSL .....  | 9  |
| Dimensions and Patterns — 3.2 x 2.5 mm <sup>2</sup> ..... | 10 |
| Dimensions and Patterns — 5.0 x 3.2 mm <sup>2</sup> ..... | 10 |
| Dimensions and Patterns — 7.0 x 5.0 mm <sup>2</sup> ..... | 11 |
| Additional Information .....                              | 12 |
| Revision History .....                                    | 13 |

## Electrical Characteristics

All Min and Max limits in the Electrical Characteristics tables are specified over temperature and rated operating voltage with standard output termination shown in the termination diagrams. Typical values are at 25°C at nominal supply voltage.

**Table 2. Electrical Characteristics – Common to LVPECL, Low-swing LVPECL, LVDS and HCSL**

| Parameter                                  | Symbol  | Min.       | Typ. | Max. | Unit  | Condition   |
|--|---------|------------|------|------|-------|---|
| Frequency Range                            |         |            |      |      |       |   |
| Output Frequency Range                     | f       | 220.000001 | –    | 725  | MHz   | Accurate to 6 decimal places  |
| Frequency Stability                        |         |            |      |      |       |   |
| Frequency Stability                        | F_stab  | -10        | –    | +10  | ppm   | Inclusive of initial tolerance, operating temperature, rated power supply voltage and load variations   |
|  |         | -20        | –    | +20  | ppm   |   |
|  |         | -25        | –    | +25  | ppm   |   |
|  |         | -50        | –    | +50  | ppm   |   |
| First Year Aging                           | F_1y    | -0.7       | ±0.4 | +0.7 | ppm   | At 85°C   |
| 5 Year Aging                               | F_5y    | -1.1       | ±0.7 | +1.1 | ppm   | At 85°C   |
| 10 Year Aging                              | F_10y   | -1.3       | ±0.8 | +1.3 | ppm   | At 85°C   |
| 20 Year Aging                              | F_20y   | -1.5       | ±1.0 | +1.5 | ppm   | At 85°C   |
| Temperature Range                          |         |            |      |      |       |   |
| Operating Temperature Range                | T_use   | -20        | –    | +70  | °C    | Extended Commercial   |
|  |         | -40        | –    | +85  | °C    | Industrial  |
|  |         | -40        | –    | +95  | °C    |   |
|  |         | -40        | –    | +105 | °C    | Extended Industrial   |
| Rugged Characteristics                     |         |            |      |      |       |   |
| Acceleration (g) sensitivity, Gamma Vector | F_g     | –          | –    | 0.1  | ppb/g | Low sensitivity grade; total gamma over 3 axes; 15 Hz to 2 kHz; MIL-PRF-55310, computed per section 4.8.18.3.1  |
| Supply Voltage                             |         |            |      |      |       |   |
| Supply Voltage                             | Vdd     | 2.97       | 3.30 | 3.63 | V     |   |
|  |         | 2.70       | 3.00 | 3.30 | V     |   |
|  |         | 2.52       | 2.80 | 3.08 | V     |   |
|  |         | 2.25       | 2.50 | 2.75 | V     |   |
| Input Characteristics                      |         |            |      |      |       |   |
| Input Voltage High                         | VIH     | 70%        | –    | –    | Vdd   | Pin 1, OE   |
| Input Voltage Low                          | VIL     | –          | –    | 30%  | Vdd   | Pin 1, OE   |
| Input Pull-up Impedance                    | Z_in    | –          | 100  | -    | kΩ    | Pin 1, OE logic high or logic low   |
| Output Characteristics                     |         |            |      |      |       |   |
| Duty Cycle                                 | DC      | 45         | –    | 55   | %     |   |
| Startup and OE Timing                      |         |            |      |      |       |   |
| Startup Time                               | T_start | –          | –    | 3.0  | ms    | Measured from the time Vdd reaches its rated minimum value.   |
| OE Enable/Disable Time                     | T_oe    | –          | –    | 3.8  | μs    | f = 322.265625 MHz. Measured from the time OE pin reaches rated VIH and VIL to the time clock pins reach 90% of swing and high-Z. See <a href="#">Figure 8</a> and <a href="#">Figure 9</a> |

**Table 3. Electrical Characteristics – LVPECL Specific**

| Parameter                                    | Symbol              | Min.                  | Typ.  | Max.                  | Unit | Condition   |
|--|---------------------|-----------------------|-------|-----------------------|------|---|
| Current Consumption                          |                     |                       |       |                       |      |   |
| Current Consumption                          | I <sub>dd</sub>     | –                     | –     | 94                    | mA   | Excluding Load Termination Current, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| OE Disable Supply Current                    | I <sub>OE</sub>     | –                     | –     | 63                    | mA   | OE = Low  |
| Output Disable Leakage Current               | I <sub>leak</sub>   | –                     | 0.15  | –                     | μA   | OE = Low  |
| Maximum Output Current                       | I <sub>driver</sub> | –                     | –     | 33                    | mA   | Maximum average current drawn from OUT+ or OUT-   |
| Output Characteristics for LVPECL            |                     |                       |       |                       |      |   |
| Output High Voltage                          | VOH                 | V <sub>dd</sub> -1.15 | –     | V <sub>dd</sub> -0.7  | V    | See Figure 4  |
| Output Low Voltage                           | VOL                 | V <sub>dd</sub> -2.0  | –     | V <sub>dd</sub> -1.5  | V    | See Figure 4  |
| Output Differential Voltage Swing            | V <sub>Swing</sub>  | 1.2                   | 1.6   | 2.0                   | V    | See Figure 5  |
| Rise/Fall Time                               | Tr, Tf              | –                     | 225   | 330                   | ps   | 20% to 80%, see Figure 5  |
| Output Characteristics for Low-swing LVPECL  |                     |                       |       |                       |      |   |
| Output High Voltage                          | VOH                 | V <sub>dd</sub> -1.2  | –     | V <sub>dd</sub> -0.75 | V    | See Figure 4  |
| Output Low Voltage                           | VOL                 | V <sub>dd</sub> -1.8  | –     | V <sub>dd</sub> -1.25 | V    | See Figure 4  |
| Output Differential Voltage Swing            | V <sub>Swing</sub>  | 0.4                   | 1     | 1.2                   | V    | Output frequency 1 to 220 MHz, See Figure 5   |
|  |                     | 0.4                   | 1     | 1.6                   | V    | Output frequency greater than 220 MHz, See Figure 5   |
| Rise/Fall Time                               | Tr, Tf              | –                     | 225   | 320                   | ps   | 20% to 80%. See Figure 5  |
| Jitter – 7.0 x 5.0 mm Package                |                     |                       |       |                       |      |   |
| RMS Period Jitter <sup>[3]</sup>             | T <sub>jitt</sub>   | –                     | 1.0   | 1.6                   | Ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>    | –                     | 0.220 | 0.270                 | Ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40 to 85°C  |
|  |                     | –                     | 0.220 | 0.300                 | Ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -40 to 95°C and -40 to 105°C |
|  |                     | –                     | 0.1   | –                     | Ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz, Includes spurs, all V <sub>dd</sub> levels              |
| Jitter – 5.0 x 3.2 and 3.2 x 2.5 mm Packages |                     |                       |       |                       |      |   |
| RMS Period Jitter <sup>[3]</sup>             | T <sub>jitt</sub>   | –                     | 1.0   | 1.6                   | Ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>    | –                     | 0.225 | 0.282                 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40 to 85°C. |
|  |                     | –                     | 0.225 | 0.315                 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -40 to 95°C and -40 to 105°C |
|  |                     | –                     | 0.1   | –                     | ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz, Includes spurs, all V <sub>dd</sub> levels              |

**Notes:**

- Measured according to JESD65B.

**Table 4. Electrical Characteristics – LVDS Specific**

| Parameter                                    | Symbol                          | Min.  | Typ.  | Max.  | Unit | Condition   |
|--|---------------------------------|-------|-------|-------|------|---|
| Current Consumption                          |                                 |       |       |       |      |   |
| Current Consumption                          | I <sub>dd</sub>                 | –     | –     | 85    | mA   | Excluding Load Termination Current, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| OE Disable Supply Current                    | I <sub>OE</sub>                 | –     | –     | 63    | mA   | OE = Low  |
| Output Disable Leakage Current               | I <sub>leak</sub>               | –     | 0.15  | –     | μA   | OE = Low  |
| Output Characteristics                       |                                 |       |       |       |      |   |
| Differential Output Voltage                  | V <sub>OD</sub>                 | 300   | –     | 450   | mV   | See Figure 6  |
| V <sub>OD</sub> Magnitude Change             | ΔV <sub>OD</sub>                | –     | –     | 50    | mV   | See Figure 6  |
| Offset Voltage                               | V <sub>OS</sub>                 | 1.125 | –     | 1.375 | V    | See Figure 6  |
| V <sub>OS</sub> Magnitude Change             | ΔV <sub>OS</sub>                | –     | –     | 50    | mV   | See Figure 6  |
| Rise/Fall Time                               | T <sub>r</sub> , T <sub>f</sub> | –     | 370   | 470   | ps   | Measured with 2 pF capacitive loading to GND, 20% to 80%, see Figure 3  |
| Jitter – 7.0 x 5.0 mm Package                |                                 |       |       |       |      |   |
| RMS Period Jitter <sup>[4]</sup>             | T <sub>jitt</sub>               | –     | 0.92  | 1.6   | ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>                | –     | 0.215 | 0.265 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40-85°C         |
|  |                                 | –     | 0.215 | 0.280 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges are -40 to 95°C and -40 to 105°C |
|  |                                 | –     | 0.1   | –     | ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz. Includes spurs for all V <sub>dd</sub> levels.              |
| Jitter – 5.0 x 3.2 and 3.2 x 2.5 mm Packages |                                 |       |       |       |      |   |
| RMS Period Jitter <sup>[4]</sup>             | T <sub>jitt</sub>               | –     | 0.92  | 1.6   | ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>                | –     | 0.235 | 0.282 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40-85°C         |
|  |                                 | –     | 0.235 | 0.310 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges are -40 to 95°C and -40 to 105°C |
|  |                                 | –     | 0.1   | –     | ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz. Includes spurs for all V <sub>dd</sub> levels.              |

**Notes:**

4. Measured according to JESD65B.

Table 5. Electrical Characteristics – HCSL Specific

| Parameter                                    | Symbol              | Min.  | Typ.  | Max.  | Unit | Condition   |
|--|---------------------|-------|-------|-------|------|---|
| Current Consumption                          |                     |       |       |       |      |   |
| Current Consumption                          | I <sub>dd</sub>     | –     | –     | 97    | mA   | Excluding Load Termination Current, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| OE Disable Supply Current                    | I <sub>OE</sub>     | –     | –     | 63    | mA   | OE = Low  |
| Output Disable Leakage Current               | I <sub>leak</sub>   | –     | 0.15  | –     | μA   | OE = Low  |
| Maximum Output Current                       | I <sub>driver</sub> | –     | –     | 35    | mA   | Maximum average current drawn from OUT+ or OUT-   |
| Output Characteristics                       |                     |       |       |       |      |   |
| Output High Voltage                          | VOH                 | 0.60  | –     | 0.90  | V    | See <a href="#">Figure 4</a>  |
| Output Low Voltage                           | VOL                 | -0.05 | –     | 0.08  | V    | See <a href="#">Figure 4</a>  |
| Output Differential Voltage Swing            | V <sub>Swing</sub>  | 1.2   | 1.4   | 1.9   | V    | See <a href="#">Figure 5</a>  |
| Rise/Fall Time                               | Tr, Tf              | –     | 360   | 505   | ps   | Measured with 2 pF capacitive loading to GND, 20% to 80%, see <a href="#">Figure 4</a>  |
| Jitter – 7.0 x 5.0 mm Package                |                     |       |       |       |      |   |
| RMS Period Jitter <sup>[5]</sup>             | T <sub>jitt</sub>   | –     | 1.0   | 1.6   | ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>    | –     | 0.215 | 0.265 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40 to 85°C        |
|  |                     | –     | 0.215 | 0.282 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature range ranges -40 to 95°C and -40 to 105°C |
|  |                     | –     | 0.1   | –     | ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz, Includes spurs, all V <sub>dd</sub> levels                    |
| Jitter – 5.0 x 3.2 and 3.2 x 2.5 mm Packages |                     |       |       |       |      |   |
| RMS Period Jitter <sup>[5]</sup>             | T <sub>jitt</sub>   | –     | 1.0   | 1.6   | ps   | f = 100, 156.25 or 212.5 MHz, V <sub>dd</sub> = 3.3 V or 2.5 V  |
| RMS Phase Jitter (random)                    | T <sub>phj</sub>    | –     | 0.235 | 0.282 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -20 to 70°C and -40 to 85°C        |
|  |                     | –     | 0.235 | 0.305 | ps   | f = 322.265625 MHz, Integration bandwidth = 12 kHz to 20 MHz, all V <sub>dd</sub> levels, includes spurs. Temperature ranges -40 to 95°C and -40 to 105°C       |
|  |                     | –     | 0.1   | –     | ps   | f = 322.265625 MHz, IEEE802.3-2005 10GbE jitter mask integration bandwidth = 1.875 MHz to 20 MHz, Includes spurs for all V <sub>dd</sub> levels.                |

**Note:**

5. Measured according to JESD65B.

Table 6. Pin Description

| Pin | Map   | Functionality      |  |
|-----|-------|--------------------|--|
| 1   | OE/NC | Output Enable (OE) | H <sup>[6]</sup> : specified frequency output<br>L: output is high impedance |
|     |       | Non Connect (NC)   | H or L or Open: No effect on output frequency or other device functions.     |
| 2   | NC    | NA                 | No Connect; Leave it floating or connect to GND for better heat dissipation  |
| 3   | GND   | Power              | VDD Power Supply Ground  |
| 4   | OUT+  | Output             | Oscillator output  |
| 5   | OUT-  | Output             | Complementary oscillator output  |
| 6   | VDD   | Power              | Power supply voltage <sup>[7]</sup>  |

**Notes:**

6. In OE mode, a pull-up resistor of 10 kΩ or less is recommended if pin 1 is not externally driven.  
 7. A capacitor of value 0.1 μF or higher between VDD and GND is required. An additional 10 μF capacitor between VDD and GND is required for the best phase jitter performance.




Figure 3. Pin Assignments

**Table 7. Absolute Maximum Ratings**

**Caution:** Attempted operation outside the absolute maximum ratings may cause permanent damage to the part. Actual performance of the IC is only guaranteed within the operational specifications, not at absolute maximum ratings.

| Parameter  | Min. | Max.       | Unit |
|--|------|------------|------|
| Vdd  | -0.5 | 4.0        | V    |
| VIH  |      | Vdd + 0.3V | V    |
| VIL  | -0.3 |            | V    |
| Storage Temperature  | -65  | 150        | °C   |
| Maximum Junction Temperature   |      | 130        | °C   |
| Soldering Temperature (follow standard Pb-free soldering guidelines) |      | 260        | °C   |

**Table 8. Thermal Considerations<sup>[8]</sup>**

| Package     | $\theta_{JA}$ , 4 Layer Board (°C/W) | $\theta_{JC}$ , Bottom (°C/W) |
|-------------|--------------------------------------|-------------------------------|
| 3225, 6-pin | 80                                   | 30                            |
| 5032, 6-pin | 53                                   | 20                            |
| 7050, 6-pin | 52                                   | 19                            |

**Notes:**

8. Refer to JESD51 for  $\theta_{JA}$  and  $\theta_{JC}$  definitions, and reference layout used to determine the  $\theta_{JA}$  and  $\theta_{JC}$  values in the above table.

**Table 9. Maximum Operating Junction Temperature<sup>[9]</sup>**

| Max Operating Temperature (ambient) | Maximum Operating Junction Temperature |
|-------------------------------------|--|
| 70°C                                | 95°C                                   |
| 85°C                                | 110°C                                  |
| 95°C                                | 120°C                                  |
| 105°C                               | 130°C                                  |

**Notes:**


9. Datasheet specifications are not guaranteed if junction temperature exceeds the maximum operating junction temperature.

**Table 10. Environmental Compliance**


| Parameter  | Test Conditions           | Value  | Unit     |
|--|---------------------------|--------|----------|
| Mechanical Shock Resistance  | MIL-STD-883F, Method 2002 | 10,000 | <i>g</i> |
| Mechanical Vibration Resistance                                      | MIL-STD-883F, Method 2007 | 70     | <i>g</i> |
| Soldering Temperature (follow standard Pb free soldering guidelines) | MIL-STD-883F, Method 2003 | 260    | °C       |
| Moisture Sensitivity Level   | MSL1 @ 260°C              |        |          |
| Electrostatic Discharge (HBM)  | HBM, JESD22-A114          | 2,000  | V        |
| Charge-Device Model ESD Protection                                   | JESD220C101               | 750    | V        |
| Latch-up Tolerance   | JESD78 Compliant          |        |          |



## Waveform Diagrams



**Figure 4. LVPECL, Low-swing LVPECL, and HCSL Voltage Levels per Differential Pin (i.e. OUT+, or OUT-)**



**Figure 5. LVPECL, Low-swing LVPECL, and HCSL Voltage Levels Across Differential Pair (i.e. OUT+ minus OUT-)**

## Waveform Diagrams (continued)




Figure 6. LVDS Voltage Levels per Differential Pin (i.e. OUT+, or OUT-)




Figure 7. LVDS Differential Waveform (i.e. OUT+ minus OUT-)

## Timing Diagrams




Figure 8. Hardware OE Enable Timing






Figure 9. Hardware OE Disable Timing

## Termination Diagrams


### LVPECL and Low-swing LVPECL




**Figure 10. LVPECL and Low-swing LVPECL with AC-coupled Termination**



**Figure 11. LVPECL and Low-swing LVPECL DC-coupled Load Termination with Thevenin Equivalent Network**




**Figure 12. LVPECL and Low-swing LVPECL with Y-Bias Termination**




**Figure 13. LVPECL and Low-swing LVPECL with DC-coupled Parallel Shunt Load Termination**

## Termination Diagrams (continued)


### LVDS



**Figure 14. LVDS Single DC Termination at the Load**




**Figure 15. LVDS double AC Termination with Capacitor Close to the Load**



**Figure 16. LVDS Double DC Termination**

### HCSL



**Figure 17. HCSL Interface Termination**

Dimensions and Patterns — 3.2 x 2.5 mm<sup>2</sup>

# Package Size – Dimensions (Unit: mm)<sup>[10]</sup>

# Recommended Land Pattern (Unit: mm)<sup>[11]</sup>

3.2 x 2.5 x 0.85 mm

3.2 x 2.5 x 0.85 mm

Technical drawings of the 3.2 x 2.5 x 0.85 mm package showing Top, Bottom, and Side views with dimension callouts.

- TOP VIEW:** Shows overall dimensions A, B, C, D, E, and a callout for PIN1.
- BOTTOM VIEW:** Shows dimensions b, e, L, L1, P, T, and A1.
- SIDE VIEW:** Shows dimensions A, A1, A2, and A3.

|                   | SYMBOL | MIN   | NOM       | MAX   |
|-------------------|--------|-------|-----------|-------|
| TOTAL THICKNESS   | A      | 0.800 | 0.850     | 0.900 |
| STAND OFF         | A1     | 0.000 | 0.035     | 0.050 |
| BODY SIZE         | X      | D     | 3.200 BSC |       |
|                   | Y      | E     | 2.500 BSC |       |
| LEAD WIDTH        | b      | 0.550 | 0.600     | 0.650 |
| LEAD LENGTH       | L      | 0.650 | 0.700     | 0.750 |
|                   | L1     |       | 0.800 REF |       |
| LEAD PITCH        | e      |       | 1.100 BSC |       |
| PACKAGE TOLERANCE | aaa    |       | 0.100     |       |
| MOLD FLATNESS     | bbb    |       | 0.100     |       |
| COPLANARITY       | ccc    |       | 0.080     |       |
| DIMPLE WIDTH      | T      |       | 0.150 REF |       |
| DIMPLE LENGTH     | P      |       | 0.150 REF |       |
| DIMPLE DEPTH      | A2     |       | 0.100 REF |       |

Notes






1. All dimensions are in millimeters

Recommended land pattern diagram showing dimensions 2.25, 1.6, 0.65, 1.05, and 1.00.

## Package Outline

|                      |                         |
|----------------------|-------------------------|
| 6L PQFD              | POD-038-PQFD-004-C03225 |
| 3.200x2.500x0.850 mm |                         |
| 2020/09/23 Rev C00   |                         |






Dimensions and Patterns — 5.0 x 3.2 mm<sup>2</sup>

| Package Size – Dimensions (Unit: mm) <sup>[10]</sup>   |   | Recommended Land Pattern (Unit: mm) <sup>[11]</sup>                                   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
|--|---|---|-----------|---------|-------------------------|----------------------|---|--------------------|-------|-------|-------|-----------|----|-------|-------|-------|-----------|---|---|-----------|--|---|---|-----------|--|---------|---|---|-------|-------|---|---|-------|-------|------------|---|-------|-------|-------|-------------|---|-------|-------|-------|----|--|-----------|--|------------|---|--|-----------|--|-------------------|-----|--|-------|--|---------------|-----|--|-------|--|-------------|-----|--|-------|--|--------------|---|--|-----------|--|---------------|---|--|-----------|--|--------------|----|--|-----------|--|--|--|
| 5.0 x 3.2 x 0.85 mm <sup>[12]</sup>  |   | 5.0 x 3.2 x 0.85 mm <sup>[12]</sup>   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
|   |   |  |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| <table><tr><th></th><th>SYMBOL</th><th>MIN</th><th>NOM</th><th>MAX</th></tr><tr><td>TOTAL THICKNESS</td><td>A</td><td>0.800</td><td>0.850</td><td>0.900</td></tr><tr><td>STAND OFF</td><td>A1</td><td>0.000</td><td>0.035</td><td>0.050</td></tr><tr><td rowspan="2">BODY SIZE</td><td>X</td><td>D</td><td>5.000 BSC</td><td></td></tr><tr><td>Y</td><td>E</td><td>3.200 BSC</td><td></td></tr><tr><td rowspan="2">EP SIZE</td><td>X</td><td>J</td><td>3.100</td><td>3.200</td></tr><tr><td>Y</td><td>K</td><td>0.500</td><td>0.600</td></tr><tr><td>LEAD WIDTH</td><td>b</td><td>0.590</td><td>0.640</td><td>0.690</td></tr><tr><td rowspan="2">LEAD LENGTH</td><td>L</td><td>0.850</td><td>0.900</td><td>0.950</td></tr><tr><td>L1</td><td></td><td>1.000 REF</td><td></td></tr><tr><td>LEAD PITCH</td><td>e</td><td></td><td>1.270 BSC</td><td></td></tr><tr><td>PACKAGE TOLERANCE</td><td>aaa</td><td></td><td>0.100</td><td></td></tr><tr><td>MOLD FLATNESS</td><td>bbb</td><td></td><td>0.100</td><td></td></tr><tr><td>COPLANARITY</td><td>ccc</td><td></td><td>0.080</td><td></td></tr><tr><td>DIMPLE WIDTH</td><td>T</td><td></td><td>0.300 REF</td><td></td></tr><tr><td>DIMPLE LENGTH</td><td>P</td><td></td><td>0.150 REF</td><td></td></tr><tr><td>DIMPLE DEPTH</td><td>A2</td><td></td><td>0.100 REF</td><td></td></tr></table> <p>Notes<br/>1. Dimensioning and tolerancing conform to ASME Y14.5-2009<br/>2. All dimensions are in millimeters</p> |   |   | SYMBOL    | MIN     | NOM                     | MAX                  | TOTAL THICKNESS   | A                  | 0.800 | 0.850 | 0.900 | STAND OFF | A1 | 0.000 | 0.035 | 0.050 | BODY SIZE | X | D | 5.000 BSC |  | Y | E | 3.200 BSC |  | EP SIZE | X | J | 3.100 | 3.200 | Y | K | 0.500 | 0.600 | LEAD WIDTH | b | 0.590 | 0.640 | 0.690 | LEAD LENGTH | L | 0.850 | 0.900 | 0.950 | L1 |  | 1.000 REF |  | LEAD PITCH | e |  | 1.270 BSC |  | PACKAGE TOLERANCE | aaa |  | 0.100 |  | MOLD FLATNESS | bbb |  | 0.100 |  | COPLANARITY | ccc |  | 0.080 |  | DIMPLE WIDTH | T |  | 0.300 REF |  | DIMPLE LENGTH | P |  | 0.150 REF |  | DIMPLE DEPTH | A2 |  | 0.100 REF |  |  |  |
|  | SYMBOL  | MIN   | NOM       | MAX     |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| TOTAL THICKNESS  | A   | 0.800   | 0.850     | 0.900   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| STAND OFF  | A1  | 0.000   | 0.035     | 0.050   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| BODY SIZE  | X   | D   | 5.000 BSC |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
|  | Y   | E   | 3.200 BSC |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| EP SIZE  | X   | J   | 3.100     | 3.200   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
|  | Y   | K   | 0.500     | 0.600   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| LEAD WIDTH   | b   | 0.590   | 0.640     | 0.690   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| LEAD LENGTH  | L   | 0.850   | 0.900     | 0.950   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
|  | L1  |   | 1.000 REF |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| LEAD PITCH   | e   |   | 1.270 BSC |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| PACKAGE TOLERANCE  | aaa   |   | 0.100     |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| MOLD FLATNESS  | bbb   |   | 0.100     |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| COPLANARITY  | ccc   |   | 0.080     |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| DIMPLE WIDTH   | T   |   | 0.300 REF |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| DIMPLE LENGTH  | P   |   | 0.150 REF |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| DIMPLE DEPTH   | A2  |   | 0.100 REF |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| <table><tr><th colspan="2">Package Outline</th></tr><tr><td>6L PQFV</td><td>POD-PQFV-004-C05032-039</td></tr><tr><td>5.000x3.200x0.850 mm</td><td></td></tr><tr><td>2019/03/13 Rev B00</td><td></td></tr></table>   |   | Package Outline   |           | 6L PQFV | POD-PQFV-004-C05032-039 | 5.000x3.200x0.850 mm |  | 2019/03/13 Rev B00 |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| Package Outline  |   |   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| 6L PQFV  | POD-PQFV-004-C05032-039   |   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| 5.000x3.200x0.850 mm   |  |   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |
| 2019/03/13 Rev B00   |   |   |           |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |           |  |   |   |           |  |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |    |  |           |  |            |   |  |           |  |                   |     |  |       |  |               |     |  |       |  |             |     |  |       |  |              |   |  |           |  |               |   |  |           |  |              |    |  |           |  |  |  |

## Notes:

- Top Marking: Y denotes manufacturing origin and XXXX denotes manufacturing lot number. The value of “Y” will depend on the assembly location of the device.
- A capacitor of value 0.1  $\mu$ F or higher between VDD and GND is required. An additional 10  $\mu$ F capacitor between VDD and GND is required for the best phase jitter performance.
- The center pad has no electrical function. Soldering down the center pad to the GND is recommended for best thermal dissipation, but is optional.

## Dimensions and Patterns — 7.0 x 5.0 mm<sup>2</sup>

| Package Size – Dimensions (Unit: mm) <sup>[13]</sup>   |   | Recommended Land Pattern (Unit: mm) <sup>[14]</sup>                                 |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
|--|---|---|--------|---------|-------------------------|----------------------|---|--------------------|-------|-------|-------|-----------|----|-------|-------|-------|-----------|---|---|-------|-----|---|---|-------|-----|---------|---|---|-------|-------|---|---|-------|-------|------------|---|-------|-------|-------|-------------|---|-------|-------|-------|------------|----|-------|-----|--|------------|---|-------|-----|--|-------------------|-----|-------|--|--|---------------|-----|-------|--|--|-------------|-----|-------|--|--|--------------|---|-------|-----|--|---------------|---|-------|-----|--|--------------|----|-------|-----|--|---|
| 7.0 x 5.0 x 0.85 mm <sup>[15]</sup>  |   | 7.0 x 5.0 x 0.85 mm <sup>[15]</sup>   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
|   |   |  |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| <table><tr><th></th><th>SYMBOL</th><th>MIN</th><th>NOM</th><th>MAX</th></tr><tr><td>TOTAL THICKNESS</td><td>A</td><td>0.800</td><td>0.850</td><td>0.900</td></tr><tr><td>STAND OFF</td><td>A1</td><td>0.000</td><td>0.035</td><td>0.050</td></tr><tr><td rowspan="2">BODY SIZE</td><td>X</td><td>D</td><td>7.000</td><td>BSC</td></tr><tr><td>Y</td><td>E</td><td>5.000</td><td>BSC</td></tr><tr><td rowspan="2">EP SIZE</td><td>X</td><td>J</td><td>3.400</td><td>3.500</td></tr><tr><td>Y</td><td>K</td><td>1.400</td><td>1.500</td></tr><tr><td>LEAD WIDTH</td><td>b</td><td>1.350</td><td>1.400</td><td>1.450</td></tr><tr><td>LEAD LENGTH</td><td>L</td><td>0.850</td><td>0.900</td><td>0.950</td></tr><tr><td>LEAD PITCH</td><td>L1</td><td>1.000</td><td>REF</td><td></td></tr><tr><td>LEAD PITCH</td><td>e</td><td>2.540</td><td>BSC</td><td></td></tr><tr><td>PACKAGE TOLERANCE</td><td>aaa</td><td>0.100</td><td></td><td></td></tr><tr><td>MOLD FLATNESS</td><td>bbb</td><td>0.100</td><td></td><td></td></tr><tr><td>COPLANARITY</td><td>ccc</td><td>0.080</td><td></td><td></td></tr><tr><td>DIMPLE WIDTH</td><td>T</td><td>0.300</td><td>REF</td><td></td></tr><tr><td>DIMPLE LENGTH</td><td>P</td><td>0.150</td><td>REF</td><td></td></tr><tr><td>DIMPLE DEPTH</td><td>A2</td><td>0.100</td><td>REF</td><td></td></tr></table> <p>Notes</p> <ol style="list-style-type: none"><li>Dimensioning and tolerancing conform to ASME Y14.5-2009</li><li>All dimensions are in millimeters</li></ol> |   |   | SYMBOL | MIN     | NOM                     | MAX                  | TOTAL THICKNESS   | A                  | 0.800 | 0.850 | 0.900 | STAND OFF | A1 | 0.000 | 0.035 | 0.050 | BODY SIZE | X | D | 7.000 | BSC | Y | E | 5.000 | BSC | EP SIZE | X | J | 3.400 | 3.500 | Y | K | 1.400 | 1.500 | LEAD WIDTH | b | 1.350 | 1.400 | 1.450 | LEAD LENGTH | L | 0.850 | 0.900 | 0.950 | LEAD PITCH | L1 | 1.000 | REF |  | LEAD PITCH | e | 2.540 | BSC |  | PACKAGE TOLERANCE | aaa | 0.100 |  |  | MOLD FLATNESS | bbb | 0.100 |  |  | COPLANARITY | ccc | 0.080 |  |  | DIMPLE WIDTH | T | 0.300 | REF |  | DIMPLE LENGTH | P | 0.150 | REF |  | DIMPLE DEPTH | A2 | 0.100 | REF |  | <p><b>Note:</b></p> <p>Circles in center pad are thermal vias, recommended to improve thermal performance</p> |
|  | SYMBOL  | MIN   | NOM    | MAX     |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| TOTAL THICKNESS  | A   | 0.800   | 0.850  | 0.900   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| STAND OFF  | A1  | 0.000   | 0.035  | 0.050   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| BODY SIZE  | X   | D   | 7.000  | BSC     |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
|  | Y   | E   | 5.000  | BSC     |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| EP SIZE  | X   | J   | 3.400  | 3.500   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
|  | Y   | K   | 1.400  | 1.500   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| LEAD WIDTH   | b   | 1.350   | 1.400  | 1.450   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| LEAD LENGTH  | L   | 0.850   | 0.900  | 0.950   |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| LEAD PITCH   | L1  | 1.000   | REF    |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| LEAD PITCH   | e   | 2.540   | BSC    |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| PACKAGE TOLERANCE  | aaa   | 0.100   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| MOLD FLATNESS  | bbb   | 0.100   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| COPLANARITY  | ccc   | 0.080   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| DIMPLE WIDTH   | T   | 0.300   | REF    |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| DIMPLE LENGTH  | P   | 0.150   | REF    |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| DIMPLE DEPTH   | A2  | 0.100   | REF    |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| <table><tr><th colspan="2">Package Outline</th></tr><tr><td>6L PQFV</td><td>PQD-PQFV-004-C07050-037</td></tr><tr><td>7.000x5.000x0.850 mm</td><td></td></tr><tr><td>2019/03/13 Rev 800</td><td></td></tr></table>   |   | Package Outline   |        | 6L PQFV | PQD-PQFV-004-C07050-037 | 7.000x5.000x0.850 mm |  | 2019/03/13 Rev 800 |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| Package Outline  |   |   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| 6L PQFV  | PQD-PQFV-004-C07050-037   |   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| 7.000x5.000x0.850 mm   |  |   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |
| 2019/03/13 Rev 800   |   |   |        |         |                         |                      |   |                    |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |         |   |   |       |       |   |   |       |       |            |   |       |       |       |             |   |       |       |       |            |    |       |     |  |            |   |       |     |  |                   |     |       |  |  |               |     |       |  |  |             |     |       |  |  |              |   |       |     |  |               |   |       |     |  |              |    |       |     |  |   |

### Notes:

- Top Marking: Y denotes manufacturing origin and XXXX denotes manufacturing lot number. The value of “Y” will depend on the assembly location of the device.
- A capacitor of value 0.1  $\mu$ F or higher between VDD and GND is required. An additional 10  $\mu$ F capacitor between VDD and GND is required for the best phase jitter performance.
- The center pad has no electrical function. Soldering down the center pad to the GND is recommended for best thermal dissipation, but is optional.

## Additional Information

**Table 11. Additional Information**

| Document                                     | Description  | Download Link   |
|--|--|---|
| <b>ECCN #: EAR99</b>                         | Five character designation used on the commerce Control List (CCL) to identify dual use items for export control purposes.           | —   |
| <b>HTS Classification Code: 8542.39.0000</b> | A Harmonized Tariff Schedule (HTS) code developed by the World Customs Organization to classify/define internationally traded goods. | —   |
| <b>Part number Generator</b>                 | Tool used to create the part number based on desired features.   | —   |
| <b>Manufacturing Notes</b>                   | Tape & Reel dimension, reflow profile and other manufacturing related info   | <a href="https://www.sitime.com/sites/default/files/gated/Manufacturing-Notes-for-SiTime-Products.pdf">https://www.sitime.com/sites/default/files/gated/Manufacturing-Notes-for-SiTime-Products.pdf</a> |
| <b>Qualification Reports</b>                 | RoHS report, reliability reports, composition reports  | <a href="http://www.sitime.com/support/quality-and-reliability">http://www.sitime.com/support/quality-and-reliability</a>   |
| <b>Performance Reports</b>                   | Additional performance data such as phase noise, current consumption and jitter for selected frequencies                             | <a href="http://www.sitime.com/support/performance-measurement-report">http://www.sitime.com/support/performance-measurement-report</a>   |
| <b>Termination Techniques</b>                | Termination design recommendations   | <a href="http://www.sitime.com/support/application-notes">http://www.sitime.com/support/application-notes</a>   |
| <b>Layout Techniques</b>                     | Layout recommendations   | <a href="http://www.sitime.com/support/application-notes">http://www.sitime.com/support/application-notes</a>   |
| <b>Evaluation Boards</b>                     | SiT6085/6EB rev. 3.0, SiT6085EB rev.3.1 and SiT6097EB rev. 2.0 Evaluation Boards for Differential Oscillators User Manual            | <a href="https://www.sitime.com/support/user-guides">https://www.sitime.com/support/user-guides</a>   |

## Revision History

**Table 12. Revision History**

| Revision | Release Date | Change Summary   |
|----------|--------------|--|
| 0.5      | 22-Jul-2019  | Initial draft  |
| 1.00     | 16-Feb-2021  | Updated package Dimensions Drawings<br>Updated Table 8 Thermal Considerations for 5032 package<br>Updated Table 2 specification for First Year Aging<br>Added 5, 10, and 20 year aging specs<br>Added Evaluation Boards SiT6085EB reference in Additional Information<br>Rearranged layout, added Description, Block Diagram and TOC<br>Tightened LVDS minimum VOD specification<br>Added HTS code<br>Added low-swing LVPECL package code and specifications<br>Fixed Ordering typo, updated trademarks, date format, other formatting changes |
| 1.01     | 17-Mar-2021  | Updated L1 and Dimple Width package dimensions for 3.2 x 2.5 mm package  |
| 1.02     | 21-Nov-2022  | Updated Ordering packaging information with F option<br>Updated hyperlinks and icons on page 1. Disclaimer update  |

**SiTime Corporation**, 5451 Patrick Henry Drive, Santa Clara, CA 95054, USA | **Phone:** +1-408-328-4400 | **Fax:** +1-408-328-4439

© SiTime Corporation 2019-2023. The information contained herein is subject to change at any time without notice. SiTime assumes no responsibility or liability for any loss, damage or defect of a Product which is caused in whole or in part by (i) use of any circuitry other than circuitry embodied in a SiTime product, (ii) misuse or abuse including static discharge, neglect or accident, (iii) unauthorized modification or repairs which have been soldered or altered during assembly and are not capable of being tested by SiTime under its normal test conditions, or (iv) improper installation, storage, handling, warehousing or transportation, or (v) being subjected to unusual physical, thermal, or electrical stress.

**Disclaimer:** SiTime makes no warranty of any kind, express or implied, with regard to this material, and specifically disclaims any and all express or implied warranties, either in fact or by operation of law, statutory or otherwise, including the implied warranties of merchantability and fitness for use or a particular purpose, and any implied warranty arising from course of dealing or usage of trade, as well as any common-law duties relating to accuracy or lack of negligence, with respect to this material, any SiTime product and any product documentation. This product is not suitable or intended to be used in a life support application or component or to operate nuclear facilities, or in other applications where human life may be involved or at stake. All sales are made conditioned upon compliance with the critical uses policy set forth below.

### CRITICAL USE EXCLUSION POLICY

BUYER AGREES NOT TO USE SITIME'S PRODUCTS FOR ANY APPLICATION OR IN ANY COMPONENTS USED IN LIFE SUPPORT DEVICES OR TO OPERATE NUCLEAR FACILITIES OR FOR USE IN OTHER APPLICATIONS OR COMPONENTS WHERE HUMAN LIFE OR PROPERTY MAY BE AT STAKE.

SiTime owns all rights, title and interest to the intellectual property related to SiTime's products, including any software, firmware, copyright, patent, or trademark. The sale of SiTime products does not convey or imply any license under patent or other rights. SiTime retains the copyright and trademark rights in all documents, catalogs and plans supplied pursuant to or ancillary to the sale of products or services by SiTime. Unless otherwise agreed to in writing by SiTime, any reproduction, modification, translation, compilation, or representation of this material shall be strictly prohibited.