


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00425	Connector, plug, USB A	1	
2	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
3	30-00008	Wire, 2C BC, 22 AWG, UL2468, 300V, 80C, 3.6 mm, PVC, 87A	1	
4	24-00023	Overmold, PVC, black	1	
5	24-00043	Overmold, PVC, black	1	
6	Label 241	Adhesive, flag, 15x65 mm	1	



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	11/10/2009	Initial release	GL 2016.02.05 15:13:02 -08'00'	RoHS compliant	
A1	3/16/2010	Added label drawing	Verified: LA Digitally signed by LA DN: cn=LA, o=Tensility, ou=Engineering, email=LA@tensility.com, c=US Date: 2016.02.12 11:28:06 -08'00'	Function test: no open, no short circuit, no intermittent	
A2	9/6/2011	Updated specifications	Dimensions are in millimeters.	Description:	
A3	8/8/2012	Added label specs an added wire part number	Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, USB A plug to 5.5x2.1x12 mm 50-00024 plug, center neg, 22 AWG, UL2468, 30-00008 wire	
Size: A Part number: 10-00241 Scale: 1:1					Sheet 1 of 1